

Product Category : Concrete Anchor Systems

MATERIAL : 1018M00440 Conc Anchor System, Injection, Sz 3/8

APS00003510 — Adhesives Technology Corp. - Pompano Beach, FL **Phone : 954-782-2221** **Ext. # : 177**
450 East Copans Road **Fax : 954-782-2499**
Pompano Beach, FL 33064 **Contact : Susan Bogdan**

<u>Product</u>	<u>Approved On</u>	<u>Remarks</u>
Ultrabond 1300 - 3/8 - AdhesivesTech	8-18-2003	Approx. Cure Time: Refer to product data Min. Embedment mm (in): 88.9 (3 1/2) Working Loads, Pull-Out, kN (lbs): 11.3 (2531) Working Loads, Shear, kN (lbs): 7.8 (1759)
Ultrabond 2300 - 3/8 - AdhesivesTech	8-18-2003	Approx. Cure Time: Refer to product data Min. Embedment mm (in): 88.9 (3 1/2) Working Loads, Pull-Out, kN (lbs): 10.8 (2342) Working Loads, Shear, kN (lbs): 7.8 (1759)

MATERIAL : Conc Anchor System, Injection, Sz 3/4

APS00003510 — Adhesives Technology Corp. - Pompano Beach, FL **Phone : 954-782-2221** **Ext. # : 177**
450 East Copans Road **Fax : 954-782-2499**
Pompano Beach, FL 33064 **Contact : Susan Bogdan**

<u>Product</u>	<u>Approved On</u>	<u>Remarks</u>
Ultrabond 1300 - 3/4 - AdhesivesTech	8-18-2003	Approx. Cure Time: Refer to product data Min. Embedment mm (in): 171.5 (6 3/4) Working Loads, Pull-Out, kN (lbs): 29.9 (6716) Working Loads, Shear, kN (lbs): 28.6 (6433)
Ultrabond 2300 - 3/4 - AdhesivesTech	8-18-2003	Approx. Cure Time: Refer to product data Min. Embedment mm (in): 171.5 (6 3/4) Working Loads, Pull-Out, kN (lbs): 33.6 (7552) Working Loads, Shear, kN (lbs): 28.6 (6433)

MATERIAL : Conc Anchor System, Injection, Sz 1/2

APS00003510 — Adhesives Technology Corp. - Pompano Beach, FL **Phone : 954-782-2221** **Ext. # : 177**
450 East Copans Road **Fax : 954-782-2499**
Pompano Beach, FL 33064 **Contact : Susan Bogdan**

<u>Product</u>	<u>Approved On</u>	<u>Remarks</u>
Ultrabond 1300 - 1/2 - AdhesivesTech	8-18-2003	Approx. Cure Time: Refer to product data Min. Embedment mm (in): 114.3 (4 1/2) Working Loads, Pull-Out, kN (lbs): 16.1 (3628) Working Loads, Shear, kN (lbs): 11.5 (2595)
Ultrabond 2300 - 1/2 - AdhesivesTech	8-18-2003	Approx. Cure Time: Refer to product data Min. Embedment mm (in): 114.3 (4 1/2) Working Loads, Pull-Out, kN (lbs): 16.3 (3678) Working Loads, Shear, kN (lbs): 11.5 (2595)