

Crack Repair

TABLE 1: Crack repair usage estimating guide for CRACKBOND EPOXY REPAIR PASTE¹

Approximate Coverage Rates Linear Feet (Linear Meters)				
Crack Width in. (cm)	Crack Depth in. (cm)	Package Size		
		22 fl. oz. (473 ml)	102 fl. oz. (3.2 L)	3 Gal (56.8L)
1/16 in. or 0.0625 (0.159)	0.25 (0.6)	202.1 (61.6)	982 (299.2)	3,696 (1,127)
	0.375 (1.0)	134.8 (41.1)	655 (199.5)	2,464 (751.0)
	0.5 (1.3)	101.1 (30.8)	491 (149.6)	1,848 (563.3)
	0.75 (1.9)	67.4 (20.5)	327 (99.7)	1,232 (375.5)
1/8 in. or 0.1250 (0.318)	0.25 (0.6)	101.1 (30.8)	491 (149.6)	1,848 (563)
	0.375 (1.0)	67.4 (20.5)	327 (99.7)	1,232 (375.5)
	0.5 (1.3)	50.5 (15.4)	245 (74.8)	924 (281.6)
	0.75 (1.9)	33.7 (10.3)	164 (49.9)	616 (187.8)
3/16 in. or 0.1875 (0.476)	0.25 (0.6)	67.4 (20.5)	327 (99.7)	1,232 (376)
	0.375 (1.0)	44.9 (13.7)	218 (66.5)	821 (250.3)
	0.5 (1.3)	33.7 (10.3)	164 (49.9)	616 (187.8)
	0.75 (1.9)	22.5 (6.8)	109 (33.2)	411 (125.2)
1/4 in. or 0.25 (0.635)	0.25 (0.6)	50.5 (15.4)	245 (74.8)	924 (282)
	0.375 (1.0)	33.7 (10.3)	164 (49.9)	616 (187.8)
	0.5 (1.3)	25.3 (7.7)	123 (37.4)	462 (140.8)
	0.75 (1.9)	16.8 (5.1)	82 (24.9)	308 (93.9)
3/8 in. or 0.3750 (0.953)	0.25 (0.6)	33.7 (10.3)	164 (49.9)	616 (188)
	0.375 (1.0)	22.5 (6.8)	109 (33.2)	411 (125.2)
	0.5 (1.3)	16.8 (5.1)	82 (24.9)	308 (93.9)
	0.75 (1.9)	11.2 (3.4)	55 (16.6)	205 (62.6)
1/2 in. or 0.50 (1.270)	0.25 (0.6)	25.3 (7.7)	123 (37.4)	462 (141)
	0.375 (1.0)	16.8 (5.1)	82 (24.9)	308 (93.9)
	0.5 (1.3)	12.6 (3.9)	61 (18.7)	231 (70.4)
	0.75 (1.9)	8.4 (2.6)	41 (12.5)	154 (46.9)

1. Values are approximate and may vary depending on waste, concrete and user technique.