

SAFETY DATA SHEET

Version: 2 Issue Date: 6-26-2015 Revision Date: 4-24-2023

ASI 502 Clear

Section 1: Product and Company Identification

American Sealants, Inc. Emergency Phone Number

9190 Yeager Ln Infotrac: +1-800-535-5053 (Within US)

Fort Wayne, Indiana 46809 Infotrac: +1-352-323-3500 (Outside US)

Phone: 260-489-0728 Fax: 260-489-0519

Product Identifier: ASI 502 Clear

Recommended Use: Adhesive, binding agents

Restrictions on Use: None known

Section 2: Hazard(s) Identification

Hazard Classification

This product is not hazardous under the criteria of the Hazardous Products Regulation (HPR) as implemented under the Workplace Hazardous Materials Information System (WHMIS 2015).

Label Elements

Precautionary Statements

Prevention Use only outdoors or in a well-ventilated area.

Other hazards

No data available

Section 3: Composition/Information on Ingredients

Chemical Nature: Silicone elastomer

This product is a mixture.

Contains no hazardous ingredients according to GHS

Section 4: First-Aid Measures

Description of first aid measures

General advice:

SAFTEY DATA SHEET

Product Identifier: ASI 502 Clear Version: 2

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the

initial 1-2 minutes and continue flushing for several additional minutes. If effects occur.

consult a physician, preferably an ophthalmologist.

Ingestion: Rinse mouth with water. No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of

symptoms and the clinical condition of the patient. Skin contact may aggravate

preexisting dermatitis.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2) Dry

chemical.

Unsuitable Extinguishing

Media:

None known.

Special Hazards Arising from the substance or mixture

Hazardous combustion Carbon oxides. Silicon oxides.

products:

Unusual Fire and Explosion

Hazards:

Exposure to combustion products may be a hazard to health.

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers. Evacuate area. Fire

residues and contaminated fire extinguishing water must be disposed

of in accordance with local regulations.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment

for firefighters:

Wear self-contained breathing apparatus for firefighting if necessary.

Use personal protective equipment.

Section 6: Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Methods and Materials for

Containment and Cleaning Up:

Follow safe handling advice and personal protective equipment recommendations.

Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate

Issue Date: 6-26-2015 Page **2** of **8**

Product Identifier: ASI 502 Clear Version: 2

> containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

See sections: 7, 8, 11, 12 and 13.

Discharge into the environment must be avoided. Prevent further **Environment Precautions:**

leakage or spillage if safe to do so. Retain and dispose of

contaminated wash water. Local authorities should be advised if

significant spillages cannot be contained.

Section 7: Handling and Storage

Precautions for Safe Handling Take care to prevent spills, waste and minimize release to the

environment. Handle in accordance with good industrial hygiene and

safety practice.

Use only with adequate ventilation. See Engineering measures under

EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for Safe Storage, including

any Incompatibilities:

Keep in properly labelled containers. Store in accordance with the

particular national regulations.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: None known.

Section 8: Exposure Controls/Personal Protection

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable. Consult local authorities for recommended exposure limits.

Exposure controls

Use local exhaust ventilation, or other engineering controls to maintain airborne **Engineering controls:**

> levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some

operations.

Individual protection measures

Eve/face Use safety glasses (with side shields).

protection: Skin protection

> Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection:

Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated

Issue Date: 6-26-2015 Page 3 of 8

SAFTEY DATA SHEET

Product Identifier: ASI 502 Clear Version: 2

by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without

sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor

cartridge.

Section 9: Physical and Chemical Properties

Appearance Paste Color: Colorless

Odor: Acetic acid Odor Threshold: No data available

pH: Not applicable Melting Point/freezing Not applicable

point:

Initial boiling point and

boiling range:

Not applicable

Flash point:

Closed cup > 100 °C

Evaporation Rate: Not applicable Flammability (soild, gas) Not classified as a

flammability hazard

Upper/lower flammability

or explosive limits

Vapor Density (air = 1):

No data

Vapor Pressure:

Density:

1.007

Water Solubility No data available Partition Coefficient (n-

No data available

octanol/water)

No data available

Not applicable

Auto Ignition: No data available

Decomposition temperature

No data available

Dynamic viscosity Not applicable

Kinematic viscosity

Not applicable

Explosive properties Not explosive **Oxidizing properties** The substance or mixture

is not classified as

oxidizing

Molecular weight No data available Particle size

No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

Section 10: Stability and Reactivity

Reactivity:Not classified as a reactivity hazard **Chemical Stability:**Stable under normal conditions

Possibility of Hazardous Reactions: Can react with strong oxidizing agents. When heated to temperatures

above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required.

Conditions to Avoid: None known.

Incompatible Materials: Oxidizing agents

Hazardous Decomposition Products: Decomposition products can include and are not limited to:

Formaldehyde

Section 11: Toxicological Information

Issue Date: 6-26-2015 Page **4** of **8**

Product Identifier: ASI 502 Clear Version: 2

Toxicological information appears in this section when such data is available.

Information on likely routes of

Eye contact, skin contact, ingestion

exposure

Acute toxicity (represents short term exposures with immediate effects – no chronic/delayed effects known

unless otherwise noted)

Acute oral toxicity Very low if swallowed. Harmful effects not anticipated from swallowing

small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, >5,000 mg/kg Estimated

Acute dermal toxicity Prolonged skin contact is unlikely to result in absorption of harmful

amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, >2,000 mg/kg Estimated

Acute inhalation toxicity Brief exposure (minutes) is not likely to cause adverse effects. Vapor

from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

Skin corrosion/irritationBased on information for component(s):

Prolonged exposure not likely to cause significant skin irritation.

May cause drying and flaking of the skin.

Serious eye damage/irritation Based on information for component(s):

May cause slight temporary eye irritation.

May cause mild eye discomfort.

Sensitization For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in

guinea pigs.

For respiratory sensitization: No relevant information found.

Specific target organ toxicity-single

exposure

Evaluation of available data suggests that this material is not an STOT-SE

toxicant.

Specific Target Organ Toxicity –

Repeated Exposure:

Based on available data for the component(s), repeated exposures are not

anticipated to cause significant adverse effects.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects –

no immediate effects known unless otherwise noted)

Aspiration Hazard Based on physical properties, not likely to be an aspiration hazard.

Carcinogenicity No relevant data found

Teratogenicity Contains component(s) which did not cause birth defects or any other

fetal effects in lab animals.

Reproductive toxicity Contains component(s) which did not interfere with reproduction in

animal studies.

Issue Date: 6-26-2015 Page **5** of **8**

Product Identifier: ASI 502 Clear Version: 2

Mutagenicity In vitro genetic toxicity studies were negative for component(s) tested.

Genetic toxicity studies in animals were negative for component(s)

tested.

Section 12: Ecological Information

Ecotoxicological information appears in this section when such data is available.

ToxicityNo data availablePersistence and Degradability:No data availableBioaccumulative Potential:No data availableMobility in soilNo data available

Section 13: Disposal Considerations

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO

ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations.

Regulations may vary in different locations. Waste

characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section10 Regulatory Information,

MSDS Section 15

Treatment and disposal methods of used

packaging:

Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

Section 14: Transport Information

TDG

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk according to Annex Consult IMO regulations before transporting ocean bulk

II of MARPOL 73/78 and the IBC or

IGC Code

Classification for AIR transport (IATA/ICAO):

Issue Date: 6-26-2015 Page **6** of **8**

Product Identifier: ASI 502 Clear Version: 2

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Section 15: Regulatory Information

Canadian Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

Section 16: Other Information


Issue Date: 6-26-2015 Revision Date: 4-24-2023

Revision: 1

NFPA Ratings:

Health: 0

Fire: 1 Reactivity: 0



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS III:



0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

Key/Legend:

AICS (Australia); DSL (Canada); IECSC (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIoC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA PO – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits

Issue Date: 6-26-2015 Page **7** of **8**

SAFTEY DATA SHEET

Product Identifier: ASI 502 Clear Version: 2

(OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA P0 / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

End of Document

Issue Date: 6-26-2015 Page **8** of **8**