OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

| Identification

- · Product identifier
- · Trade name: ACCU-GROUT Part A
- Relevant identified uses of the substance or mixture and uses advised against
- · Product description Epoxy Grout
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Adhesives Technology Corp.

450 East Copans Rd.

Pompano Beach, FL 33064

(800) 892-1880 (800) 362-3320

Web: www.atcepoxy.com

Emergency telephone number:

CHEM-TEL (800) 255-3924 24/7

Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS07 GHS08 GHS09

- · Signal word Warning
- · Hazard-determining components of labeling:

Epoxy resin titanium dioxide

(Contd. on page 2)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 1)

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Toxic to aquatic life with long lasting effects.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

85 percent of the mixture consists of ingredient(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1

Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1

1 Fire = 1

REACTIVITY | Reactivity = 0

· Other hazards None known

3 Composition/information on ingredients

1317-61-9 Iron Oxide

2-12%

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 2)

· Dangerous Components:		
25068-38-6	Epoxy resin Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥85%
13463-67-7	titanium dioxide Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	5-10%

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek medical treatment.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, dry chemical, water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 3)

7 Handling and storage

- Handling:
- Precautions for safe handling

Avoid contact with skin, eyes and clothing

Do not take internally.

Use personal protection equipment as outlined in section 8.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool, dry place in tightly closed receptacles.

Store in a well ventilated place.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

13463-67-7 titanium dioxide

PEL Long-term value: 15* mg/m³

*total dust

REL See Pocket Guide App. A

TLV Long-term value: 10 mg/m³

withdrawn from NIC

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment: Suitable respiratory protective device recommended.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Tightly sealed goggles

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Grey
Odor: Mild

Odor threshold: Not determined.pH-value: Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Not determined.
Not determined.

248 °C (478 °F)
Flammability (solid, gaseous):
Not determined.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.Upper: Not determined.Vapor pressure: Not applicable.

• **Density** @ **20** °**C** (**68** °**F**): 1.14 g/cm³ (9.513 lbs/gal)

• Relative density
• Vapour density

Not determined.
>1 (Air=1)

• Evaporation rate Slower than n-butyl acetate

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strong oxidizing agents.

Strong acids, strong bases

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 5)

Amines

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin:

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

- · on the eye: Causes serious eye irritation.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
13463-67-7 titanium dioxide	2B
· NTP (National Toxicology Program)	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

* 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 01/21/2015 Printing date 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 6)

3 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Do not allow product to reach sewage system.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

- Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

4 Transport information

· UN-Number

· DOT Non-Regulated Material

UN3077 · ADR, IMDG, IATA

· UN proper shipping name

· DOT Non-Regulated Material

UN3077 Environmentally hazardous substances, solid, n.o.s. · ADR ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, · IMDG

N.O.S. (Epoxy resin), MARINE POLLUTANT

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, · IATA

N.O.S.

· Transport hazard class(es)

· DOT

· Class Non-Regulated Material

· ADR, IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles

· Label

· Packing group

Non-Regulated Material · DOT

· ADR, IMDG, IATA

· Environmental hazards: Product contains environmentally hazardous substances: Epoxy

resin

· Marine pollutant: Yes

Symbol (fish and tree) Symbol (fish and tree)

· Special marking (ADR): · Special marking (IATA): Symbol (fish and tree)

· Special precautions for user Warning: Miscellaneous dangerous substances and articles

· EMS Number: F-A,S-F

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 7)

· Transport/Additional information:

ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 5 kg
 Code: E1

Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· UN "Model Regulation": UN3077, Environmentally hazardous substances, solid, n.o.s., 9,

Ш

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7 titanium dioxide

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 8)

· Hazard pictograms







GHS07 GHS08 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

Epoxy resin

titanium dioxide

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Toxic to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Continue mising.

Specific treatment (see on this label). Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right	· State Right to Know		
25068-38-6	Epoxy resin	≥85%	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
	titanium dioxide	5-10%	
	♦ Carc. 2, H351; ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335		
1317-61-9	Iron Oxide	2-12%	
All ingredien	ts are listed.		

(Contd. on page 10)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: ACCU-GROUT Part A

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of preparation / last revision 01/21/2015 / 4
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

1 Identification

- · Product Identifier
- · Trade Name: ACCU-GROUT Part B
- Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

- · Product Description: Epoxy Grout
- · Details of the Supplier of the Safety Data Sheet:
- · Manufacturer/Supplier:
- · Adhesives Technology Corp.

450 East Copans Rd.

Pompano Beach, FL 33064

(800) 892-1880 (800) 362-3320

Web: www.atcepoxy.com

· Emergency telephone number:

CHEM-TEL (800) 255-3924 24/7

2 Hazard(s) Identification

· Classification of the substance or mixture:



Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:







GHS05 GHS07 GHS08

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

· Signal word: Danger

· Hazard-determining components of labeling:

Tall Oil Fatty Acids, Reaction Product With Tiethylenetetramine triethylenetetramine

· Hazard statements:

Combustible liquid. H227

H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

H317 May cause an allergic skin reaction.

Precautionary statements:

P210 Keep away from flames and hot surfaces. - No smoking.

P260 Do not breathe dusts or mists.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace. P272 Wear protective gloves/protective clothing/eye protection/face protection. P280

P284 [In case of inadequate ventilation] wear respiratory protection. If swallowed: Call a poison center/doctor if you feel unwell. P301+P312 P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin: Wash with plenty of water. P302+P352

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P362+P364 Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. P333+P313 If experiencing respiratory symptoms: Call a poison center/doctor. P342+P311

P363 Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray. P370+P378

Store in a well-ventilated place. Keep cool. P403+P235

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Unknown acute toxicity:

80 % of the mixture consists of component(s) of unknown toxicity.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 1Reactivity = 0

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

· HMIS-ratings (scale 0 - 4)



· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:		
	Tall Oil Fatty Acids, Reaction Product With Tiethylenetetramine	70-95%
	Resp. Sens. 1B, H334; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Irrit. 2B, H320	
112-24-3	triethylenetetramine	5-30%
	Skin Corr. 1B, H314; 1 Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	

Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of §1910.1200 of 29 CFR 1910.1200 Trade Secrets.

4 First-Aid Measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures

- · Extinguishing media
- Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: No further relevant information is available.
- Special hazards arising from the substance or mixture:

Combustible liquid. Vapors can travel to a source of ignition and flash back.

Explosive mixtures may occur at temperatures at or above flashpoint.

(Contd. on page 4)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

· Advice for firefighters

· Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralizing agent.

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	
112-24-3 triethylenetetramine	3 ppm
PAC-2:	
112-24-3 triethylenetetramine	14 ppm
· PAC-3:	
112-24-3 triethylenetetramine	83 ppm

7 Handling and Storage

Handling

· Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin, eyes and clothing

Avoid breathing fume/gas/mist/vapors/spray.

Do not take internally.

Use personal protection equipment as outlined in section 8.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Protect from heat.

Keep ignition sources away - Do not smoke.

· Conditions for safe storage, including any incompatibilities

- · Storage
- Requirements to be met by storerooms and receptacles:

Store in a cool, dry place in tightly closed receptacles.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · Specific end use(s): No further relevant information available.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:
- · Components with occupational exposure limits:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

112-24-3 triethylenetetramine

WEEL Long-term value: 6 mg/m³, 1 ppm

Skin

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- Exposure controls:
- Personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection:



Tightly sealed goggles

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

9 Physical and Chemical Properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid
Color: Amber
Odour: Distinctive
Odor threshold: Not determined.

· **pH-value** @ **20** °**C** (**68** °**F**): 12

Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Flash point:
Flammability (solid, gaseous):
Ignition temperature:
Decomposition temperature:
Not determined.
220 °C (428 °F)
Not applicable.
315 °C (599 °F)
Not determined.

· **Auto igniting:** Product is not self-igniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: 2.1 Vol % **Upper:** 10.5 Vol %

· Vapor pressure @ 20 °C (68 °F): 0.1 hPa (0.1 mm Hg)

• **Density @ 20 °C (68 °F):** 0.956 g/cm³ (7.9778 lbs/gal)

• Relative density:
• Vapor density:
• Evaporation rate:

Not determined.

Not determined.

· Solubility in / Miscibility with:

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content:

Organic solvents: 0.0 %

• Other information: No further relevant information available.

10 Stability and Reactivity

- · **Reactivity:** No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: Carbon Oxides
- · Possibility of hazardous reactions: Reacts with oxidizing agents.
- · Conditions to avoid: Heat and direct sunlight

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

· Incompatible materials: Strong oxidizing agents.

11 Toxicological Information

- · Information on toxicological effects:
- · Acute toxicity:

· LD/LC50	values that are	e relevant for	classification:
-----------	-----------------	----------------	-----------------

112-24-3 triethylenetetramine

Oral LD50 2,500 mg/kg (Rat)
Dermal LD50 805 mg/kg (Rabbit)

· Primary irritant effect:

· On the skin:

Strong caustic effect on skin and mucous membranes.

May cause an allergic skin reaction.

· On the eye:

Strong irritant with the danger of severe eye injury.

Corrosive effect.

Causes serious eve irritation.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories:

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

12 Ecological Information

- · Toxicity:
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

Danger to drinking water if even small quantities leak into the ground.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- Results of PBT and vPvB assessment:
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects: No further relevant information available.

13 Disposal Considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging
- · Recommendation: Disposal must be made according to official regulations.

14 Transport Information

· UN-Number:

· DOT, ADR/ADN, IMDG, IATA UN3266

UN proper shipping name:

DOT
 Corrosive liquid, basic, inorganic, n.o.s. (Triethylenetetramine)
 ADR/ADN
 UN3266 Corrosive liquid, basic, inorganic, n.o.s. mixture
 IMDG, IATA
 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. mixture

Transport hazard class(es):

· DOT



· Class: 8 Corrosive substances

· Label:

· ADR/ADN



· Class: 8 (C5) Corrosive substances

· Label:

· IMDG, IATA



· Class: 8 Corrosive substances

· Label:

· Packing group:

· DOT, ADR/ADN, IMDG, IATA

· *Environmental hazards:* Not applicable.

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

· Special precautions for user: Warning: Corrosive substances

Danger code (Kemler):
EMS Number:
Segregation groups:
Stowage Category
80
F-A,S-B
Alkalis
B

Stowage Code
 Sw2 Clear of living quarters.
 Segregation Code
 SG35 Stow "separated from" acids.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:

· DOT

• Quantity limitations: On passenger aircraft/rail: 1 L

On cargo aircraft only: 30 L

· ADR/ADN

· Excepted quantities (EQ): Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ):

Excepted quantities (EQ): Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 3266 CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.

MIXTURE, 8, II

15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed or exempt from listing.

· California Proposition 65:

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· New Jersey Right-to-Know List:

112-24-3 triethylenetetramine

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

New Jersey Special Hazardous Substance List:	
112-24-3 triethylenetetramine	CO
· Pennsylvania Right-to-Know List:	
112-24-3 triethylenetetramine	
Pennsylvania Special Hazardous Substance List:	
None of the ingredients are listed.	

· Carcinogenic categories:

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:







GHS05 GHS07 GHS08

· Signal word: Danger

· Hazard-determining components of labeling:

Tall Oil Fatty Acids, Reaction Product With Tiethylenetetramine triethylenetetramine

Hazard statements:

H227 Combustible liquid.

H302+H312 Harmful if swallowed or in contact with skin. H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

· Precautionary statements:

P210 Keep away from flames and hot surfaces. – No smoking.

P260 Do not breathe dusts or mists.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection. P301+P312 If swallowed: Call a poison center/doctor if you feel unwell. P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 11)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/02/2018 Reviewed on 11/02/2018

Trade Name: ACCU-GROUT Part B

P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Immediately call a poison center/doctor. P310

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). P321

Take off contaminated clothing and wash it before reuse. P362+P364 P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P363 Wash contaminated clothing before reuse.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· National regulations:

None of the ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

6 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- Date of preparation / last revision: 11/02/2018 / 6
- Abbreviations and acronvms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B

Resp. Sens. 1: Respiratory sensitisation - Category 1

Resp. Sens. 1B: Respiratory sensitisation - Category 1B

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106