

Document #: AMER-023 Revision: 2 Revision Date: 2/8/2022 Page 1 of 9

ASI 5900

Section 1: Product and	d Company Identification	
American Sealants, Inc.		Emergency Phone Number
9190 Yeager Ln		INFOTRAC (International): 1-352-323-3500
Fort Wayne, Indiana 468	09	INFOTRAC (North America): 1-800-535-5053
Phone: 260-489-0728		
Fax: 260-489-0519		
Product Identifier:	ASI 5900	
Recommended Use:	Adhesive/sealant	
Restrictions on Use:	None	

Section 2: Hazard(s) Identification			
Appearance: Paste	Physical Sta	te: Liquid	Odor: Odorless
GHS Classification:			
Acute Toxicity – Inhalation (d	ust/mist)	Category 4	
Skin Sensitization		Category 1	
Reproductive Toxicity		Category 1B	
Specific Target Organ Toxicity Exposure)	(Repeated	Category 1	
	</td <td></td> <th></th>		
Signal Warning:	Danger		
	Harmful if ir		
	-	an allergic skin read	
		e fertility or the ur	
Precautionary Statement(s):	causes dam	age to organs thro	ough prolonged or repeated exposure
	Obtain spec	ial instructions befo	ore use
	Do not hand Wear protect	lle until all safety pi	recautions have been read and understood ive clothing/eye protection/face protection



Product Identifier: ASI 5900

Document #: AMER-023 Revision: 2

Response:	Contaminated work clothing must not be allowed out of the workplace Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product If exposed or concerned: Get medical advice/attention
	IF ON SKIN: Wash with plenty of water and soap Wash contaminated clothing before reuse If skin irritation or rash occurs: Get medical advice/attention IF INHALED: Remove person to fresh air and keep comfortable for breathing
Storage	Store locked up
Disposal	Dispose of contents/container to an approved waste disposal plant

Section 3: Composition/Information on Ingredients			
Chemical Name	CAS No.	Weight %	
Limestone	1317-65-3	40-50	
Calcium Carbonate	471-34-1	15-20	
Titanium(iV) Oxide	13463-67-7	1-5	
Proprietary Component 3	Proprietary	1-5	
Proprietary Component 4	Proprietary	0.1-1	
Proprietary Component 5	Proprietary	0.1-1	
Stearic Acid	57-11-4	0.1-1	
**If Chemical Name/CAS No is "proprietary" ar hemical identity and/or percentage of compo			

Section 4: First-Aid Measures	
General Advice:	If exposed or concerned, get medical advice/attention.
Inhalation:	Remove person to fresh air and keep comfortable for breathing.
Skin Contact:	Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Eye Contact:	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Ingestion:	Clean mouth with water and drink afterwards plenty of water.
Most Important Symptoms and	d Effects:
	skin. Harmful if inhaled. May cause an allergic skin reaction. May damage uses damage to organs through prolonged or repeated exposure.
Indication of any immediate m	edical attention and special treatment needed:
Notes to physician:	Treat symptomatically

Section 5: Fire-Fighting Measures	
Suitable Extinguishing Media:	Carbon Dioxide (CO ₂)
	Dry Chemical



Product Identifier: ASI 5900

Document #: AMER-023 Revision: 2

Unsuitable Extinguishing Media:	Foam Water Spray (fog) Not determined
Specific Hazards Arising from the Chemical:	None
Explosion Data:	
Sensitivity to Mechanical Impact:	Not applicable
Sensitivity to Static Discharge:	Not applicable
Protective equipment and precautions for fire	efighters
As in any fire, wear self-contained breathing a	pparatus pressure-demand, MSHA/NIOSH (approved or

equivalent) and full protective gear.

Section 6: Accidental Release Measures				
Personal precautions, protective e	quipment and emergency procedures			
Personal Precautions:	Use personal protection recommended in Section 8. Avoid eye, skin and clothing contact.			
Environmental Precautions:	See Section 12 for additional Ecological information			
Methods and Materials for Contain	nment and Cleaning Up			
Methods for Containment:	Prevent further leakage or spillage if safe to do so.			
Methods for Clean Up:	Collect spill with absorbent material such as cardboard, allow to cure and place into a container approved for waste disposal.			

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective
precautions have been read and understood. Wear protective
gloves/protective clothing and eye/face protection. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.
ng and incompatibilities
Store locked up.
Moisture

Section 8: Exposure Controls/Personal Protection			
Component Exposure Limits			
Chemical Component	CAS No.	Exposure Limits	
Limestone	1317-65-3	OSHA PEL:	
	•	TWA: 15 mg/m3 (total dust)	
		TWA: 5 mg/m3 (respirable fraction	
		TWA (vacated): 15 mg/m3 (total dust)	
		TWA (vacated): 5 mg/m3 (respirable fraction)	



Product Identifier: ASI 5900

TWA: 10 mg/m3 (total dust) TWA: 5 mg/m3 (respirable fraction) Calcium Carbonate 471-34-1 NIOSH IDLH: Titanium(IV) Oxide 13463-67-7 ACGIH TLV TWA: 10 mg/m3 (total dust) TWA: 10 mg/m3 (total dust) Titanium(IV) Oxide 13463-67-7 ACGIH TLV TWA: 10 mg/m3 (total dust) TWA: 10 mg/m3 (total dust) TWA: 10 mg/m3 (total dust) NOSH IDLH TWA: 10 mg/m3 (total dust) IDLH: 5,000 mg/m3 TWA: 2.4 mg/m3 (tB 63 fine TWA: 0.3 mg/m3 CDB 63 ultrafine, including engineered nanoscale Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn S** Stearic Acid 57-11-4 ACGIH TLV TWA: 0.1 mg/m3 Sn (vacated) S* Stearic Acid 57-11-4 Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear safety glasse				NIOSH IDLH:	
Calcium Carbonate 471-34-1 NIOSH IDLH: TWA: 10 mg/m3 (total dust) TWA: 15 mg/m3 (respirable dust) Titanium(IV) Oxide 13463-67-7 ACGIH TLV TWA: 10 mg/m3 TWA: 10 mg/m3 TWA: 10 mg/m3 OSHA PEL TWA: 15 mg/m3 (total dust) TWA: 10 mg/m3 (total dust) NIOSH IDLH IDLH: 5,000 mg/m3 TWA: 0.1 mg/m3 CIB 63 fine INOSH IDLH IDLH: 5,000 mg/m3 TWA: 0.3 mg/m3 CIB 63 fine Proprietary Component 4 Proprietary ACGIH TLV Stearic Acid Proprietary ACGIH TLV Stearic Acid 57-11-4 ACGIH TLV Appropriate Engineering Control Apply technical measures to comply with the occupational exposure limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear safety glasses or goggles to avoid eye contact. Skin are impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:				TWA: 10 mg/m3 (total dust)	
TWA: 10 mg/m3 (total dust) TWA: 5 mg/m3 (respirable dust) Titanium(IV) Oxide 13463-67-7 ACGIH TLV TWA: 10 mg/m3 TWA: 10 mg/m3 (total dust) TWA: 10 mg/m3 OSHA PEL TWA: 15 mg/m3 (total dust) TWA: 2.4 mg/m3 (total dust) TWA: 2.4 mg/m3 (total dust) NIOSH IDLH IDLH: 5,000 mg/m3 TWA: 2.4 mg/m3 CIB 63 fine TWA: 2.4 mg/m3 CIB 63 ditrafine, including engineered nanoscale Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) S* (Vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn ACGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 2.4 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 0.1 mg/m3 except cyhexatin Sn ACGIH TLV Stearic Acid 57-11-4 ACGIH TLV <th></th> <th>1</th> <th></th> <th>TWA: 5 mg/m3 (respirable fraction)</th>		1		TWA: 5 mg/m3 (respirable fraction)	
Titanium(IV) Oxide 13463-67-7 ACGIH TLV Titanium(IV) Oxide 13463-67-7 ACGIH TLV TWA: 10 mg/m3 TWA: 10 mg/m3 (total dust) TWA: 15 mg/m3 (total dust) TWA: 15 mg/m3 (total dust) TWA: 15 mg/m3 (total dust) NIOSH PEL TWA: 2.4 mg/m3 CIB 63 fine TWA: 2.4 mg/m3 CIB 63 ditrafine, including engineered nanoscale Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn STEL: 0.2 mg/m3 Sn S* STEL: 0.1 mg/m3 Sn S* STA PEL TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 5 mg/m3 Sn Stearic Acid 57-11-4 ACGIH TLV Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear impervious gloves such as vinyl to minimize contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.	Calcium Carbonate	471-	34-1	NIOSH IDLH:	
Titanium(IV) Oxide 13463-67-7 ACGIH TLV TWA: 10 mg/m3 TWA: 10 mg/m3 OSHA PEL TWA: 15 mg/m3 (total dust) TWA: 15 mg/m3 (total dust) TWA: 2.4 mg/m3 (total dust) NIOSH IDLH IDLH: 5,000 mg/m3 TWA: 2.4 mg/m3 CDB 63 line TWA: 0.3 mg/m3 COB 63 ultrafine, including engineered nanoscale engineered nanoscale Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn Stearic Acid 57-11-4 Stearic Acid 57-11-4 Appropriate Engineering Controls Apply technical measures to comply with the occupational exposure limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Kear Safety glasses or goggles to avoid eye contact. Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:					
TWA: 10 mg/m3 OSHA PEL TWA: 15 mg/m3 (total dust) TWA: 15 mg/m3 (total dust) TWA: 10 mg/m3 (total dust) NIOSH IDLH IDLH: 5,000 mg/m3 TWA: 0.3 mg/m3 COB 63 inter TWA: 0.3 mg/m3 COB 63 ultrafine, including engineered nanoscale Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDH: 5: Smg/m3 Sn Stearic Acid 57-11-4 Acgint TLV Stearic Acid 57-11-4 Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:				– – – – – – – – – –	
OSHA PEL TWA: 15 mg/m3 (total dust) TWA (vacated): 10 mg/m3 (total dust) NIOSH IDLH IDLH: 5,000 mg/m3 TWA: 2.4 mg/m3 CIB 63 fine TWA: 0.3 mg/m3 COB 63 ultrafine, including engineered nanoscale Proprietary Component 4 Proprietary Component <	Titanium(IV) Oxide	13463	8-67-7	ACGIH TLV	
Proprietary Component 4 Proprietary ACGIH TLV Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn x* OSHA PEL TWA: 0.1 mg/m3 Sn y* OSHA PEL TWA: 0.1 mg/m3 Sn s* OSHA PEL TWA: 0.1 mg/m3 Sn y* NIOSH IDLH IDLH: 25 mg/m3 Sn Stearic Acid 57-11-4 ACGIH TLV Stearic Acid 57-11-4 ACGIH TLV Appropriate Engineering Control Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.				TWA: 10 mg/m3	
TWA (vacated): 10 mg/m3 (total dust) NIOSH IDLH IDLH: 5,000 mg/m3 TWA: 2.4 mg/m3 CIB 63 fine TWA: 2.4 mg/m3 CIB 63 fine TWA: 0.3 mg/m3 CIB 63 diutrafine, including engineered nanoscale Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn KCGIH TLV TWA: 0.1 mg/m3 inhalable particulate matter TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter <t< td=""><td></td><td></td><td></td><td>OSHA PEL</td></t<>				OSHA PEL	
NIOSH IDLH IDLH: 5,000 mg/m3 TWA: 2.4 mg/m3 CIB 63 fine TWA: 0.3 mg/m3 COB 63 ultrafine, including engineered nanoscale Proprietary Component 4 Proprietary Component 5 Stearic Acid Appropriate Engineering Controls Appro				TWA: 15 mg/m3 (total dust)	
Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn S* Stearic Acid 57-11-4 ACGIH TLV Stearic Acid 57-11-4 Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:					
Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 CDB 63 ultrafine, including engineered nanoscale STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* Stearic Acid 57-11-4 ACGIH TLV ACGIH TLV Stearic Acid 57-11-4 AcGIH TLV TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 Sn (vacated) S* Stearic Acid 57-11-4 AcGIH TLV TWA: 0.1 mg/m3 Sn tWA: 0.1 mg/m3 Sn (vacated) S* Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.				NIOSH IDLH	
Proprietary Component 4 Proprietary ACGIH TLV Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) S* Stearic Acid 57-11-4 ACGIH TLV Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Apply technical measures to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:				-	
engineered nanoscale Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn Stearic Acid 57-11-4 Accil H TLV Stearic Acid 57-11-4 Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Year safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Kefer to 29 CFR 1910.134 for respiratory protection requirements.				-	
Proprietary Component 4 Proprietary ACGIH TLV STEL: 0.2 mg/m3 Sn STEL: 0.1 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn Stearic Acid 57-11-4 ACGIH TLV TWA: 0.1 mg/m3 inhalable particulate matter TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.					
STEL: 0.2 mg/m3 Sn TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn AcGiH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Stearic Acid 57-11-4 AcGiH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.	Drawnister (Company of 4	Duomisto			
TWA: 0.1 mg/m3 Sn S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn Stearic Acid 57-11-4 AcGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.	Proprietary Component 4	Proprieta	ry		
S* OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn Stearic Acid 57-11-4 AcGiH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:				-	
OSHA PEL TWA: 0.1 mg/m3 Sn (vacated) TWA: 0.1 mg/m3 Sn (vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn Kearic Acid 57-11-4 AcGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Stearic Acid Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory pr				-	
Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Apply technical measures to avoid eye contact. Skin and Body Protection: Wear safety glasses or goggles to avoid eye contact. Refer to 29 CFR 1910.134 for respiratory protection requirements.				-	
Stearic Acid57-11-4(vacated) TWA: 0.1 mg/m3 Sn (vacated) S*Stearic Acid57-11-4IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin SnAcGIH TLVTWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matterAppropriate Engineering ControlsApply technical measures to comply with the occupational exposur limits.Individual protection measures, such as personal protective equipmentWear safety glasses or goggles to avoid eye contact.Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skin Refer to 29 CFR 1910.134 for respiratory protection requirements.					
(vacated) S* NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn AcGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter Stearic Acid Xers afety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.				-	
NIOSH IDLH IDLH: 25 mg/m3 Sn TWA: 0.1 mg/m3 except Cyhexatin Sn AcGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.					
Stearic Acid 57-11-4 TWA: 0.1 mg/m3 except Cyhexatin Sn AcGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.					
Stearic Acid 57-11-4 TWA: 0.1 mg/m3 except Cyhexatin Sn AcGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA: 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Wear safety glasses or goggles to avoid eye contact. Skin and Body Protection: Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.				IDLH: 25 mg/m3 Sn	
Stearic Acid 57-11-4 ACGIH TLV TWA: 10 mg/m3 inhalable particulate matter TWA : 3 mg/m3 respirable particulate matter TWA: 3 mg/m3 respirable particulate matter Appropriate Engineering Controls Apply technical measures to comply with the occupational exposur limits. Individual protection measures, such as personal protective equipment Eye/Face Protection: Wear safety glasses or goggles to avoid eye contact. Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:				-	
Appropriate Engineering ControlsApply technical measures to comply with the occupational exposur limits.Individual protection measures, such as personal protective equipmentWear safety glasses or goggles to avoid eye contact.Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skin Respiratory Protection:Refer to 29 CFR 1910.134 for respiratory protection requirements.	Stearic Acid	57-11-4			
Appropriate Engineering ControlsApply technical measures to comply with the occupational exposur limits.Individual protection measures, such as personal protective equipmentWear safety glasses or goggles to avoid eye contact.Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skin Refer to 29 CFR 1910.134 for respiratory protection requirements.				TWA: 10 mg/m3 inhalable particulate matter	
limits.Individual protection measures, such as personal protective equipmentEye/Face Protection:Wear safety glasses or goggles to avoid eye contact.Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skinRespiratory Protection:Refer to 29 CFR 1910.134 for respiratory protection requirements.				TWA : 3 mg/m3 respirable particulate matter	
limits.Individual protection measures, such as personal protective equipmentEye/Face Protection:Wear safety glasses or goggles to avoid eye contact.Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skinRespiratory Protection:Refer to 29 CFR 1910.134 for respiratory protection requirements.					
Individual protection measures, such as personal protective equipmentEye/Face Protection:Wear safety glasses or goggles to avoid eye contact.Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skinRespiratory Protection:Refer to 29 CFR 1910.134 for respiratory protection requirements.	Appropriate Engineering Cont	rols	Apply te	chnical measures to comply with the occupational exposure	
Eye/Face Protection:Wear safety glasses or goggles to avoid eye contact.Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skinRespiratory Protection:Refer to 29 CFR 1910.134 for respiratory protection requirements.					
Skin and Body Protection:Wear impervious gloves such as vinyl to minimize contact with skinRespiratory Protection:Refer to 29 CFR 1910.134 for respiratory protection requirements.		es, such as p			
Respiratory Protection: Refer to 29 CFR 1910.134 for respiratory protection requirements.	-				
	Skin and Body Protection: Wear im				
General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety	Respiratory Protection:		Refer to	29 CFR 1910.134 for respiratory protection requirements.	
practice.					

Section 9: Physical and Chemical Properties				
Physical State:	Liquid	Appearance:	Paste	
Color:	In accordance with pro	In accordance with product description		
Odor:	Odorless	Odor Threshold:	Not determined	
pH:	Not determined	Melting Point:	Not determined	



Product Identifier: ASI 5900

Boiling Point:	Not determined	Flash Point:	Not applicable
Evaporation Rate:	Not determined	Flammability (Sold, Gas)	Liquid-Not applicable
Flammability Limits in A	ir:		
Upper Limit: Lower Limit:	Not applicable Not applicable		
Vapor Pressure:	Not determined	Vapor Density:	Not determined
Density:	15.01 lb/gal	Water Solubility:	Slightly soluble
Solubility in other Solvents:	Not determined	Partition Coeffecient:	Not determined
Auto-ignition Temp.:	Not applicable	Decomposition Temp.:	Not determined
Kinematic Viscosity:	Not determined	Dynamic Viscosity:	Not determined
Explosive Properties:	Not determined	Oxidizing Properties:	Not determined

Not reactive under normal conditions.
Stable under recommended storage conditions.
None under normal processing.
Keep out of reach of children.
Moisture
Thermal decomposition may produce toxic fumes of Carbon monoxide and/or Carbon dioxide.

Section 11: Toxicological Info	ormation							
Information on Likely Routes of	Exposure							
Eye Contact:	Avoid eye contact with eyes.							
Skin Contact:	May be harmful in contact with skin							
Inhalation:	Do not inhale							
Ingestion:	Do not	ingest						
Component Information								
Component	CAS No.	Results	Species	Dose	Exposure			
Calcium Carbonate	471-34-1	LD50 Oral	Rat	=6,450 mg/kg	N/A			
Calcium carbonate	471-34-1	LD50 Dermal		> 2,000 mg/kg				
Proprietary Component 2	Proprietary	LD50 Dermal	Rabbit	> 2,000 mg/kg	N/A			
Titanium(IV) Oxide	13463-67-7	LD50 Oral	Rat	> 10,000 mg/kg	N/A			
Proprietory Component 2	Dropriotony	LD50 Oral	Rat	=7,340 μL/kg	N/A			
Proprietary Component 3	Proprietary	LD50 Dermal	Rabbit	=3.54 mL/kg				
Proprietary Component 4	Proprietary	LD50 Dermal	Rat	> 2,000 mg/kg	N/A			
Bronriotony Component 5	Propriotony	LD50 Dermal	Rat	> 3,170 mg/kg	N/A			
Proprietary Component 5	Proprietary	LC50 Inhalation	Γdι	=500 mg/m3	4 hr			
				0,				

LD50 Dermal

LD50 Oral

Rabbit

Rat

> 2,009 mg/kg =4,600 mg/kg

Proprietary

57-11-4

Proprietary Component 6

Stearic Acid

N/A

N/A



Product Identifier: ASI 5900

Information on physical, Symptoms: Delayed and immediate Sensitization: Carcinogenicity:		Please see Sectior ell as chronic effect May cause an alle The table below ir	n 4 of the SD s from shor rgic skin rea ndicates whe	t and long-te ction. ether each ag	rm exposure	1
Symptoms: Delayed and immediate Sensitization:		Please see Sectior ell as chronic effect May cause an alle The table below ir	n 4 of the SD s from shor rgic skin rea ndicates whe	t and long-te ction. ether each ag	rm exposure	
Symptoms: Delayed and immediate Sensitization:		Please see Sectior ell as chronic effect May cause an alle The table below ir	n 4 of the SD s from shor rgic skin rea ndicates whe	t and long-te ction. ether each ag	rm exposure	
Sensitization:	effects as we	May cause an alle The table below ir	rgic skin rea ndicates whe	ction. ether each ag	·	
		The table below in	ndicates whe	ether each ag	aney has listed an	
Carcinogenicity:					oncy bac listed an	
				product as a	whole has not be	
Chemical Name	CAS No.	ACGIH	IARC	:	NTP	OSHA
Titanium(IV) Oxide	13463-67-7		Group	2B		Х
Legend						
ACGIH (American	n Conference d	of Governmental In	dustrial Hyg	ienists)		
A3 - Animal Co	arcinogen					
IARC (Internation	nal Agency for	Research on Cance	er)			
Group 2B - Pos	ssibly Carcino	genic to Humans				
OSHA (Occupatio	onal Safety an	d Health Administr	ation of the	US Departme	ent of Labor)	
X - Present						
STOT – Repeated Exposu	ure:	May cause damag	e to organs	through prol	onged or repeated	exposure.
Numerical Measures of	Toxicity					
The following values are	e calculated b	ased on chapter 3.	1 of the GHS	o document	•	
Oral LD50		10,075.80 mg/kg				
Dermal LD50		2,330.90 mg/kg				
ATEmix (inhaltat dust/mist)	tion-	1.60 mg/L				

Section 12: Ecological Information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Dropriotory Component 2		10000: 96 h Danio rerio mg/L	
Proprietary Component 2		LC50 static	
Drogwistow (Component 2		191: 96 h Oncorhynchus mykiss	
Proprietary Component 3		mg/L LC50 not specified	
Drogwistowy Component 4		2: 96 h Oryzias latipes mg/L LC50	
Proprietary Component 4		semi-static	
Dropriotory Component F		4.4: 96 h Lepomis macrochirus	
Proprietary Component 5		mg/L LC50 flow-through	

Not determined



Product Identifier: ASI 5900

Bioaccumulation:
There is not data for this product
Mobility:
Not determined
Other Adverse Effects:
Not determined

Section 13: Disposal Consideration	ons				
Waste Treatment Methods					
Disposal of Wastes:		d be in accordance with applicable regional, nationa and regulations.			
Contaminated Packaging:	Disposal should be in accordance with applicable regional, national and local laws and regulations.				
California Hazardous Waste Status					
Chemical Component	CAS No.	California Hazardous Waste Status			
Proprietary Component 4	Proprietary	Toxic			

Section 14: Transport Inf	ormation
Note	
Please see current shipping circumstances.	paper for most up to date shipping information, including exemptions and special
DOT	Not regulated
ΙΑΤΑ	Not regulated
IMDG	Not regulated

International Inventories									
Chemical Name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Limestone	Х	Active	Х	Х	Х	Х	Х	Х	Х
Proprietary Component 1					Х				Х
Calcium Carbonate	Х	Active	Х	Х	Х	Х	Х	Х	Х
Proprietary Component 2	х	Active	Х	Х	Х	Х		Х	Х
Titanium(IV) Oxide	х	Active	Х	Х	Х	Х	Х	Х	Х
Proprietary Component 3	х	Active	Х	Х	Х	Х	Х	Х	Х
Proprietary Component 4	Х	Active	Х	Х	Х	Х	Х	Х	Х
Proprietary Component 5	х	Active	Х	Х	Х	Х	Х	Х	Х
Proprietary Component 6	х	Active	Х	Х	Х	Х	Х	Х	Х
Stearic acid	Х	Active	Х	Х	Х	Х	Х	Х	Х




Product Identifier: ASI 5900	

Proprietary Component 7	Х	Active	Х	х	X	X		Х	Х
Legend:	^	ALLIVE	^	^	^	^		^	^
•	d States	Toxic Subst	ances Contr	ol Act Section 8(b) Invento	orv			
				List/Non-Domes	-				
				ting Chemical Su			n List of N	lotified	
Chemical Sub		•		ting chemical se	abstances	/ Lui Opca		otineu	
ENCS - Japa			hemical Sul	ostances					
IECSC - Chin		-							
		•	-	cal Substances					
		-		nd Chemical Sub	ostances				
AICS - Austr	• •	•			Jotanees				
Ales Alest			ienneur sub.	Junees					
US Federal Regulations									
CERCLA									
This material, as s	upplied.	does not co	ntain anv su	Ibstances regula	ted as haz	zardous si	ubstances	s under t	he
Comprehensive Er	•••		•	-					
Superfund Amend		•				- 73		,	
SARA 311/312 Ha				. , .	,				
Acute Health Hazard		•	'es						
Chronic Health Haza	rd:	Ν	No						
Fire Hazard:	-	Ν	No						
Sudden Release of									
Pressure Hazard:		Ν	No						
Reactive Hazard:		Ν	No						
SARA 313									
Section 313 of Titl	e III of tl	he Superfun	d Amendme	nts and Reautho	orization A	Act of 198	6 (SARA).	This pro	oduct
does not contain a		•					• •	•	
the Code of Feder					•				
CWA (Clean Wate	r Act)								
This product does	not con	tain any sub	stances regu	ulated as polluta	nts pursu	ant to the	e Clean W	ater Act	(40
CFR 122.21 and 40		•	C C		•				
US State Regulations									
California Proposi	tion 65								
Titanium dioxide i	s a possi	ible carcinog	en when it a	appears as a resp	pirable du	st.			
Chemical	Compo	nent		CAS No.		Califo	ornia Pro	position	65
Titaniun	n(IV) Oxi	ide		13463-67-7			Carcino	gen	
	N				•				
US State Right-to-	KNOW R			New lawser	B.4				mic
Chemical Name		CAS No.		New Jersey	ivias	sachusett	IS P	ennsylva	inia
Limestone Titanium(IV) Oxide		1317-65-3 13463-67-7		Х		Х		Х	
				Х		Х		Х	



Product Identifier: ASI 5900



Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

End of Document