

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 10/15/2024 Version: 1.0

## **SECTION 1: Identification**

#### 1.1. Identification

Product form : Mixture
Product name : 10-2055PCL

#### 1.2. Recommended use and restrictions on use

Recommended use : Adhesives

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

#### 1.3. Supplier

Epoxies, Etc. 21 Starline Way Cranston, RI 02921 USA T 401-946-5564

T 401-946-5564 www.epoxies.com

# 1.4. Emergency telephone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

# **SECTION 2: Hazard(s) identification**

## 2.1. Classification of the substance or mixture

#### **GHS US classification**

Skin corrosion/irritation Category 1C H314 Causes severe skin burns and eye damage

Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Respiratory sensitization, Category 1 H334 May cause allergy or asthma symptoms or breathing difficulties if

inhale

Skin sensitization, Category 1 H317 May cause an allergic skin reaction Carcinogenicity Category 2 H351 Suspected of causing cancer

Specific target organ toxicity (repeated exposure) Category 2 H373 May cause damage to organs through prolonged or repeated

exposure

Full text of H statements : see section 16

## 2.2. GHS Label elements, including precautionary statements

#### **GHS US labeling**

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P284 - [In case of inadequate ventilation] wear respiratory protection.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P304+P341 - If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 - If experiencing respiratory symptoms: Call a poison center or doctor.

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

#### 2.4. Unknown acute toxicity (GHS US)

No additional information available

#### **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Propoxylated Amine	CAS-No.: 102-60-3	5 – 10	Eye Irrit. 2, H319
Polyoxypropylenediamine	CAS-No.: 9046-10-0	1 – 10	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Diphenylmethane 4,4'-diisocyanate	CAS-No.: 101-68-8	1-5	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Diphenylmethane diisocyanate (homopolymer)	CAS-No.: 39310-05-9	< 5	Resp. Sens. 1, H334

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Benzene, 1,1'-methylenebis[isocyanato-	CAS-No.: 26447-40-5	< 1	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373

Comments : Components not listed are either non-hazardous or are below reportable limits.

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements: see section 16

## **SECTION 4: First-aid measures**

## 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory

symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a

physician immediately.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

## 5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.

Explosion hazard : No direct explosion hazard. Hazardous decomposition products in case of fire : Toxic fumes may be released.

## 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

10/15/2024 (Issue date) US - en 3/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb

spillage to prevent material-damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin

and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent

migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment.

Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed

out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands

after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store locked up.

Packaging materials : Store always product in container of same material as original container.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### Diphenylmethane 4,4'-diisocyanate (101-68-8)

#### **USA - ACGIH - Occupational Exposure Limits**

Local name Methylene bisphenyl isocyanate (MDI)

10/15/2024 (Issue date) US - en 4/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diphenylmethane 4,4'-diisocyanate (101-68-8)	
ACGIH OEL TWA	0.005 ppm
Remark (ACGIH)	TLV® Basis: Resp sens
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Methylene bisphenyl isocyanate (MDI)
OSHA PEL C	0.2 mg/m³
	0.02 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

# 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

# Personal protective equipment symbol(s):







## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : According to product specification

Odor : Mild odour
Odor threshold : No data available

pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Flash point : No data available

10/15/2024 (Issue date) US - en 5/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20°C : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature No data available Decomposition temperature No data available Viscosity, kinematic No data available : No data available Viscosity, dynamic **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

## 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

## 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Polyoxypropylenediamine (9046-10-0)	
LD50 oral rat	2885 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	2980 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Polyoxypropylenediamine (9046-10-0)	
LC50 Inhalation - Rat	> 0.74 mg/l air (Equivalent or similar to OECD 403, 8 h, Rat, Male / female, Experimental value, Inhalation (vapours))
ATE US (oral)	2885 mg/kg body weight
ATE US (dermal)	2980 mg/kg body weight
Propoxylated Amine (102-60-3)	
LD50 oral rat	2890 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
ATE US (oral)	2890 mg/kg body weight
Diphenylmethane 4,4'-diisocyanate (10	01-68-8)
LD50 oral rat	> 2000 mg/kg body weight (Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 oral	31600 mg/kg
LD50 dermal rabbit	> 9400 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat (Dust/Mist)	0.369 mg/l/4h
ATE US (oral)	31600 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	0.369 mg/l/4h
Benzene, 1,1'-methylenebis[isocyanato	o- (26447-40-5)
LD50 oral rat	> 2000 mg/kg body weight (Other, Rat, Male / female, Experimental value, Oral)
LD50 oral	31600 mg/kg
LD50 dermal rabbit	> 9400 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Skin)
LC50 Inhalation - Rat	0.49 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol))
LC50 Inhalation - Rat (Dust/Mist)	0.369 mg/l/4h
ATE US (oral)	31600 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	0.49 mg/l/4h
ATE US (dust, mist)	0.369 mg/l/4h
Skin corrosion/irritation	: Causes severe skin burns.
Propoxylated Amine (102-60-3)	
рН	No data available in the literature
Diphenylmethane 4,4'-diisocyanate (10	11-68-8)
рН	7 (6.8E-3 g/l, 25 °C)
Serious eye damage/irritation	: Causes serious eye damage.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

skin reaction.  Germ cell mutagenicity : Not classified Carcinogenicity : Suspected of causing cancer.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  IARC group 3 - Not classified STOT-single exposure : Not classified  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-single exposure	Diphenylmethane 4,4'-diisocyanate (101-68	I	
PH 7 (6.8E-3 g/l, 25 °C) Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an alle skin reaction.  Serm cell mutagenicity : Not classified : Suspected of causing cancer.    Diphenylmethane 4,4'-diisocyanate (101-68-8)			
Respiratory or skin sensitization  Serm cell mutagenicity  Suspected of causing cancer.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  IARC group  3 - Not classified  Stort-single exposure  May cause respiratory irritation.  Benzene, 1,1'-methylenebis[isocyanate (101-68-8)  TOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  May cause damage to organs through prolonged or repeated exposure.  May cause damage to organs through prolonged or repeated exposure.  May cause damage to organs through prolonged or repeated exposure.  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Spiration hazard  Stort classified  Stort classified  Stort classified  Stort classified  Tot classified  Tot classified  Tot classified  Tot classified  Not data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic  No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato-(2644'-40-5)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato-(2644'-40-5)  Viscosity, kinematic  9,09 mm²/s (20 °C)  Symptoms/effects after inhalation  May cause allergy or asthma symptoms or breathing difficulties if inhaled.	ш		
skin reaction, Germ cell mutagenicity : Not classified Diphenylmethane 4,4'-diisocyanate (101-68-8)  IARC group 3 - Not classified Reproductive toxicity : Not classified STOT-single exposure : Not classified Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-single exposure May cause respiratory irritation.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) STOT-single exposure May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard Not classified Not data available  Propoxylpropylenediamine (9046-10-0) Viscosity, kinematic Not data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8) Viscosity, kinematic Not data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8) Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) Viscosity, kinematic Not applicable (solid)	11	7 (6.8E-3 g/l, 25 °C)	
Carcinogenicity : Suspected of causing cancer.    Diphenylmethane 4,4'-diisocyanate (101-68-8)     IARC group   3 - Not classified	espiratory or skin sensitization	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allerg skin reaction.	
Diphenylmethane 4,4'-diisocyanate (101-68-8)  Reproductive toxicity : Not classified  STOT-single exposure : Not classified  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-single exposure May cause respiratory irritation.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified  Viscosity, kinematic No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic Not data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic 9.99 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	erm cell mutagenicity	: Not classified	
ARC group  Reproductive toxicity Reproduction. Reproductive toxicity ritiation. Reproduc	arcinogenicity	Suspected of causing cancer.	
Reproductive toxicity : Not classified STOT-single exposure : Not classified  Diphenylmethane 4,4'-diisocyanate (101-68-8) STOT-single exposure May cause respiratory irritation.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) STOT-single exposure May cause respiratory irritation.  STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified //scosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0) Viscosity, kinematic 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3) Viscosity, kinematic Not available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8) Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) Viscosity, kinematic 9.09 mm²/s (20 °C) Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	)iphenylmethane 4,4'-diisocyanate (101-68	-8)	
FTOT-single exposure : Not classified  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-single exposure May cause respiratory irritation.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-single exposure May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified //scosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic Not available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic 9.09 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	ARC group	3 - Not classifiable	
Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-single exposure  May cause respiratory irritation.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-single exposure  May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard  : Not classified  ///ciscosity, kinematic  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	eproductive toxicity	: Not classified	
STOT-single exposure May cause respiratory irritation.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) STOT-single exposure May cause respiratory irritation.  STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified Viscosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0) Viscosity, kinematic 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3) Viscosity, kinematic No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8) Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5) Viscosity, kinematic 9.09 mm²/s (20 °C) Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	TOT-single exposure	: Not classified	
Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-single exposure : May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure   May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure   May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified viscosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic   10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic   Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic   9.09 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Piphenylmethane 4,4'-diisocyanate (101-68	-8)	
STOT-single exposure	GTOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.  Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified Viscosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic 9.09 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Benzene, 1,1'-methylenebis[isocyanato- (26	6447-40-5)	
Diphenylmethane 4,4'-diisocyanate (101-68-8)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified Viscosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic 9.09 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	GTOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard  In the classified  Viscosity, kinematic  In the literature  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic  In the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  May cause allergy or asthma symptoms or breathing difficulties if inhaled.	TOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.	
Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified Viscosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic   10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic   No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic   Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic   9.09 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Diphenylmethane 4,4'-diisocyanate (101-68	-8)	
STOT-repeated exposure  May cause damage to organs through prolonged or repeated exposure.  Aspiration hazard : Not classified Viscosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic : 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic : No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic : Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic : 9.09 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	TOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard : Not classified  Viscosity, kinematic : No data available   Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic : 10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic : No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic : Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic : 9.09 mm²/s (20 °C)  Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Benzene, 1,1'-methylenebis[isocyanato- (26	6447-40-5)	
Viscosity, kinematic : No data available  Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic	TOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Polyoxypropylenediamine (9046-10-0)  Viscosity, kinematic	spiration hazard	: Not classified	
Viscosity, kinematic  10.9 mm²/s (20 °C, OECD 114: Viscosity of Liquids)  Propoxylated Amine (102-60-3)  Viscosity, kinematic  No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	scosity, kinematic	: No data available	
Propoxylated Amine (102-60-3)  Viscosity, kinematic  No data available in the literature  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Polyoxypropylenediamine (9046-10-0)		
Viscosity, kinematic  Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	iscosity, kinematic	10.9 mm <sup>2</sup> /s (20 °C, OECD 114: Viscosity of Liquids)	
Diphenylmethane 4,4'-diisocyanate (101-68-8)  Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Propoxylated Amine (102-60-3)		
Viscosity, kinematic  Not applicable (solid)  Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	/iscosity, kinematic	No data available in the literature	
Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)  Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Diphenylmethane 4,4'-diisocyanate (101-68	-8)	
Viscosity, kinematic  9.09 mm²/s (20 °C)  Symptoms/effects after inhalation  : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	/iscosity, kinematic	Not applicable (solid)	
Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Benzene, 1,1'-methylenebis[isocyanato- (26	6447-40-5)	
	/iscosity, kinematic	9.09 mm <sup>2</sup> /s (20 °C)	
Symptome (offects ofter skin contact . Rurns May cause an allerais skin reaction	ymptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
zympioma/enecta aner akin contact . Duma. Iviay cause an allergic skin reaction.	ymptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.	

# SECTION 12: Ecological information

# 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

10/15/2024 (Issue date) US - en 8/13

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Polyoxypropylenediamine (9046-10-0)		
LC50 - Fish [1]	772.14 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Cyprinodon variegatus, Static system Salt water, Experimental value, GLP)	
EC50 - Crustacea [1]	80 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
ErC50 algae	15 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)	
Propoxylated Amine (102-60-3)		
LC50 - Fish [1]	≈ 4600 mg/l Test organisms (species): Leuciscus idus	
EC50 - Crustacea [1]	> 100 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Read-across, Locomotor effect)	
EC50 72h - Algae [1]	150.67 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
ErC50 algae	150.67 mg/l (EU Method C.3, 72 h, Desmodesmus subspicatus, Read-across, GLP)	
LOEC (chronic)	> 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	≥ 10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
Benzene, 1,1'-methylenebis[isocyanato- (264	47-40-5)	
LC50 - Fish [1]	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Static system, Fresh water, Read-across, Lethal)	
EC50 - Crustacea [1]	> 1000 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Read-across)	
EC50 72h - Algae [1]	> 1640 mg/l (OECD 201: Alga, Growth Inhibition Test, Scenedesmus subspicatus, Static system, Fresh water, Read-across, Growth rate)	

# 12.2. Persistence and degradability

10-2055PCL		
Persistence and degradability	Not rapidly degradable	
Polyoxypropylenediamine (9046-10-0)		
Persistence and degradability	Not readily biodegradable in water.	
Propoxylated Amine (102-60-3)		
Persistence and degradability	Not readily biodegradable in water.	
Diphenylmethane 4,4'-diisocyanate (101-68-8)		
Persistence and degradability	Not readily biodegradable in water.	
Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)		
Persistence and degradability	Contains non readily biodegradable component(s).	
Diphenylmethane diisocyanate (homopolyme	r) (39310-05-9)	
Persistence and degradability	Not rapidly degradable	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

# 12.3. Bioaccumulative potential

Polyoxypropylenediamine (9046-10-0)		
Partition coefficient n-octanol/water (Log Pow)	1.34 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Propoxylated Amine (102-60-3)		
Partition coefficient n-octanol/water (Log Pow)	-2.08 (Calculated, EPIWIN, 25 °C)	
Bioaccumulative potential	Not bioaccumulative.	
Diphenylmethane 4,4'-diisocyanate (101-68-8)		
BCF - Fish [1]	92 – 200 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Cyprinus carpio, Flow-through system, Fresh water, Experimental value, GLP)	
Partition coefficient n-octanol/water (Log Pow)	4.5 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 22 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)		
BCF - Fish [1]	92 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across, GLP)	
Partition coefficient n-octanol/water (Log Pow)	4.51 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 22 °C)	
Bioaccumulative potential	Does not contain bioaccumulative component(s).	

# 12.4. Mobility in soil

Polyoxypropylenediamine (9046-10-0)	Polyoxypropylenediamine (9046-10-0)	
Surface tension	Data waiving	
Ecology - soil	No (test)data on mobility of the substance available.	
Propoxylated Amine (102-60-3)		
Surface tension	64.94 mN/m (20 °C, 0.1 vol %, EU Method A.5: Surface tension)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.484 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Highly mobile in soil.	
Diphenylmethane 4,4'-diisocyanate (101-68-8)		
Surface tension	No data available in the literature	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.5 – 5.5 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	
Ecology - soil	Adsorbs into the soil.	
Benzene, 1,1'-methylenebis[isocyanato- (2644	.7-40-5)	
Ecology - soil	No (test)data on mobility of the component(s) available.	

# 12.5. Other adverse effects

No additional information available

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Sewage disposal recommendations : Disposal must be done according to official regulations. Product/Packaging disposal recommendations : Disposal must be done according to official regulations.

Additional information : Do not re-use empty containers.

# **SECTION 14: Transport information**

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated	Not applicable	Not applicable	Not applicable
14.2. Proper Shipping Name			
Not regulated	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not regulated Not applicable Not applicable Not applicable			
14.4. Packing group			
Not regulated Not applicable Not applicable Not applicable			
14.5. Environmental hazards	14.5. Environmental hazards		
Not regulated	Not regulated Not applicable Not applicable Not applicable		
No supplementary information availab	No supplementary information available		

# 14.6. Special precautions for user

DOT

Not regulated

TDG

Not applicable

IMDO

Not applicable

IATA

Not applicable

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Diphenylmethane 4,4'-diisocyanate CAS-No. 101-68-8 1 – 5%

#### Diphenylmethane 4,4'-diisocyanate (101-68-8)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ 5000 lb

#### 15.2. International regulations

#### **CANADA**

#### Polyoxypropylenediamine (9046-10-0)

Listed on the Canadian DSL (Domestic Substances List)

#### **Propoxylated Amine (102-60-3)**

Listed on the Canadian DSL (Domestic Substances List)

#### Diphenylmethane 4,4'-diisocyanate (101-68-8)

Listed on the Canadian DSL (Domestic Substances List)

#### Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)

Listed on the Canadian DSL (Domestic Substances List)

#### Diphenylmethane diisocyanate (homopolymer) (39310-05-9)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

## Polyoxypropylenediamine (9046-10-0)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

# **Propoxylated Amine (102-60-3)**

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Diphenylmethane 4,4'-diisocyanate (101-68-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### Benzene, 1,1'-methylenebis[isocyanato- (26447-40-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

# 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Diphenylmethane 4,4'-diisocyanate(101-68-8)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

# **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of hazard classes and H-statements	
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.