

TABLE 1: Control joint usage estimating guide for CRACKBOND JF-90 HD^{1,2}

Approximate Coverage Rates Linear Feet (Linear Meters)			
Crack Width in. (cm)	Crack Depth in. (cm)	Package Size	
		20.3 fl. oz. (591 ml)	10 Gal. (38.0 L)
1/16 in. or 0.0625 (0.159)	0.25 (0.6)	202.1 (61.6)	12,320 (3,755)
	0.375 (1.0)	134.8 (41.1)	8,214 (2503.5)
	0.5 (1.3)	101.1 (30.8)	6,160 (1877.6)
1/8 in. or 0.1250 (0.318)	0.375 (1.0)	67.4 (20.5)	4,107 (1251.7)
	0.5 (1.3)	50.5 (15.4)	3,080 (938.8)
	0.75 (1.9)	33.7 (10.3)	2,053 (625.9)
3/16 in. or 0.1875 (0.476)	0.375 (1.0)	44.9 (13.7)	2,738 (834.5)
	0.5 (1.3)	33.7 (10.3)	20,547 (6262.6)
	0.75 (1.9)	22.5 (6.8)	1,369 (417.2)
1/4 in. or 0.25 (0.635)	0.50 (1.3)	25.3 (7.7)	1,540 (469.4)
	0.75 (1.9)	16.8 (5.1)	1,027 (312.9)
	1.00 (2.5)	12.6 (3.9)	770 (234.7)
3/8 in. or 0.3750 (0.953)	0.75 (1.9)	11.2 (3.4)	684 (208.6)
	1.00 (2.5)	8.4 (2.6)	513 (156.5)
	1.50 (3.8)	5.6 (1.7)	342 (104.3)
1/2 in. or 0.50 (1.270)	1.00 (2.5)	6.3 (1.9)	385 (117.4)
	1.50 (3.8)	4.2 (1.3)	257 (78.2)
	2.00 (5.1)	3.2 (1.0)	193 (58.7)
3/4 in. or 0.75 (1.905)	1.50 (3.8)	2.8 (0.9)	171 (52.2)
	2.00 (5.1)	2.1 (0.6)	128 (39.1)
	2.50 (6.4)	1.7 (0.5)	103 (31.3)

1. Values are approximate and may vary depending on waste, concrete and user technique.

2. For best results, saw cuts should be installed to full depth and at least 1 in. deep in formed joints.