



# 502 & 503

100% RTV Silicone



Introducing Design Polymeric DP 502 100% RTV Silicone and DP 503 100% High Temperature RTV Silicone, recommended on a variety of HVAC substrates including galvanized steel, stainless steel, aluminum, wood, fiberglass PVC, PVS, and painted substrates.

- **LEED V4** Qualified
- Non-Slump, Non-sag
- Mold and Mildew Resistant
- Low VOC
- Weather and UV Resistant
- Flexible, will not shrink or crack
- Indoor and Outdoor Usage

**DP 502:** Service temperature -50°F to 500°F.  
Intermittent temperatures up to 500°F.

**DP 503 Red:** Service temperature -50°F to 500°F.  
Intermittent temperature up to 600°F.

**Meets or Exceeds:**

- ASTM C920 Type S, Grade NS, Class 25
- ASTM G26
- TT-S 001543A, TT-S 00230C Type II
- FDA Regulation No. 21 CFR177 2600
- NSF Standard 51
- UL Recognized
- MIL-46106 TYPE 1

Packaging: 10 ounce tubes, 12 tubes per case



A Meridian Brand

5655 E. North Belt Road, Las Vegas, NV 89115  
Toll Free 800.641.0808 | Phone 714.432.0600  
Fax 714.432.0660 | [www.designpoly.com](http://www.designpoly.com)

