

SAFETY DATA SHEET

Version: 1
Issue Date: 12-16-2021
Revision Date: 8-4-2022

ASI 502 White with Mold Resistance

Section 1: Product and Company Identification

American Sealants, Inc.
9190 Yeager Ln
Fort Wayne, Indiana 46809
Phone: 260-489-0728
Fax: 260-489-0519

Emergency Phone Number
Infotrac: +1-800-535-5053 (Within US)
Infotrac: +1-352-323-3500 (Outside US)

Product Identifier: ASI 502 White with Mold Resistance
Recommended Use: Adhesive, binding agents
Restrictions on Use: None known

Section 2: Hazard(s) Identification

Hazard Classification

GHS classification in accordance with 29 CFR 1910.1200
Not a hazardous substance or mixture.

Label Elements

Precautionary Statements

Prevention Use only outdoors or in a well-ventilated area.

Other hazards

No data available

Section 3: Composition/Information on Ingredients

Chemical Nature: Silicone elastomer

This product is a mixture.
Contains no hazardous ingredients according to GHS

Section 4: First-Aid Measures

Description of first aid measures

SAFETY DATA SHEET

Product Identifier: ASI 502 White w/Mold Resistance

Version: 1

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: No emergency medical treatment necessary.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO₂) Dry chemical.

Unsuitable Extinguishing Media: None known.

Special Hazards Arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

Advice for firefighters

Fire Fighting Procedures: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Section 6: Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Follow safe handling advice and personal protective equipment recommendations.

Methods and Materials for Containment and Cleaning Up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations

SAFTEY DATA SHEET

Product Identifier: ASI 502 White w/Mold Resistance

Version: 1

Environment Precautions:

are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. See sections: 7, 8, 11, 12 and 13. Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Section 7: Handling and Storage

Precautions for Safe Handling

Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for Safe Storage, including any Incompatibilities:

Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

Section 8: Exposure Controls/Personal Protection

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls:

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Individual protection measures

Eye/face protection:

Use safety glasses (with side shields).

Skin protection

Hand protection: Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized.

Other protection: No precautions other than clean body-covering clothing should be needed.

Respiratory protection:

Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection

SAFTEY DATA SHEET

Product Identifier: ASI 502 White w/Mold Resistance

Version: 1

should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.

Section 9: Physical and Chemical Properties

Appearance	Paste	Color:	In accordance with product description
Odor:	Acetic acid	Odor Threshold:	No data available
pH:	Not applicable	Melting Point/freezing point:	No data available
Initial boiling point and boiling range:	Not applicable	Flash point:	Not applicable
Evaporation Rate:	Not applicable	Flammability (solid, gas)	Not classified as a flammability hazard
Upper/lower flammability or explosive limits	No data available	Vapor Pressure:	Not applicable
Vapor Density (air = 1):	No data available	Density:	1.007
Water Solubility	No data available	Partition Coefficient (n-octanol/water)	No data available
Auto Ignition:	No data available	Decomposition temperature	No data available
Dynamic viscosity	Not applicable	Kinematic viscosity	Not applicable
Explosive properties	Not explosive	Oxidizing properties	The substance or mixture is not classified as oxidizing
Molecular weight	No data available	Particle size	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

Section 10: Stability and Reactivity

Reactivity:	Not classified as a reactivity hazard
Chemical Stability:	Stable under normal conditions
Possibility of Hazardous Reactions:	Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required.
Conditions to Avoid:	None known.
Incompatible Materials:	Oxidizing agents
Hazardous Decomposition Products:	Decomposition products can include and are not limited to: Formaldehyde

Section 11: Toxicological Information

SAFTEY DATA SHEET

Product Identifier: ASI 502 White w/Mold Resistance

Version: 1

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure

Eye contact, skin contact, ingestion

Acute toxicity (represents short term exposures with immediate effects – no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity

Very low if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Acute dermal toxicity

Based on information for component(s):

LD50, >5,000 mg/kg Estimated

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Acute inhalation toxicity

Based on information for component(s):

LD50, >2,000 mg/kg Estimated

No adverse effects are anticipated from inhalation.

Skin corrosion/irritation

As product: The LC50 has not been determined.

Prolonged exposure not likely to cause significant skin irritation.

Serious eye damage/irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely

Sensitization

For skin sensitization:

Did not cause allergic skin reactions when tested in humans.

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant information found.

Specific target organ toxicity-single exposure

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Toxicity – Repeated Exposure:

Contains a component(s) that is/are encapsulated in the product and are not expected to be released under normal processing conditions or foreseeable emergency

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Carcinogenicity

Based on information for component(s): Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positive results have been reported in other studies using routes of exposure not relevant to industrial handling. Contains an additional component(s) that is/are encapsulated in the product and are

SAFTEY DATA SHEET

Product Identifier: ASI 502 White w/Mold Resistance

Version: 1

	not expected to be released under normal processing conditions or foreseeable emergency.
Teratogenicity	Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.
Reproductive toxicity	Contains component(s) which did not interfere with reproduction in animal studies.
Mutagenicity	Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others. Contains component(s) which were negative in animal genetic toxicity studies.

Section 12: Ecological Information

Ecotoxicological information appears in this section when such data is available.

Toxicity	No data available
Persistence and Degradability:	No data available
Bioaccumulative Potential:	No data available
Mobility in soil	No data available

Section 13: Disposal Considerations

Disposal methods:	DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15
Treatment and disposal methods of used packaging:	Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

Section 14: Transport Information

SAFTEY DATA SHEET

Product Identifier: ASI 502 White w/Mold Resistance

Version: 1

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport

Transport in bulk according to Annex II of MARPOL 73/78 and IBC Code Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Section 15: Regulatory Information

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

No SARA hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Calculated RQ exceeds reasonably attainable upper limit.

Components	CASRN	RQ (RCRA Code)
Acetic acid	64-19-7	5,000 lbs RQ
Acetic anhydride	108-24-7	5,000 lbs RQ

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Polydimethylsiloxane hydroxy-terminated	701313-67-8
Silicon dioxide	7631-86-9
Siloxanes and silicones, dimethyl	63148-62-9
Titanium dioxide	13463-67-7

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SAFTEY DATA SHEET

Product Identifier: ASI 502 White w/Mold Resistance

Version: 1

Section 16: Other Information


Issue Date: 12-16-2021

Revision Date: 8-4-2022

Revision: 1

NFPA Ratings:

Health: 0
Fire: 1
Reactivity: 0



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

Key/Legend:

AICS (Australia); DSL (Canada); IECSC (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIoC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA P0 – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA P0 / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

End of Document