

10-3016 NC EPOXY ADHESIVE

DESCRIPTION:

10-3016NC is a two component epoxy adhesive and sealant. This system is a low viscosity and unfilled. It can be pigmented if required.

TYPICAL SPECIFICATIONS:

ColorClearViscosity, 25 °C, cps1,000Specific gravity, 25 °C1.24

Pot life, 100 grams, 25°C 45 Minutes

10-3016 has an adjustable mix ratio in order to obtain a rigid, semi-rigid, or flexible bond line.

RESIN/HARDENER RATIO

Rigid formulation
Semi-Rigid formulation
Flexible formulation
100:50
100:100
100:150

IMPORTANT:

EPOXIES, ETC. MAKES NO EXPRESS OR IMPLIED WARRANTIES OR MERCHANTABILITY, FITNESS OR OTHERWISE WITH RESPECT TO ITS PRODUCTS. The information in this brochure is based on data obtained by our own research and is considered reliable. However, no warranty is expressed or implied regarding the accuracy of these data, the results to be obtained from the use thereof, or that any such use will not infringe any patent. The properties given are typical values and are not intended for use in preparing specifications. This information is furnished upon the condition that the person receiving it shall make his own tests to determine the suitability thereof for his particular purpose.

06/12