



EPX50-OVERLAY FAST

FAST-SETTING, MOISTURE-INSENSITIVE, EPOXY URETHANE CO-POLYMER OVERLAY RESIN

FOR PROJECTS THAT REQUIRE RAPID CURE TIMES FOR SHORTER LANE CLOSURES

EPX50-OVERLAY FAST is a fast-setting formulation of our EPX50-OVERLAY epoxy-urethane product, making it an excellent option for similar projects that need faster curing at lower temperatures to meet lane closure requirements. Cartridge units are also available for treating cracks, repairing spalls, and patching areas from pull-off tests in concrete and epoxy overlays.

Features & Advantages

Epoxy-urethane technology	3.5 hr cure time at 50° F
Excellent bond strength	Designed for hand mix or mechanical applications
Moisture-insensitive	Non-regulated, hazmat certification or placards not required for transport
Nonflammable	
Easy to mix - 1:1 ratio, color coded	
Retains tensile elongation at low temperatures	

echem

A Meridian Adhesives Group Company

4102 El Rey Rd SE • Albuquerque, NM 87105
(505) 832-3667 • e-chem.net

EPX50-OVERLAY FAST is available in 10, 110, and 500 gallon kits.




Low **CHLORIDE ION PROTECTION - 0 COULOMBS** High

(AASHTO T-277)




Low **ELONGATION** High

(>45% ASTM D-638)



Low **DECK PROTECTION** High

(15 years)



EPX50-OVERLAY FAST
Product Information