



ASI 52AB FLUID AIR BARRIER


High Performing Flexible Coating & Sealant Compound



NO SHRINK/CRACK



PAINTABLE



WATER TIGHT

Built for Real World

Construction schedules don't stop because the substrate is damp or rain is in the forecast. ASI 52AB fluid applied air barrier delivers seamless air and moisture protection with advanced STPE hybrid technology. Unlike many conventional coatings, ASI 52AB can be applied to damp surfaces, resists wash-off when exposed to moisture before cure, and won't shrink or crack over time. Whether you're sealing sheathing, rough openings, penetrations, or entire wall assemblies, ASI 52AB helps keep projects moving.

Highlights

- Bonds To Wet Substrates
- 100% Solids, Will Not Shrink or Crack
- Resistant to UV Degradation & Weathering
- Excellent, Broad Adhesion Range
- Water Resistant Prior To Cure, Will Not Outgas Or Wash off
- Excellent Physical Properties
- Prevents Moisture Transmission
- Contains No Solvents, Phalates or Isocyanates Which Makes ASI 52AB VOC Compliant
- Excellent Unprimed Adhesion To Various Substrates
- Breathable, Allows Damp Surfaces To Dry
- Excellent Perm Rating
- Low Odor, Eco-Friendly Formulation
- Phalate Free Formulation



 **Meridian**
Product Assembly

American Sealants Inc.
9190 Yeager Lane, Fort Wayne, IN 46809
Tel: (978) 667-3805 Fax: 800-325-7040
americansealantsinc.com