

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

1 Identification

- · Product identifier
- · Trade name: EP100 Seal Component A
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Product description Low viscosity epoxy resin
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E-Chem, LLC

4102 El Rey Rd. SE

Albuquerque, NM 87105

Phone: 505.217.2121 Fax: 505.217.3721

Email: mail@e-chem.net Web: www.e-chem.net

Emergency telephone number:

Chemtrec at 1-800-424-9300 24 Hours

Outside the U.S., call Chemtrec collect at 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS09 Environment

Aguatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS07 GHS09

- Signal word Warning
- · Hazard-determining components of labeling:

Epoxy resin

Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 1)

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

100 percent of the mixture consists of ingredient(s) of unknown toxicity.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 1 Fire = 1Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 1

Reactivity = 0

Other hazards None known

3 Composition/information on ingredients

2461-15-6 [[(2-ethylhexyl)oxy]methyl]oxirane

15-35%

70-90%

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous Components:

25068-38-6 Epoxy resin

Aquatic Chronic 2, H411; (1) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1,

Ľ317

4 First-aid measures

Description of first aid measures

· After inhalation:

In case of unconsciousness, place patient securely on side position for transportation. Supply fresh air and to be sure call for a doctor.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 2)

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Never give anything by mouth to an unconscious person.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin, eyes and clothing

Avoid breathing fume/gas/mist/vapors/spray.

Do not take internally.

Use personal protection equipment as outlined in section 8.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool, dry place.

Store in a well ventilated place.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eves and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Purple • Odor: Mild

· Odor threshold: Not determined.

· pH-value @ 20 °C (68 °F): 7

· Change in condition

Melting point/Melting range: Not determined.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 4)

Boiling point/Boiling range: Not determined.

• Flash point: 248 °C (478 °F)

• Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

Vapor pressure: Not determined.

• **Density** @ **20** °**C** (**68** °**F**): 1.1 g/cm³ (9.18 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Solvent content:

Organic solvents: 0.0 %

Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strong oxidizing agents.

Strong acids, strong bases

· Hazardous decomposition products: Carbon dioxide, carbon monoxide and nitrogen oxides.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin:

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

on the eye:

Irritating effect.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 5)

Causes serious eye irritation.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Do not allow product to reach sewage system.

It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 6)

· Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IATA Non-Regulated Material

· *IMDG* UN3082

· UN proper shipping name

· DOT, ADR, ADN, IATA Non-Regulated Material

· IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Epoxy resin), MARINE POLLUTANT

· Transport hazard class(es)

· DOT, ADR, ADN, IATA

· Class Non-Regulated Material

· IMDG



• Class 9 Miscellaneous dangerous substances and articles

· Label

· Packing group

· DOT, ADR, IATA Non-Regulated Material

· *IMDG*

· *Environmental hazards:* Product contains environmentally hazardous substances: Epoxy

resin

· Marine pollutant: Yes

Symbol (fish and tree)

· Special precautions for user Not applicable.

· **EMS Number:** F-A,S-F

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 7)

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS07 GHS09

- Signal word Warning
- Hazard-determining components of labeling:

Epoxy resin

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP100 Seal Component A

(Contd. of page 8)

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know		
25068-38-6	Epoxy resin	70-90%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
2461-15-6	[[(2-ethylhexyl)oxy]methyl]oxirane	15-35%
All ingredients are listed.		

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 01/21/2015 / 1

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106