

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/16/2024 Version: 1.0

SECTION 1 Identification	
1.1. Product identifier	
Product form Product name	: Mixture : EP15-GROUT Part A
1.2. Other means of identification	
No additional information available	
1.3. Recommended use of the chemical and restrictions on use	
No additional information available	
1.4. Supplier's details	
Echem 4102 El Rey Road SE Albuquerque, New Mexico United States T (505) 832-3667 - F (505) 217-3721 https://e-chem.net/	
1.5. Emergency phone number	
Emergency number	: 1-800-424-9300 For Chemical Emergency Call Chemtrec 24hr/day 7days/week Within USA and Canada: 1-800-424-9300

Outside USA and Canada: 703-527-3887

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Hazardous to the aquatic environment — Acute Hazard, Category 2	H401	Toxic to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411	Toxic to aquatic life with long lasting effects.
Full text of H statements : see section 16		

(collect calls accepted)

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)

Signal word (GHS US) Hazard statements (GHS US)



: Warning

- : H315 Causes skin irritation
 - H317 May cause an allergic skin reaction
 - H319 Causes serious eye irritation
 - H361 Suspected of damaging fertility or the unborn child

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	H401 - Toxic to aquatic life
	H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (GHS US)	: P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.
	P264 - Wash hands, forearms and face thoroughly after handling.
	P272 - Contaminated work clothing must not be allowed out of the workplace.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing
	protection.
	P302+P352 - If on skin: Wash with plenty of water.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P308+P313 - If exposed or concerned: Get medical advice/attention.
	P321 - Specific treatment (see supplemental first aid instruction on this label).
	P332+P313 - If skin irritation occurs: Get medical advice or attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
	P337+P313 - If eye irritation persists: Get medical advice or attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P363 - Take off immediately all contaminated clothing and wash it before reuse.
	P391 - Collect spillage.
	P405 - Store locked up.
	P501 - Dispose of contents and/or container to hazardous or special waste collection point, in
	accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Bisphenol A diglycidyl ether resin	CAS-No.: 1675-54-3	< 100	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs.	CAS-No.: 68609-97-2	5 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317
Titanium oxide (TiO2)	CAS-No.: 13463-67-7	< 1	Carc. 2, H351

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Phenol, 4-nonyl-, branched	CAS-No.: 84852-15-3		Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Comments

: This product contains Titanium Dioxide, which is suspected of causing cancer when inhaled in fine particulate form. Titanium Dioxide should not be respirable in this formulation.

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures	
4.1. Description of necessary first-aid mea	asures
First-aid measures general First-aid measures after inhalation First-aid measures after skin contact	 IF exposed or concerned: Get medical advice/attention. Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact First-aid measures after ingestion	 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a poison center/doctor/physician if you feel unwell.
4.2. Most important symptoms/effects, ac	ute and delayed
Symptoms/effects after skin contact Symptoms/effects after eye contact	Irritation. May cause an allergic skin reaction.Eye irritation.
4.3. Indication of immediate medical atten	tion and special treatment needed, if necessary
Other medical advice or treatment	: Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.	
5.2. Specific hazards arising from the chem	ical	
Hazardous decomposition products in case of fire	: Toxic fumes may be released.	
5.3. Special protective equipment and preca	autions for fire-fighters	
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6 Accidental release measures		
6.1. Personal precautions, prote	ctive equipment and emergency procedures	
For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

For emergency responders Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Environmental precautions : Avoid release to the environment. 6.2. Methods and materials for containment and cleaning up : Collect spillage. For containment : Collect spillage. Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handl until all safety precautions have been read and understood. Wear personal protective equipmen Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, inclu	

Storage conditions

: Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Titanium oxide (TiO2) (13463-67-7)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Titanium dioxide (*not respirable as contained in this liquid mixture)	
ACGIH OEL TWA	0.2 mg/m ³ (Respirable fraction) 2.5 mg/m ³ (Respirable fraction)	
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
Regulatory reference	ACGIH 2024	
USA - OSHA - Occupational Exposure Limits		
Local name	Titanium dioxide (*not respirable as contained in this liquid mixture)	
8.2. Appropriate engineering controls		

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.3. Individual protection measures, such as personal protective equipment

and protection:
rotective gloves
ye protection:
afety glasses
kin and body protection:
/ear suitable protective clothing
espiratory protection:
n case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: Mixture contains one or more component(s) which have the following colour(s): Yellow-brown Colourless Pure substance: white Unpurified: coloured Dark grey to black Ligh vellow
Odor	 There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Mild odour Odourless Phenol odour
Odor threshold	: No data available
рН	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available
Bisphenol A diglycidyl ether resin	
Particle characteristics	No data available

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs.		
Particle characteristics	No data available	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium oxide (TiO2)			
Particle characteristics No data available			
Phenol, 4-nonyl-, branched			
Particle characteristics No data available			

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information				
11.1. Information on toxicological	11.1. Information on toxicological effects			
Acute toxicity (oral): Not classifiedAcute toxicity (dermal): Not classifiedAcute toxicity (inhalation): Not classified				
Bisphenol A diglycidyl ether resin (1675-54-3)				
LD50 oral rat	> 2000 mg/kg body weight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))			
LD50 oral	22736 mg/kg			
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal, 14 day(s))			
LD50 dermal	23200 mg/kg			
ATE US (oral)	22736 mg/kg body weight			
ATE US (dermal)	23200 mg/kg body weight			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. ((68609-97-2)			
LD50 oral rat	26800 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))			
LD50 oral	17100 mg/kg			
LD50 dermal rabbit	≥ 4000 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 3 day(s))			
ATE US (oral)	17100 mg/kg body weight			
Titanium oxide (TiO2) (13463-67-7)				
LD50 oral rat	> 2000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))			
LD50 oral	5000 mg/kg			
LC50 Inhalation - Rat	5.09 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))			
LC50 Inhalation - Rat (Dust/Mist)	> 3.43 mg/l Source: ECHA			
ATE US (oral)	5000 mg/kg body weight			
ATE US (vapors)	5.09 mg/l/4h			
ATE US (dust, mist)	5.09 mg/l/4h			
Phenol, 4-nonyl-, branched (84852-15-3)				
LD50 oral rat	1412 mg/kg body weight (Rat, Male / female, Experimental value, Oral, 14 day(s))			
LD50 oral	580 mg/kg			
LD50 dermal rabbit	3160 mg/kg Source: ChemIDPlus			
LD50 dermal	2037 mg/kg			
ATE US (oral)	580 mg/kg body weight			
ATE US (dermal)	2037 mg/kg body weight			
Skin corrosion/irritation : Causes skin irritation.				
Bisphenol A diglycidyl ether resin (1675-54-3)				
pH No data available in the literature				
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)			
рН	No data available in the literature			
Titanium oxide (TiO2) (13463-67-7)				
рН	7 (aqueous suspension, 10 %)			
Phenol, 4-nonyl-, branched (84852-15-3)				
рН	No data available in the literature			
Serious eye damage/irritation :	Causes serious eye irritation.			
Bisphenol A diglycidyl ether resin (1675-54-3)			
рН	No data available in the literature			
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)				
рН	No data available in the literature			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

рН	7 (aqueous suspension, 10 %)	
Phenol, 4-nonyl-, branched (84852-15-3)		
эH	No data available in the literature	
espiratory or skin sensitization erm cell mutagenicity	May cause an allergic skin reaction.Not classified	
arcinogenicity	: Not classified.	
Bisphenol A diglycidyl ether resin (1675-5	4-3)	
ARC group	3 - Not classifiable	
Fitanium oxide (TiO2) (13463-67-7)		
Additional information	*Not a respirable hazard as contained in this liquid mixture	
ARC group	2B - Possibly carcinogenic to humans	
eproductive toxicity	: Suspected of damaging fertility or the unborn child.	
Phenol, 4-nonyl-, branched (84852-15-3)		
NOAEL (animal/female, F0/P)	15 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study), Remarks on results: other:Generation: All generations tested: F0, F1, F2, F3 (migrated information)	
NOAEL (animal/male, F1)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:EPA OPPTS 837.3800 (US EPA OPPTS 1998)	
TOT-single exposure	: Not classified	
TOT-repeated exposure	: Not classified	
Phenol, 4-nonyl-, branched (84852-15-3)		
LOAEL (oral,rat,90 days)	400 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)	
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity in Rodents)	
spiration hazard	: Not classified	
EP15-GROUT Part A		
/iscosity, kinematic	No data available	
Bisphenol A diglycidyl ether resin (1675-5	(4-3)	
/iscosity, kinematic	No data available in the literature	
Oxirane, 2-[(C12-14-alkyloxy)methyl] deriv	rs. (68609-97-2)	
/iscosity, kinematic	No data available in the literature	
Fitanium oxide (TiO2) (13463-67-7)		
/iscosity, kinematic	Not applicable (solid)	
Phenol, 4-nonyl-, branched (84852-15-3)		
/iscosity, kinematic	No data available in the literature	
ymptoms/effects after skin contact ymptoms/effects after eye contact	 Irritation. May cause an allergic skin reaction. Eye irritation. 	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general Hazardous to the aquatic environment, short-term (acute) Hazardous to the aquatic environment, long-term (chronic)	:	Toxic to aquatic life. Toxic to aquatic life with long lasting effects. Not classified Not classified
Bisphenol A diglycidyl ether resin (1675-54	-3))

Bisphenor A digryclayr ether resin (1675-54-3)			
EC50 - Crustacea [1]	1.7 mg/l		
Titanium oxide (TiO2) (13463-67-7)			
LC50 - Fish [1]	> 1000 mg/l (Pisces, Fresh water, Literature study)		
EC50 - Crustacea [1]	> 1000 mg/l (Invertebrata, Fresh water, Literature study)		
EC50 72h - Algae [1]	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)		
Phenol, 4-nonyl-, branched (84852-15-3)			
EC50 - Crustacea [1]	84 μg/l (ASTM E729-88, 48 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Lethal)		
EC50 96h - Algae [1]	0.027 mg/l (EPA OTS 797.1050, Skeletonema costatum, Static system, Salt water, Experimental value, Cell numbers)		
ErC50 algae	0.027 mg/l		
NOEC chronic fish	0.006 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '91 d'		

12.2. Persistence and degradability

EP15-GROUT Part A			
Persistence and degradability	Not rapidly degradable		
Bisphenol A diglycidyl ether resin (1675-54-3)			
Persistence and degradability	Not readily biodegradable in water.		
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)			
Persistence and degradability	Readily biodegradable in water.		
Titanium oxide (TiO2) (13463-67-7)			
Persistence and degradability	Biodegradability: not applicable.		
Chemical oxygen demand (COD)	Not applicable (inorganic)		
ThOD	Not applicable (inorganic)		
Phenol, 4-nonyl-, branched (84852-15-3)			
Persistence and degradability Not readily biodegradable in water.			
12.3. Bioaccumulative potential			
Bisphenol A diglycidyl ether resin (1675-54-3)			
BCF - Other aquatic organisms [1] 31 (QSAR, Fresh weight)			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bisphenol A diglycidyl ether resin (1675-54-3)				
Partition coefficient n-octanol/water (Log Pow)	≥ 2.918 (Experimental value, EU Method A.8: Partition Coefficient, 25 °C)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).			
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)				
Partition coefficient n-octanol/water (Log Pow)	3.8 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).			
Titanium oxide (TiO2) (13463-67-7)				
Bioaccumulative potential Not bioaccumulative.				
Phenol, 4-nonyl-, branched (84852-15-3)				
BCF - Fish [1]	1200 – 1300 (Equivalent or similar to OECD 305, 16 day(s), Gasterosteus aculeatus, Flow- through system, Salt water, Experimental value, Fresh weight)			
Partition coefficient n-octanol/water (Log Pow)	5.4 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23 °C)			
Bioaccumulative potential	Potential for bioaccumulation (500 \leq BCF \leq 5000).			

12.4. Mobility in soil

Bisphenol A diglycidyl ether resin (1675-54-3)				
Surface tension	58.7 – 58.9 mN/m (20 °C, EU Method A.5: Surface tension)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)			
Ecology - soil	Low potential for adsorption in soil.			
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)				
Surface tension	Not applicable (water solubility < 1 mg/l), EU Method A.5: Surface tension			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	 > 5.6 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) 			
Ecology - soil	Adsorbs into the soil.			
Titanium oxide (TiO2) (13463-67-7)				
Surface tension	No data available in the literature			
Ecology - soil	Low potential for mobility in soil.			
Phenol, 4-nonyl-, branched (84852-15-3)				
Surface tension	38.9 mN/m (20 °C, EU Method A.5: Surface tension)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4 (log Koc, Calculated value)			
Ecology - soil	Low potential for mobility in soil.			
12.5. Other adverse effects				
Ozone :	Not classified			

Fluorinated greenhouse gases

: No

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13 Disposal considerations

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14 Transport information

DOT	TDG	IMDG	ΙΑΤΑ			
14.1. UN number						
UN3082	UN3082	3082	3082			
14.2. Proper Shipping Name			1			
Environmentally hazardous substances, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A diglycidyl ether resin)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A diglycidyl ether resin)	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A diglycidyl ether resin)			
14.3. Transport hazard class(es	5)		1			
9	9	9	9			
14.4. Packing group						
III	III	III	III			
14.5. Environmental hazards						
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes			
No supplementary information availab	ble		1			
4.6. Transport in bulk						
lot applicable						

14.7. Special precautions for user	
Special transport precautions	: As per 49 CFR 171.4(c)(1) packaging requirements do not apply to this product if shipped in non-bulk packaging and is not shipped via vessel for domestic travel.
DOT	

UN-No.(DOT)

: UN3082

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	:	 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s." UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as d
DOT Backaging Exponsions (40 CEB 172 year)		MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)	•	155 203
DOT Packaging Bulk (49 CFR 173.xxx)	:	203
		No Limit
CFR 173.27)		
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	No Limit
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
TDG		

UN-No. (TDG)

: UN3082

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, TOXIC, N.O.S. (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (f) UN2849, MEDICINE, SOLID, TOXIC, N.O.S. (g) UN28414, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SUBD, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, on a road vehicle or transport, handling or transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the danger
	safety.
Explosive Limit and Limited Quantity Index	: 5L
Excepted quantities (TDG)	: E1
Emergency Response Guide (ERG) Number	: 171
IMDG	
Special provision (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A
Special provision (IATA)	: A97, A158, A197, A215
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ERG code (IATA)

: 9L

SECTION 15 Regulatory informati	on	
15.1. Federal regulations		
All components of this product are present a (TSCA) inventory	nd listed as Active on the United States Er	nvironmental Protection Agency Toxic Substances Control Act
Contains chemical(s) subject to TSCA 12b e	xport notification if product is shipped outs	side the U.S
Phenol, 4-nonyl-, branched	CAS-No. 84852-15-3	< 1%
15.2. International regulations		
CANADA		
Bisphenol A diglycidyl ether resin (1	675-54-3)	
Listed on the Canadian DSL (Domestic Subs	stances List)	
Oxirane, 2-[(C12-14-alkyloxy)methyl]	derivs. (68609-97-2)	
Listed on the Canadian DSL (Domestic Sub	stances List)	
Titanium oxide (TiO2) (13463-67-7)		
Listed on the Canadian DSL (Domestic Sub	stances List)	
Phenol, 4-nonyl-, branched (84852-1	5-3)	
Listed on the Canadian DSL (Domestic Sub	•	
EU-Regulations		
No additional information available		
National regulations		
Titanium oxide (TiO2) (13463-67-7)		
Listed on IARC (International Agency for Re Listed on INSQ (Mexican National Inventory		
Phenol, 4-nonyl-, branched (84852-1	5-3)	

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date : 5/16/2024

Full text of hazard classes and H-statements		
H302	Harmful if swallowed	
H314	Causes severe skin burns and eye damage	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H318	Causes serious eye damage	
H319	Causes serious eye irritation	
H351	Suspected of causing cancer.	
H361	Suspected of damaging fertility or the unborn child	
H400	Very toxic to aquatic life	
H401	Toxic to aquatic life	
H410	Very toxic to aquatic life with long lasting effects	
H411	Toxic to aquatic life with long lasting effects	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.