

EP100-SEAL LM

LOW-VISCOSITY, LOW SURFACE
TENSION, 100% SOLIDS EPOXY

PROLONGS THE LIFE OF CONCRETE BY SEALING CRACKS AGAINST MOISTURE AND CHLORIDE ION INTRUSION

EP100-SEAL LM is a low-modulus formulation of our EP100-SEAL epoxy healer/sealer product, making it an excellent option where greater degrees of movement are required. **EP100-SEAL LM**'s bond strength and >60% elongation ensures cracks remain sealed during bridge deck movements.

Features & Advantages

Meets ASTM C881 (Type III, Grade 1, Class B & C.)	100% solids
VOC compliant (0 g/L)	Low viscosity
Excellent bond strength	Solvent-free
Moisture insensitive	Low odor
High early strength	Low modulus
Easy to mix - 2:1 ratio	Designed for hand mix or mechanical applications

echem

A Meridian Adhesives Group Company

4102 El Rey Rd SE • Albuquerque, NM 87105
(505) 832-3667 • e-chem.net

EP100-SEAL LM is available in 3, 15, 165, and 750 gallon kits.




Tined: 1 gallon/60-80 ft²
Smooth: 1 gallon/80-150 ft²



(\$2.90 per yd²)



(100 cps - ASTM D2393)



EP100-SEAL LM
Product Information