

**DESCRIPTION: TOUCHDOWN® 725 ALL PURPOSE SPRAY ADHESIVE**

Taylor Touchdown 725 is a non-wrinkling, pressure sensitive all purpose spray adhesive. It bonds to most materials including carpet, tile, fabrics, wood, rubber artwork, leather, etc.

**APPLICATION**

Shake well before using. For best results, hold can 8" to 12" from surface to be bonded and apply uniform coat.

Permanent bond: Coat both surfaces evenly. Allow 30 seconds dry time before assembly. Bonds should be made while adhesive is wet and aggressively tacky.

Non-permanent bond: For easy removable applications, apply a light coat to one surface and allow to dry at least 5 minutes before mounting. Surfaces can then be separated when desired.

**PHYSICAL PROPERTIES**

Base: Synthetic rubber, resin blend  
Appearance: Light yellow liquid  
Odor: Minty when wet  
Shelf Life: One year in unopened container at 70°F  
Flammability: EXTREMELY FLAMMABLE  
Other features: Freeze/thaw stable to 10° F (-12.22° C).  
Clean up: Invert can and depress tip until adhesive is cleared. Clean up overspray and smears with naphtha or turpentine. Replace cap and store in a cool place, away from direct sunlight.

**CALIFORNIA PROPOSITION 65: WARNING**

This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm. Contains Acetone (CAS 67-64-1), Hexane (CAS 110-54-3), Propane (CAS 74-98-6), Dimethyl Ether (CAS 115-10-6), and NJTSRN80100049-5029P.

**CAUTION**

Avoid contact with skin or eyes. Use directional arrow on spray head to avoid spraying into eyes. May cause eye, skin and respiratory tract irritation. Avoid prolonged exposure to vapor.

**DANGER**

EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN. Keep away from heat, sparks and flame. Contents under pressure. Store in a cool space away from direct sunlight, radiators, stoves and other sources of heat. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120° F. Use only in well ventilated area.

**LIMITED WARRANTY**

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For information, call Technical Services at 800-868-4583; visit us on the web at [www.wftaylor.com](http://www.wftaylor.com); or e-mail us at [info@wftaylor.com](mailto:info@wftaylor.com).

W.F. TAYLOR CO., INC. \* FONTANA, CA 800.397.4583 \* DALTON, GA 800.868.4583