

Citrus Adhesive Solvent / Cleaner

DESCRIPTION: CRACKBOND® INDUSTRIAL CITRUS CLEANER is a heavy-duty stripper and degreaser used for general cleaning and degreasing of concrete surfaces, tools and equipment.

APPLICATIONS: INDUSTRIAL CITRUS CLEANER is designed for stripping, degreasing and cleaning all types of concrete, equipment and tools. It is ideal for removal of curing compounds, acrylic sealers and waxes from concrete and cleaning uncured epoxies from tools, equipment and surfaces. It is excellent on concrete floor applications for dirt, tire marks, oil spills, grease and other contaminant removal and will strip most curing and sealing compounds. Applications include:

- Warehouses
- Industrial plants
- Food processing plants
- Automotive plants
- Parking garages
- Plazas
- Service stations

ADVANTAGES:

- Heavy-duty cleaner, stripper and degreaser
- High-strength concentration
- Multi-purpose use
- Bio renewable product
- Organic - safe to use solvent

COMPLIANCES:

- Non-carcinogenic / Non-mutagenic
- Biodegradable product containing no ozone depleting chemicals
- Recognized as GRAS by FDA
- Approved for use in food contact applications by FDA
- Approved as an inert ingredient by the EPA

Appearance: Clear to light yellow with a citrus scent

Shelf Life: 2 years in original unopened container

Storage: 40 - 95 °F (4 - 35 °C) in a cool and well-ventilated area

COVERAGE: INDUSTRIAL CITRUS CLEANER may be diluted with water or used full strength. Recommended dilution ratios from 1:1 to 12:1 with clean water. Suggest trying different dilution rates to cover cleaning and stripping needs.

INSTALLATION: Placement - Apply INDUSTRIAL CITRUS CLEANER full strength for removing heavy dirt buildup, tire marks, oil spills, grease, hydraulic fluid and any difficult to remove contaminants from the concrete surface. Apply full strength to the floor, scrubbing with a stiff broom or floor buffer (swing scrubber); then allow the INDUSTRIAL CITRUS CLEANER to dwell on the surface for 20 minutes or sufficient time to soften the contaminate for removal.

Longer dwell times may be necessary for removal of curing compounds or cure and seals. Do not allow INDUSTRIAL CITRUS CLEANER to dry during the dwell period. Once the contaminate is softened, rinse the entire area thoroughly with water before the product dries. Re-application may be necessary for extremely dirty, stained floors or hard to remove curing compounds.



LIMITATIONS:

- For professional use only
- Do not use on resilient flooring or asphaltic surfaces
- INDUSTRIAL CITRUS CLEANER will adversely affect vegetation

CLEAN-UP: Tools and equipment – use water

CAUTIONS: READ SDS PRIOR TO USING PRODUCT!

- INDUSTRIAL CITRUS CLEANER and the materials it removes may be hazardous and should be disposed of according to all local, state and federal regulations
- Irritant
- Product is a strong sensitizer. Use of safety goggles and chemical resistant gloves are recommended
- Use in a well-ventilated area and avoid breathing vapors
- Use of a NIOSH/MSHA organic vapor respirator is recommended if ventilation is inadequate
- Avoid skin contact
- Do not take internally
- Keep out of reach of children
- Keep away from heat and flames
- Do not allow product to flow into waterways

FIRST AID EYE CONTACT: Flush immediately with water for at least 15 minutes. Contact physician immediately.

RESPIRATORY CONTACT: Remove person to fresh air.

SKIN CONTACT: Remove any contaminated clothing. Remove immediately with a dry cloth or paper towel. Solvents should not be used as they carry the irritant into the skin. Wash skin thoroughly with soap and water

IF INGESTED: Do not induce vomiting. If swallowed give water to drink. Seek medical treatment immediately.

GENERAL: Remove contaminated soaked clothing immediately. In the event of persistent symptoms, seek medical treatment.

TABLE 1: CRACKBOND INDUSTRIAL CITRUS CLEANER Packaging

Package Size	1 Gallon (3.8 L)	5 Gallon (18.9 L)
Part #	B1G-ICC	B5G-ICC