

SAFETY DATA SHEET

Version: 2
Issue Date: 6-19-2015
Revision Date: 8-4-2022

ASI 504 Colors

Section 1: Product and Company Identification

American Sealants, Inc. 9190 Yeager Ln Fort Wayne, Indiana 46809 Phone: 260-489-0728 Fax: 260-489-0519	Emergency Phone Number Infotrac: +1-800-535-5053 (Within US) Infotrac: +1-352-323-3500 (Outside US)
Product Identifier: ASI 504 Colors	
Recommended Use: Sealant	
Restrictions on Use: None known	

Section 2: Hazard(s) Identification

Hazard Classification

GHS classification in accordance with 29 CFR 1910.1200
Not a hazardous substance or mixture.

Other hazards

No data available

Section 3: Composition/Information on Ingredients

Chemical Nature: Silicone elastomer

This product is a mixture.

Component	CASRN	Concentration
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 16.0 – 34.0%

Section 4: First-Aid Measures

Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SAFETY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Inhalation: Move person to fresh air and keep comfortable for breathing; consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO₂) Dry chemical.

Unsuitable Extinguishing Media: None known.

Special Hazards Arising from the substance or mixture

Hazardous combustion products: Carbon oxides. Silicon oxides.

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

Advice for firefighters

Fire Fighting Procedures: Use water spray to cool unopened containers. Evacuate area. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Remove undamaged containers from fire area if it is safe to do so.

Special protective equipment for firefighters: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Section 6: Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Methods and Materials for Containment and Cleaning Up:

Follow safe handling advice and personal protective equipment recommendations.

Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.

SAFETY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Environment Precautions:	<p>See sections: 7, 8, 11, 12 and 13.</p> <p>Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.</p>
---------------------------------	---

Section 7: Handling and Storage	
Precautions for Safe Handling	<p>Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.</p> <p>Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.</p>
Conditions for Safe Storage, including any Incompatibilities:	<p>Keep in properly labelled containers. Store in accordance with the particular national regulations.</p> <p>Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.</p>

Section 8: Exposure Controls/Personal Protection			
Control parameters			
If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.			
Component	Regulation	Type of listing	Value
Distillates (petroleum), hydrotreated middle	OSHA Z-1	TWA	2,000 mg/m ³ 500 ppm
	<i>Further information: (b): The value in mg/m³ is approximate</i>		
	OSHA Z-1	TWA Mist	5 mg/m ³
	OSHA P0	TWA Mist	5 mg/m ³
Exposure controls			
Engineering controls:	Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.		
Individual protection measures			
Eye/face protection:	Use safety glasses (with side shields).		
Skin protection	<p>Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements</p>		

SAFTEY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Respiratory protection:	<p>(cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.</p> <p>Other protection: Wear clean, body-covering clothing.</p> <p>Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.</p>
--------------------------------	--

Section 9: Physical and Chemical Properties			
Appearance	Paste	Color:	In accordance to product description
Odor:	Acetic acid	Odor Threshold:	No data available
pH:	Not applicable	Melting Point/freezing point:	No data available
Initial boiling point and boiling range:	Not applicable	Flash point:	Not applicable
Evaporation Rate (Butyl Acetate=1)	Not applicable	Flammability (solid, gas)	Not classified as a flammability hazard
Upper/lower flammability or explosive limits	No data available	Vapor Pressure:	Not applicable
Vapor Density (air = 1):	No data available	Density:	0.96
Water Solubility	No data available	Partition Coefficient (n-octanol/water)	No data available
Auto Ignition:	No data available	Decomposition temperature	No data available
Dynamic viscosity	Not applicable	Kinematic viscosity	No data available
Explosive properties	Not explosive	Oxidizing properties	The substance or mixture is not classified as oxidizing
Molecular weight	No data available		
NOTE: The physical data presented above are typical values and should not be construed as a specification.			

Section 10: Stability and Reactivity	
Reactivity:	Not classified as a reactivity hazard
Chemical Stability:	Stable under normal conditions
Possibility of Hazardous Reactions:	Can react with strong oxidizing agents.
Conditions to Avoid:	None known.

SAFETY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Incompatible Materials:	Oxidizing agents
Hazardous Decomposition Products:	Decomposition products can include and are not limited to: Formaldehyde

Section 11: Toxicological Information

Toxicological information appears in this section when such data is available.

Information on likely routes of exposure Eye contact, skin contact, ingestion

Acute toxicity (represents short term exposures with immediate effects – no chronic/delayed effects known unless otherwise noted)

Acute oral toxicity Very low if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):
LD50, >5,000 mg/kg Estimated

Information for components:

Distillates (petroleum), hydrotreated middle

LD50, Rat, >5,000 mg/kg

Acute dermal toxicity Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, >2,000 mg/kg Estimated

Information for components:

Distillates (petroleum), hydrotreated middle

LD50, Rabbit, >3,160 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity Brief exposure (minutes) is not likely to cause adverse effects.

As product: The LC50 has not been determined.

Information for components:

Distillates (petroleum), hydrotreated middle

LC50, Rat, 4 hour, dust/mist, >5.2 mg/l

Skin corrosion/irritation Based on information for component(s):
Brief contact may cause slight skin irritation with local redness.
May cause drying and flaking of the skin.

Information for components:

Distillates (petroleum), hydrotreated middle

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/irritation Based on information for component(s):
May cause slight eye irritation.

SAFTEY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

	May cause mild eye discomfort.
	<u>Information for components:</u>
	<u>Distillates (petroleum), hydrotreated middle</u>
	May cause slight eye irritation.
Sensitization	For skin sensitization: No relevant data found.
	For respiratory sensitization: No relevant information found.
	<u>Information for components:</u>
	<u>Distillates (petroleum), hydrotreated middle</u>
	For similar material(s): Did not cause allergic skin reactions when tested in guinea pigs.
	For respiratory sensitization: No relevant data found.
Specific target organ toxicity-single exposure	Evaluation of available data suggests that this material is not an STOT-SE toxicant.
	<u>Information for components:</u>
	<u>Distillates (petroleum), hydrotreated middle</u>
	Available data are inadequate to determine single exposure specific target organ toxicity.
Aspiration Hazard	Based on physical properties, not likely to be an aspiration hazard.
	<u>Information for components:</u>
	<u>Distillates (petroleum), hydrotreated middle</u>
	May be fatal if swallowed and enters airways.
Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)	
Specific Target Organ Toxicity – Repeated Exposure:	Based on available data for the component(s), repeated exposures are not anticipated to cause significant adverse effects.
	<u>Information for components:</u>
	<u>Distillates (petroleum), hydrotreated middle</u>
	Based on available data, repeated exposures are not anticipated to cause significant adverse effects.
Carcinogenicity	No relevant data found.
	<u>Information for components:</u>
	<u>Distillates (petroleum), hydrotreated middle</u>
	For similar material(s): Did not cause cancer in laboratory animals.
Teratogenicity	Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.
	<u>Information for components:</u>
	<u>Distillates (petroleum), hydrotreated middle</u>
	For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.
Reproductive toxicity	Contains component(s) which did not interfere with reproduction in animal studies.

SAFTEY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Information for components:	
	<u>Distillates (petroleum), hydrotreated middle</u>
Mutagenicity	For similar material(s): In animal studies, did not interfere with reproduction.
	In vitro genetic toxicity studies were negative for component(s) tested. Genetic toxicity studies in animals were negative for component(s) tested.
Information for components:	
	<u>Distillates (petroleum), hydrotreated middle</u>
	In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Section 12: Ecological Information

Ecotoxicological information appears in this section when such data is available.

Toxicity

Distillates (petroleum), hydrotreated middle

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LL50, Scophthalmus maximus (turbot), 96 Hour, > 1,028 mg/l, Test substance: Water Accommodated Fraction

Acute toxicity to aquatic invertebrates

LL50, Acartia tonsa, 48 Hour, > 3,193 mg/l, Test substance: Water Accommodated Fraction

Acute toxicity to algae/aquatic plants

EL50, Skeletonema costatum (marine diatom), 72 Hour, > 10,000 mg/l, Test substance: Water Accommodated Fraction

Toxicity to bacteria Product name: XIAMETER™ SLT-5400 Sealant Acetoxy Extended Aluminum

Issue Date: 02/12/2020 Page 9 of 12

EC50, 3 Hour, > 100 mg/l, OECD Test Guideline 209

Chronic toxicity to aquatic invertebrates

NOELR, Ceriodaphnia dubia (water flea), 8 d, > 100 mg/l, Test substance: Water Accommodated Fraction

Persistence and Degradability:

Distillates (petroleum), hydrotreated middle

Biodegradability: Material is expected to be readily biodegradable.

10-day Window: Not applicable

Biodegradation: 74 %

Exposure time: 28 d

Method: OECD Test Guideline 306

Bioaccumulative Potential:

Distillates (petroleum), hydrotreated middle

SAFTEY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Bioaccumulation: No relevant data found.

Mobility in soil

Distillates (petroleum), hydrotreated middle

No relevant data found.

Section 13: Disposal Considerations

Disposal methods:

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging:

Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

Section 14: Transport Information

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated as dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and IBC Code Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SAFETY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Section 15: Regulatory Information

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

No SARA hazards

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Polydimethylsiloxane hydroxy-terminated	701313-67-8
Distillates (petroleum), hydrotreated middle	64742-46-7
Silicon dioxide	7631-86-9

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16: Other Information


Issue Date: 6-19-2015

Revision Date: 8-4-2022

Revision: 2

NFPA Ratings:

Health: 0
Fire: 1
Reactivity: 0



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS III:

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

SAFTEY DATA SHEET

Product Identifier: ASI 504 Colors

Version: 2

Key/Legend:

AICS (Australia); DSL (Canada); IECSC (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIoC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA P0 – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA P0 / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

End of Document