

# ADVANCED SOLUTIONS

---

FOR KITCHEN AND COUNTERTOP APPLICATIONS



## ASI 174

### *Siliconized Acrylic Latex*

Sealant for use with countertop or backsplash to any drywall or surface that needs painted.



## ASI 502

### *100% RTV Silicone*

Sealant for use around sinks, drains, faucets and countertop-to-backsplash applications.



## ASI 5900

### *Fast Grab Hybrid Adhesive*

Adhesive for bonding countertop to cabinets.



## ASI 6900

### *Extreme Grab Hybrid Adhesive*

Adhesive for installation of undermount sinks which replaces need for epoxy and clips.

ASI has been manufacturing advanced formulas for kitchen and cabinet installations for more than 30 years. We have earned a trusted reputation among installers for our competitive, quality products and our hands-on support.

## ASI 174 *Siliconized Acrylic Latex*

**Application:** Sealant for use with countertop or backsplash to any drywall or surface that needs painted.

- ✓ Mold & mildew resistant when cured
- ✓ Non-sag, use on vertical or overhead joints
- ✓ Resistant to UV degradation & weathering
- ✓ Bonds to most common building materials
- ✓ Cures to form a flexible sealant to allow for movement
- ✓ Easy to use, water clean up
- ✓ Paintable
- ✓ Good adhesion

### Conforms/Meets/Exceeds

#### Clear

- ASTM C834-05 Type C
- VOC Compliant

#### White

- ASTM C920, Class 12.5
- TT-S-00230C Class B
- VOC Compliant

### Available Colors



White



Clear

## ASI 5900 *Fast Grab Hybrid Adhesive*

**Application:** Adhesive for bonding countertop to cabinets.

- ✓ Bonds and holds counter tops and panels
- ✓ No solvents or water, will not shrink
- ✓ 100% solids, VOC compliant
- ✓ Offers immediate green strength to help hold substrates while curing
- ✓ Adheres to a wide variety of substrates
- ✓ Remains easy to dispense from 0-150°F
- ✓ Will cure to wet substrates or when moisture is present
- ✓ Remains flexible, allows for vibration & movement

### Conforms/Meets/Exceeds

- California Proposition 65
- USDA Requirements For Non-Food Contact
- CARB & SCAQMD
- VOC Compliant (9.5 grams/liter ASTM D2369)

### Available Colors



Natural White

## ASI 502 *100% RTV Silicone*

**Application:** Sealant for use around sinks, drains, faucets and countertop-to-backsplash applications.

- ✓ 100% acetoxysilicone
- ✓ Mold & mildew resistant
- ✓ Resistant to UV degradation & weathering
- ✓ Withstands extreme cold & extreme heat
- ✓ Meets NSF Standard 51 for incidental food contact
- ✓ 25% joint movement capability
- ✓ Cures to form a long-term, flexible waterproof sealant
- ✓ Non-slump; can use on overhead & vertical applications
- ✓ Creates waterproof seal



File No. E209770

### Conforms/Meets/Exceeds

- ASTM C920 Class 25, Type S, Grade NS, Use NT, G, O
- TT-S-01543A
- TT-S-00230-C
- MIL-A-46106A
- NSF Standard 51
- UL Recognized
- FDA Regulation No. 21 CFR 177.2600
- VOC Compliant (23 grams/liter ASTM D2369)

### Available Colors



Clear



White



Black



Aluminum



Bronze



Almond



Grey



Trans White



Trans Beige



Trans Earth



Trans Grey



Trans Green



Trans Rose



Trans Charcoal



Trans Blue

## ASI 6900 *Extreme Grab Hybrid Adhesive*

**Application:** Adhesive for installation of undermount sinks which replaces need for epoxy and clips.

- ✓ Can eliminate need for clamps, screws, and clips in sink installation
- ✓ Almost 3 times the green strength of ASI 5900
- ✓ Ideal for vertical applications
- ✓ No solvents or water, will not shrink
- ✓ 100% solids, VOC compliant
- ✓ Adheres to a wide variety of substrates
- ✓ Remains easy to dispense from 0-150°F
- ✓ Will cure to wet substrates or when moisture is present
- ✓ Remains flexible, allows for vibration & movement
- ✓ Extreme green strength to hold while adhesive cures

### Conforms/Meets/Exceeds

- California Proposition 65
- USDA Requirements For Non-Food Contact
- CARB & SCAQMD
- VOC Compliant (9.5 grams/liter ASTM D2369)

### Available Colors



Natural White

CALL TODAY FOR MORE INFORMATION!

1-800-325-7040