

COLORFAST™

BY *Convergent*

STAIN

Color Stain and Protective Surface Hardener

Adhesives Technology Corporation,
A Meridian Brand

115 North 1380 West
Orem, Utah 84057
United States of America

1-800-892-1880

www.atcepoxy.com



nanoLithium

Patented Technologies by Advan
Nano-Lithium® (NL) Concrete Treatment

PRODUCT DESCRIPTION

COLORFAST™ STAIN is a chemically reactive, Nano Lithium® enhanced product that creates beautiful, durable colored concrete. For application on overlays, profiled concrete, and exterior concrete, this high-solids treatment utilizes lithium densifier and a proprietary ultra-performance binder to anchor color to the concrete. It hardens and protects both interior and exterior slabs and provides stunning, long-lasting color that will not peel or flake.

COLORFAST™ STAIN is an ideal solution for all construction phases and maintenance projects that require superior and enduring color, as well as protection against UV radiation, water intrusion, aggressive chemicals, abrasion, and corrosion. This breathable stain comes in a variety of colors. COLORFAST™ STAIN is low in VOC's, environmentally friendly and has a very low polymer odor.

KEY BENEFITS

- Creates a stronger, better-looking finish that is dust-proof and resistant to staining and deterioration
- All-in-one sealer and color that is UV stable
- Meets OSHA and ADA coefficient of friction standards
- Out-performs epoxies, urethanes and acrylics in abrasion resistance, durability, adhesion, and maintenance costs
- Will not peel, flake, blister, or delaminate
- User friendly, dries quickly with low odor
- Maintenance is reduced and re-coating is simple
- VOC compliant, may contribute to LEED points (IEQ credit)

AVAILABLE COLORS



White



Real Red



Cascade Green



Egyptian Blue



Black



Wheat



Beige



Chocolate Milk



Raw Umber



Morning Fog Gray



Charcoal Gray



Neutral Gray



Burnt Umber



Sand

Customer Service:
Toll Free 1-800-892-1880

Visit our website:
www.atcepoxy.com

Or scan the code:



APPLICATION

To achieve consistent application, practice applying product on a test concrete slab before using on a jobsite. Apply only when temperatures will be above 40°F (4°C) for at least 2 hours following application. Allow a minimum of 7-14 days cure time for new concrete prior to preparation and application.

Equipment: 200-grit metal bond diamond grinding tools, autoscrubber, microfiber pad, low-pressure sprayer with conical tip, soft broom, masking tape, masking paper and/or plastic sheet.

INTERIOR/SMOOTH/TROWELLED CONCRETE

Surface Preparation: Preparation and cleanliness of concrete are essential for successful stain application. To create a smooth but porous surface, it is ideal to wet grind with 200-220 grit metal diamonds. (Do not use resin-bond or hybrid-resin diamonds.) This step opens the pores of the substrate and allows better penetration and adhesion. (Extremely rough or damaged floors may need coarser grinding before 200-grit profiling.)

Clean surface with autoscrubber, wipe with microfiber pad, and perform a white-rag wipe test to ensure all dirt and dust has been removed. Do not use citrus or acidic cleaners. If acidic or d-limonene cleaners have been used, neutralize the surface using an alkaline cleaner (TSP, Tide laundry detergent, etc.)

Mask areas that do not receive COLORFAST™ STAIN to protect from overspray.

Application: Mix product thoroughly with a mechanical mixer to ensure color uniformity. Apply using a low-pressure, pump-up, airless, or mechanical sprayer with a conical tip (very fine mist - do not use a fan tip). Apply material evenly at approximately 600-700 ft² per gallon (15-17 m² per liter). Do not over apply the product. Use a circular motion and maintain a consistent, even spray. Let product sit until it starts to dry in some areas. Using a very soft bristle broom, lightly broom out any pooled material.

Allow material to dry for 30 minutes minimum (until completely dry to the touch), then apply a second application of COLORFAST™ STAIN, repeating the steps above. Additional applications may be added until desired depth of color has been achieved. Allow each application to dry completely before the next application.

Once stain is dry (approximately one hour), apply two very thin coats of COLORFAST™ FINISH or COLORFAST™ GLOSS using a microfiber applicator pad. Let dry between coats. The surface is ready for use when dry.

EXTERIOR/ROUGH SURFACE

Surface Preparation: Clean surface with autoscrubber. Surface should be clean of dust and debris and completely dry.

Mask areas that do not receive COLORFAST™ STAIN to protect from overspray.

Application: Mix product thoroughly with a mechanical mixer to ensure color uniformity. The application for exterior concrete is the same as interior except coverage rate will be closer to 300-400 ft² per gallon (8-13 m² per liter).

Once stain is dry (approximately one hour), apply two very thin coats of COLORFAST™ FINISH or COLORFAST™ Gloss using a microfiber applicator pad. Let dry between coats. The surface is ready for use when dry.

**Before application, always do a small test sample in a less-visible area to be sure there are no variables or contaminants in the substrate that may be incompatible with this product.*

Technical Service

Customer Service:

Toll Free 1-800-892-1880

Email:

atcinfo@atcepoxy.com

Web:

www.atcepoxy.com

For Chemical/Medical Emergencies:

Infotrac 800-535-5053

Outside USA 352-323-3500

ESTIMATED COVERAGE

- Machine-troweled concrete: 600-700 ft² per gallon (15-17 m² per liter)
- Broom-finished concrete: 300-400 ft² per gallon (8-13 m² per liter)

**Coverage rate will vary with concrete porosity and environmental conditions.*

CLEAN UP

Use soap and water to clean tools and equipment. Although ColorFast™ Stain is non-toxic and environmentally safe, it is alkaline. Use up or dry out extra material and dispose of according to local regulations. Do not pour into sewer systems or storm drains.

MAINTENANCE

Routine sweeping, mopping, and washing of floors with water and Pentra-Clean™ (CR), Pentra-Clean (DC)™ or neutral pH cleaners is recommended. Plain water is sufficient for most environments. DO NOT USE cleaners that are acidic or that have citrus (d-Limonene) or Butyl compounds. Consult an Adhesives Technology Corp. Representative for further information.

MAINTENANCE (Commercial Use)

Routine sweeping, mopping, washing and mechanical scrubbing of floors with water and Pentra-Clean™ (CR), Pentra-Clean (DC)™ or neutral pH cleaners is recommended to maintain the appearance and protection of the finish. When using a mechanical scrubber, add 4 oz of the cleaner per 15 gallon water tank. We recommend using red or white pads on the machine. DO NOT USE cleaners that are acidic or that have citrus (d-Limonene) or Butyl compounds. Consult an Adhesives Technology Corp. representative for further information.

When possible, burnish interior floors with a 1500 grit diamond pad once a week, immediately after cleaning. This will keep the floor's finish smooth, glossy and clean. Reapply COLORFAST™ FINISH once every year and more frequently in high traffic areas to rejuvenate appearance and help prevent stains, spills and the wearing of color beneath.

SAFETY/HEALTH INFORMATION

KEEP OUT OF REACH OF CHILDREN.

Do not drink. If swallowed, do not induce vomiting; drink two glasses of water and call a physician. Wear goggles and gloves. If splashed in eyes, rinse eyes immediately with clean water and call a physician if irritation persists. Clean skin with soap and water.

CAUTION: Surfaces wet with COLORFAST™ STAIN may be slippery.

Additional precautions, safety information and first aid treatments are contained in the Safety Data Sheet.

PROPERTIES

Form: Liquid

Color: Varies

Odor: Slight polymer-like odor

Total Solids: 17%

Specific Gravity: 1.09

pH: 11-12

V.O.C. Content: <50g/L

Flash Point: N/A

Freeze Point: 32°F (0°C)

Shelf Life: 6 months in unopened, sealed container

Technical Service

Customer Service:

Toll Free 1-800-892-1880

Email:

atcinfo@atcepoxy.com

Web:

www.atcepoxy.com

For Chemical/Medical Emergencies:

Infotrac 800-535-5053

Outside USA 352-323-3500

PACKAGING

1-Gal Jug • 3.79 L

5-Gal Pail • 18.93 L

55-Gal Drum • 208.20 L

275-Gal Tote (IBC) • 1040 L

LIMITATIONS

COLORFAST™ STAIN is chemically resistant and helps reduce staining but some compounds, especially acids, may damage the surface.

COLORFAST™ STAIN will not bridge or fill cracks and will not salvage honeycombed or structurally unsound surfaces. This product will not alter the profile of a surface. Not suitable for asphalt, non-cementitious surfaces, or painted surfaces.

If COLORFAST™ STAIN comes into contact with glass, fabric, metal, or painted surfaces, immediately wipe contaminated surfaces with a damp cloth, then wipe dry with a second clean cloth.

Make certain the most current versions of the COLORFAST™ STAIN Product Data Sheet and SDS are being used. Call Customer Service (1-866-375-2280) or visit our website (www.atcepoxy.com) to find additional tips, guidelines, and specifications.

Proper application is the responsibility of the user. Field visits by Adhesives Technology Corp. Personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the job site.



Refer to www.atcepoxy.com for latest Technical Data Sheet and Safety Data Sheet.

Adhesives Technology Corp., A Meridian Brand, 115 North 1380 West Orem, Utah 84057 801-375-2280

Products manufactured and marketed by Adhesives Technology Corporation are protected by U.S. Patents and pending patents and/or pending patents under license in the United States and other countries.
Revision date 031026

Technical Service

Customer Service:

Toll Free 1-800-892-1880

Email:

atcinfo@atcepoxy.com

Web:

www.atcepoxy.com

For Chemical/Medical Emergencies:

Infotrac 800-535-5053

Outside USA 352-323-3500

WARRANTY

LIMITED WARRANTY NOTICE. Every reasonable effort is made to apply exacting standards both in the manufacture of our products and in the information that we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, ADHESIVES TECHNOLOGY CORP. MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and ADHESIVES TECHNOLOGY CORP shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of ADHESIVES TECHNOLOGY CORP'S Research Director. This information and all further technical advice are based on ADHESIVES TECHNOLOGY CORP'S present knowledge and experience. However, ADHESIVES TECHNOLOGY CORP. assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, ADHESIVES TECHNOLOGY CORP. disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. ADHESIVES TECHNOLOGY CORP. SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. ADHESIVES TECHNOLOGY CORP. reserves the right to make any changes according to technological progress or further developments. It is the customer's (Authorized Applicator) responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used. ADHESIVES TECHNOLOGY CORP. reserves the right to change specifications referred to in this literature at any time, without prior notice. The information contained herein is, to our knowledge, true and accurate. While this material is furnished in good faith, no warranty expressed or implied, of merchantability, completeness, fitness or otherwise is made. This material is offered only for your consideration, investigation and verification, and ADHESIVES TECHNOLOGY CORP. disclaims any liability incurred from the use thereof and shall not in any event, be liable for any special, incidental or consequential damages arising from such use. This information is not intended to be all inclusive and the manner and conditions of use and handling of any material may involve other or additional considerations specific to the use or user. Nothing herein should be construed as permission or recommendation to infringe any patent or as to any specific use. No agent, representative or employee of this company is authorized to vary any term of this notice.

Refer to www.atcepoxy.com for latest Technical Data Sheet and Safety Data Sheet.

Adhesives Technology Corp., A Meridian Brand, 115 North 1380 West Orem, Utah 84057 801-375-2280

Products manufactured and marketed by Adhesives Technology Corporation are protected by U.S. Patents and pending patents and/or pending patents under license in the United States and other countries.
Revision date 031026