

**TABLE 1: Crack repair usage estimating guide for CRACKBOND 2100 MV<sup>1</sup>**

Approximate Coverage Rates Linear Feet (Linear Meters)					
Crack Width in. (cm)	Crack Depth in. (cm)	Package Size			
		9 fl. oz. (266 ml)	102 fl. oz. (3.2 L)	2 Gal. (7.6 L)	10 Gal. (38.0 L)
1/16 in. or 0.0625 (0.159)	0.25 (0.6)	77.0 (23.5)	982 (299.2)	2,464 (751.0)	12,320 (3,755)
	0.375 (1.0)	51.3 (15.6)	655 (199.5)	1,643 (500.7)	8,214 (2503.5)
	0.5 (1.3)	38.5 (11.7)	491 (149.6)	1,232 (375.5)	6,160 (1877.6)
	0.75 (1.9)	25.7 (7.8)	327 (99.7)	821 (250.3)	4,107 (1251.7)
1/8 in. or 0.1250 (0.318)	0.25 (0.6)	38.5 (11.7)	491 (149.6)	1,232 (375.5)	6,160 (1,878)
	0.375 (1.0)	25.7 (7.8)	327 (99.7)	821 (250.3)	4,107 (1251.7)
	0.5 (1.3)	19.3 (5.9)	245 (74.8)	616 (187.8)	3,080 (938.8)
	0.75 (1.9)	12.8 (3.9)	164 (49.9)	411 (125.2)	2,053 (625.9)
3/16 in. or 0.1875 (0.476)	0.25 (0.6)	25.7 (7.8)	327 (99.7)	821 (250.3)	4,107 (1,252)
	0.375 (1.0)	17.1 (5.2)	218 (66.5)	548 (166.9)	2,738 (834.5)
	0.5 (1.3)	12.8 (3.9)	164 (49.9)	411 (125.2)	2,054 (626.6)
	0.75 (1.9)	8.6 (2.6)	109 (33.2)	274 (83.4)	1,369 (417.2)
1/4 in. or 0.25 (0.635)	0.25 (0.6)	19.3 (5.9)	245 (74.8)	616 (187.8)	3,080 (939)
	0.375 (1.0)	12.8 (3.9)	164 (49.9)	411 (125.2)	2,053 (625.9)
	0.5 (1.3)	9.6 (2.9)	123 (37.4)	308 (93.9)	1,540 (469.4)
	0.75 (1.9)	6.4 (2.0)	82 (24.9)	205 (62.6)	1,027 (312.9)
3/8 in. or 0.3750 (0.953)	0.25 (0.6)	12.8 (3.9)	164 (49.9)	411 (125.2)	2,053 (626)
	0.375 (1.0)	8.6 (2.6)	109 (33.2)	274 (83.4)	1,369 (417.2)
	0.5 (1.3)	6.4 (2.0)	82 (24.9)	205 (62.6)	1,027 (312.9)
	0.75 (1.9)	4.3 (1.3)	55 (16.6)	137 (41.7)	684 (208.6)
1/2 in. or 0.50 (1.270)	0.25 (0.6)	9.6 (2.9)	123 (37.4)	308 (93.9)	1,540 (469)
	0.375 (1.0)	6.4 (2.0)	82 (24.9)	205 (62.6)	1,027 (312.9)
	0.5 (1.3)	4.8 (1.5)	61 (18.7)	154 (46.9)	770 (234.7)
	0.75 (1.9)	3.2 (1.0)	41 (12.5)	103 (31.3)	513 (156.5)

1. Values are approximate and may vary depending on waste, concrete and user technique.