

# STRiON:FORTIFY

## PREMIUM SILICA-FREE DENSIFIER AND HARDENER

Adhesives Technology Corporation,  
A Meridian Brand

115 North 1380 West  
Orem, Utah 84057  
United States of America

1-800-892-1880

[www.atcepoxy.com](http://www.atcepoxy.com)

STRiON



### PRODUCT DESCRIPTION

STRiON:FORTIFY uses a groundbreaking new silica-free technology to create the most user-friendly concrete densifier that has ever been available. The resulting concrete surface offers everything you'd want in a densifier: hard, dense, easy to polish or burnish, dustproof, and simple to clean. Yet its application process is near-foolproof. Through its sheer simplicity, STRiON:FORTIFY saves time and money by eliminating misapplication mistakes.

Not only is it remarkably easy to apply, but it can be applied at temperatures as low as 25°F—and no rinsing is required, making it not only simple but also easy on the environment. It can be applied to freshly placed concrete and tilt-up construction slabs, and it can also be used on existing concrete surfaces and cementitious overlays as well.

STRiON:FORTIFY creates an extremely hard surface that is less porous, yet breathable. When applied to new concrete, its small molecules thoroughly penetrate the surface and an ionic reaction creates insoluble calcium-silicate hydrates. This makes concrete more abrasion-resistant, which allows abrasive tooling to create a superior polish and makes maintenance easier throughout the concrete's long life.

### KEY BENEFITS

- UL 2818 – 2022 GreenGuard Gold Certification for low chemical emissions - Gold Standard for Chemical Emissions for Building Materials, Finishes and Furnishings
- Extremely simple application, with no rinsing required
- Hardens concrete and terrazzo while preserving the surface's natural look
- Penetrates, with no film to lift or peel off, and allows abrasive tooling to work more effectively
- May be applied in temperatures as low as 25°F
- Does not contribute to surface ASR or surface crazing
- Resists dusting, making concrete easier to maintain
- VOC compliant, may contribute to LEED points (IEQ credit)

**Customer Service:**

Toll Free 1-800-892-1880

**Visit our website:**

[www.atcepoxy.com](http://www.atcepoxy.com)

**Or scan the code:****USES**

Power-Troweled Concrete, Tilt-Up Construction Slabs, Grocery Stores, Parking Garages, Fire Stations, Sidewalks, Driveways, Loading Docks, Aircraft Hangars, Automotive Dealerships, Shipping Terminals, Vehicle Maintenance Areas, Office Buildings, Healthcare Facilities, Cafeterias/Restaurants, Correctional Institutions, Retail & Shopping Centers, Schools, Stadiums, Veterinary Clinics, Common Areas, Laboratories, Lobbies, Mechanical Rooms, Mezzanines, Manufacturing Facilities, Warehouses, Storage, Distribution Centers, Food Processing Plants, Textile Mills, Wastewater Treatment Plants, Pharmaceutical Plants, Electronic Facilities, Cold Storage/Freezers, Beverage Bottling Plants, Chemical Processing Plants, etc.

**APPLICATION**

May be applied as low as 25°F. Using a sprayer, apply STRiON:FORTIFY evenly on the surface. Keep the surface wet with product for at least 20 minutes, adding more product where needed. If product is being used during the polishing process, apply after the last cutting step, then wait until the concrete is no longer wet on the surface. You can then continue grinding and polishing to the intended final surface profile and desired finish.

On existing concrete, clean surface before application to remove any dirt, laitance, curing compounds or coatings that may prevent STRiON:FORTIFY from penetrating the surface. Do not use citrus or acidic cleaners. If acidic or d-limonene cleaners have been used, neutralize the surface using an alkaline cleaner (TSP, Tide laundry detergent, etc.). A slight residue may occur after application. If it does, it removes very easily with water.

The surface is ready for use when dry to touch.

*\*It may be necessary to spray water on hot concrete with a surface temperature above 90°F (32°C) to cool the surface prior to application so STRiON:FORTIFY does not flash-dry on the surface. Proceed with product application once the surface is dry.*

*\*Before application, always do a small test sample in a less-visible area to be sure there are no variables or contaminants in the substrate that may be incompatible with this product.*

**ESTIMATED COVERAGE**

Machine-troweled: 450-650 ft<sup>2</sup> per gallon (11-16 m<sup>2</sup> per liter)

\*Coverage rate will vary with concrete porosity and environmental conditions.

**CLEAN UP**

Use soap and water to clean tools and equipment. Although STRiON:FORTIFY is nontoxic and environmentally safe, it is alkaline. Use up or dry out extra material and dispose of according to local regulations. Do not pour into sewer systems or storm drains.

**MAINTENANCE**

Clean with Pentra-Clean™ (CR), Pentra-Clean™ (DC) or neutral pH cleaners as needed. If additional protection or gloss is desired, apply Pentra-Finish™ (HG), Pentra-Pel™ (SI), or Pentra-Guard® (EXT). Consult a Adhesives Technology Corp. Representative for further information.

**Technical Service**

Customer Service:

Toll Free 1-800-892-1880

**Email:**

atcinfo@atcepoxy.com

**Web:**

www.atcepoxy.com

**For Chemical/Medical Emergencies:**

Infotrac 800-535-5053

Outside USA 352-323-3500

**SAFETY/HEALTH INFORMATION**

KEEP OUT OF REACH OF CHILDREN.

Do not drink. If swallowed, do not induce vomiting; drink two glasses of water and call a physician. Wear goggles and gloves. If splashed in eyes, rinse eyes immediately with clean water and call a physician if irritation persists. Clean skin with soap and water.

CAUTION: Surfaces wet with STRiON:FORTIFY may be slippery.

Additional precautions, safety information and first aid treatments are contained in the Safety Data Sheet.

**PROPERTIES**

Form: Liquid

Color: Clear - Colorless

Odor: Slight to none

Concentration: 10-12%

Specific Gravity: 1.044 @ 68°F

pH: 6.6

VOC Content: &lt;50g/L

Flash Point: N/A

Freeze Point: 25°F (-3.8°C)

Shelf Life: 1 year in unopened, sealed container

**PACKAGING**

1-Gal Jug • 3.79 L

5-Gal Pail • 18.93 L

55-Gal Drum • 208.20 L

275-Gal Tote (IBC) • 1040 L

**LIMITATIONS**

STRiON:FORTIFY will not bridge or fill cracks or voids and will not salvage honeycombed or structurally unsound surfaces. Not suitable for asphalt, non-cement surfaces or painted surfaces.

If STRiON:FORTIFY comes into contact with glass, fabric, metal, or painted surfaces, immediately wipe contaminated surfaces with a damp cloth, then wipe dry with a second clean cloth.

Make certain the most current versions of the STRiON:FORTIFY Product Data Sheet and SDS are being used. Call Customer Service (1-800-892-1880) or visit our website (www.atcepoxy.com) to find additional tips, guidelines and specifications. Proper application is the responsibility of the user.

**Technical Service**

Customer Service:

Toll Free 1-800-892-1880

**Email:**

atcinfo@atcepoxy.com

**Web:**

www.atcepoxy.com

**For Chemical/Medical Emergencies:**

Infotrac 800-535-5053

Outside USA 352-323-3500

**WARRANTY**

LIMITED WARRANTY NOTICE. Every reasonable effort is made to apply exacting standards both in the manufacture of our products and in the information that we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, ADHESIVES TECHNOLOGY CORP. MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and ADHESIVES TECHNOLOGY CORP. shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of ADHESIVES TECHNOLOGY CORP.'S Research Director. This information and all further technical advice are based on ADHESIVES TECHNOLOGY CORP.'S present knowledge and experience. However, ADHESIVES TECHNOLOGY CORP. assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, ADHESIVES TECHNOLOGY CORP. disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. ADHESIVES TECHNOLOGY CORP. SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. ADHESIVES TECHNOLOGY CORP. reserves the right to make any changes according to technological progress or further developments. It is the customer's (Authorized Applicator) responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used. ADHESIVES TECHNOLOGY CORP. reserves the right to change specifications referred to in this literature at any time, without prior notice. The information contained herein is, to our knowledge, true and accurate. While this material is furnished in good faith, no warranty expressed or implied, of merchantability, completeness, fitness or otherwise is made. This material is offered only for your consideration, investigation and verification, and ADHESIVES TECHNOLOGY CORP. disclaims any liability incurred from the use thereof and shall not in any event, be liable for any special, incidental or consequential damages arising from such use. This information is not intended to be all inclusive and the manner and conditions of use and handling of any material may involve other or additional considerations specific to the use or user. Nothing herein should be construed as permission or recommendation to infringe any patent or as to any specific use. No agent, representative or employee of this company is authorized to vary any term of this notice.

Refer to [www.atcepoxy.com](http://www.atcepoxy.com) for latest Technical Data Sheet and Safety Data Sheet.

Adhesives Technology Corp., A Meridian Brand, 115 North 1380 West Orem, Utah 84057 801-375-2280

Products manufactured and marketed by Adhesives Technology Corporation are protected by U.S. Patents and pending patents and/or pending patents under license in the United States and other countries.  
Revision date 070925