

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 5/23/2024 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form Product name	: Mixture : 20-3064RNCBK
1.2. Recommended use and restrictions or	n use
Recommended use Restrictions on use	: Potting compound : Not to be used for any purpose other than the one the product was designed for
1.3. Supplier	
Epoxies, Etc. 21 Starline Way Cranston, RI 02921 USA T 401-946-5564 www.epoxies.com	
1.4. Emergency telephone number	
Emergency number	: VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585
SECTION 2: Hazard(s) identification 2.1. Classification of the substance or mix	ture
GHS US classification	
Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Skin sensitization, Category 1 Hazardous to the aquatic environment – Chronic Ha Full text of H statements : see section 16	H315 Causes skin irritation H319 Causes serious eye irritation H317 May cause an allergic skin reaction azard Category 2 H411 Toxic to aquatic life with long lasting effects
2.2. GHS Label elements, including precau	itionary statements
GHS US labeling	
Hazard pictograms (GHS US)	
Signal word (GHS US) Hazard statements (GHS US)	<ul> <li>Warning</li> <li>H315 - Causes skin irritation</li> <li>H317 - May cause an allergic skin reaction</li> <li>H319 - Causes serious eye irritation</li> <li>H411 - Toxic to aquatic life with long lasting effects</li> </ul>
Precautionary statements (GHS US)	<ul> <li>P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.</li> <li>P264 - Wash hands, forearms and face thoroughly after handling.</li> <li>P272 - Contaminated work clothing must not be allowed out of the workplace.</li> <li>P273 - Avoid release to the environment.</li> <li>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P302+P352 - If on skin: Wash with plenty of water.</li> <li>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> </ul>

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P391 - Collect spillage.
P501 - Dispose of contents/container to hazardous or special waste collection point, in
accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification

: Harmful dust may be released during cutting, milling or grinding process.

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

### **SECTION 3: Composition/Information on ingredients**

### 3.1. Substances

#### Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Bisphenol A diglycidyl ether resin	CAS-No.: 25068-38-6	30 – 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Carbon black	CAS-No.: 1333-86-4	< 1	Self-heat. 1, H251 Carc. 2, H351
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs.	CAS-No.: 68609-97-2	< 1	Skin Irrit. 2, H315 Skin Sens. 1, H317

#### Comments

: Components not listed are either non-hazardous or are below reportable limits.

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation First-aid measures after skin contact	<ul> <li>Remove person to fresh air and keep comfortable for breathing.</li> <li>Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.</li> </ul>
First-aid measures after eye contact	<ul> <li>Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.</li> </ul>
First-aid measures after ingestion 4.2. Most important symptoms and eff	: Call a poison center/doctor/physician if you feel unwell. ects (acute and delayed)
Symptoms/effects after skin contact Symptoms/effects after eye contact	: Irritation. May cause an allergic skin reaction. : Eye irritation.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures		
5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.	
5.2. Specific hazards arising from the chemical		
Hazardous decomposition products in case of fire	: Toxic fumes may be released.	
5.3. Special protective equipment and precautions for fire-fighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equip	ment and emergency procedures	
6.1.1. For non-emergency personnel		
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for containment and cleaning up		
For containment Methods for cleaning up Other information	<ul> <li>Collect spillage.</li> <li>Take up liquid spill into absorbent material.</li> <li>Dispose of materials or solid residues at an authorized site.</li> </ul>	

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and store	age
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.
Hygiene measures	Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, in	ncluding any incompatibilities

Storage conditions

: Store in a well-ventilated place. Keep cool.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

8.1. Control parameters		
20-3064RNCBK		
No additional information available		
Carbon black (1333-86-4)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Carbon black (*Not a respirable hazard as contained in this liquid mixture)	
ACGIH OEL TWA	3 mg/m <sup>3</sup> (I - Inhalable particulate matter)	
Remark (ACGIH)	TLV® Basis: Bronchitis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)	
Regulatory reference	ACGIH 2022	
USA - OSHA - Occupational Exposure Limits		
Local name	Carbon black (*Not a respirable hazard as contained in this liquid mixture)	
OSHA PEL TWA [1]	3.5 mg/m <sup>3</sup>	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (	68609-97-2)	
No additional information available		
Bisphenol A diglycidyl ether resin (25068-38-6)		
No additional information available		
8.2. Appropriate engineering controls		
	Ensure good ventilation of the work station. Avoid release to the environment.	
8.3. Individual protection measures/Personal protective equipment		
Hand protection:		
Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear		
Eye protection:		
Safety glasses		
Skin and body protection:		
Wear suitable protective clothing		
Respiratory protection:		
In case of insufficient ventilation, wear suitable respiratory equipment		

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: According to product specification
Odor	: Mild odour
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### **10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions** 

No dangerous reactions known under normal conditions of use.

**10.4. Conditions to avoid** 

None under recommended storage and handling conditions (see section 7).

#### **10.5.** Incompatible materials

No additional information available

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological inform	nation	
<b>11.1. Information on toxicological effe</b> Acute toxicity (oral)	: Not classified	
Acute toxicity (dermal)	: Not classified	
Acute toxicity (inhalation)	: Not classified	
Carbon black (1333-86-4)		
LD50 oral rat	> 8000 mg/kg Source: ECHA	
LD50 oral	8000 mg/kg	
LD50 dermal rabbit	> 8000 mg/kg Source: ECHA	
ATE US (oral)	8000 mg/kg body weight	
Oxirane, 2-[(C12-14-alkyloxy)methyl]	derivs. (68609-97-2)	
LD50 oral rat	26800 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))	
LD50 oral	17100 mg/kg	
ATE US (oral)	17100 mg/kg body weight	
Bisphenol A diglycidyl ether resin (25068-38-6)		
LD50 oral	11400 mg/kg	
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))	
ATE US (oral)	11400 mg/kg body weight	
Skin corrosion/irritation	: Causes skin irritation.	
Carbon black (1333-86-4)		
рН	4 – 10 (5 %, 20 °C)	
Oxirane, 2-[(C12-14-alkyloxy)methyl]	derivs. (68609-97-2)	
рН	No data available in the literature	
Bisphenol A diglycidyl ether resin (25	5068-38-6)	
рН	No data available in the literature	
Serious eye damage/irritation	: Causes serious eye irritation.	
Carbon black (1333-86-4)		
рН	4 – 10 (5 %, 20 °C)	
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)		
рН	No data available in the literature	
Bisphenol A diglycidyl ether resin (25	5068-38-6)	
рН	No data available in the literature	
Respiratory or skin sensitization	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified.	

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon black (1333-86-4)		
Additional information	*Not a respirable hazard as contained in this liquid mixture	
IARC group	2B - Possibly carcinogenic to humans	
Bisphenol A diglycidyl ether resin (25068-38-6)		
NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)	
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)	
Reproductive toxicity :	Not classified	
STOT-single exposure :	Not classified	
STOT-repeated exposure :	Not classified	
Carbon black (1333-86-4)		
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.0071 mg/l air Animal: rat, Animal sex: male	
NOAEL (oral,rat,90 days)	> 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity Study in Rodents)	
NOAEC (inhalation,rat,dust/mist/fume,90 days)	0.0011 mg/l air Animal: rat, Animal sex: male	
Bisphenol A diglycidyl ether resin (25068-38-0	6)	
NOAEL (oral,rat,90 days)	50 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals	
	Not classified No data available	
Carbon black (1333-86-4)		
Viscosity, kinematic	Not applicable (solid)	
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)		
Viscosity, kinematic	No data available in the literature	
Bisphenol A diglycidyl ether resin (25068-38-6)		
Viscosity, kinematic	No data available in the literature	
	Irritation. May cause an allergic skin reaction. Eye irritation.	

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: Toxic to aquatic life with long lasting effects.

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carbon black (1333-86-4)			
LC50 - Fish [1]	> 1000 mg/l Source: NITE		
EC50 - Crustacea [1]	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)		
EC50 72h - Algae [1]	> 10000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
EC50 72h - Algae [2]	> 10000 mg/l Test organisms (species):		
ErC50 algae	> 10000 mg/l Source: EHCA		
Bisphenol A diglycidyl ether resin (25068-38-6)			
LC50 - Fish [1]	1.3 mg/l (96 h, Pisces, Literature study)		
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)		
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)		
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum		
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		

### 12.2. Persistence and degradability

Carbon black (1333-86-4)			
Not rapidly degradable			
Persistence and degradability Biodegradability in soil: not applicable. Biodegradability: not applicable.			
Chemical oxygen demand (COD)	Not applicable (inorganic)		
ThOD	Not applicable (inorganic)		
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (6	68609-97-2)		
Not rapidly degradable			
Persistence and degradability Readily biodegradable in water.			
Bisphenol A diglycidyl ether resin (25068-38-6)			
Not rapidly degradable			
Persistence and degradability         Not readily biodegradable in water.			
12.3. Bioaccumulative potential			
Carbon black (1333-86-4)			
Bioaccumulative potential	Not bioaccumulative.		
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)			
BCF - Fish [1]	160 – 263 (BCFWIN, Estimated value)		
Partition coefficient n-octanol/water (Log Pow)	3.77 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Bisphenol A diglycidyl ether resin (25068-38-6)			
Partition coefficient n-octanol/water (Log Pow) 3 (Estimated value, 25 °C)			
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
12.4. Mobility in soil			
Carbon black (1333-86-4)			
Surface tension	Not applicable (solid)		
Ecology - soil	No (test)data on mobility of the substance available. Not toxic to plants. Not toxic to animals.		
Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)       > 5.63 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental v GLP)			
Ecology - soil	Adsorbs into the soil.		
Bisphenol A diglycidyl ether resin (25068-38-6)			
Surface tension	59 mN/m (20 °C, 0.09 g/l)		
Ecology - soil	No (test)data on mobility of the substance available.		

### **12.5. Other adverse effects**

No additional information available

SECTION 13: Disposal considerations	
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.

# SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA					
DOT TDG		IMDG	ΙΑΤΑ		
14.1. UN number					
3082	UN3082	3082	3082		
14.2. Proper Shipping Name					
Environmentally hazardous substances, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.		
14.3. Transport hazard class(es)					
9	9	9	9		

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT	TDG	IMDG	ΙΑΤΑ
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information availab			
<b>DOT</b> UN-No.(DOT) DOT Special Provisions (49 CFR 172.	: UN3082 102) : 8 - A hazardous sub description "Other re solid materials, spec 146 - This descriptio does not meet the d	stance that is not a hazardous waste n egulated substances, liquid or solid, n.c ial provision B54 applies. n may be used for a material that pose efinition for a hazardous waste or a haz pter, or any hazard class as defined in	s.", as appropriate. In addition, for as a hazard to the environment but zardous substance, as defined in

designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

		materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times
		MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	155
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
DOT Quantity Limitations Passenger aircraft/rail (49	:	No limit
CFR 173.27)		
DOT Quantity Limitations Cargo aircraft only (49	:	No limit
CFR 175.75)		
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a
		passenger vessel.

#### TDG

UN-No. (TDG)

: UN3082

# Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions	<ul> <li>16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3).</li> <li>(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:</li> <li>(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;</li> <li>(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;</li> <li>(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;</li> <li>(d) UN3249, MEDICINE, LIQUID, TOXIC, N.O.S.</li> <li>(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.</li> <li>(f) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.</li> <li>(g) UN2349, MEDICINE, SUBJTANCE, AFFECTING HUMANS; or</li> <li>(h) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or</li> <li>(h) UN290, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or IN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of</li></ul>
	safety.
Explosive Limit and Limited Quantity Index	: 5L
Excepted quantities (TDG)	: E1
Emergency Response Guide (ERG) Number	: 171
IMDG	
Special provision (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A
ΑΤΑ	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provision (IATA)	: A97, A158, A197, A215
	,

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ERG code (IATA)

: 9L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### **15.2. International regulations**

### CANADA

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Oxirane, 2-[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Listed on the Canadian DSL (Domestic Substances List)

Bisph	henol A diglycidyl ether resin (25068-38-6)
Listed	on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

#### **National regulations**

Carbon black (1333-86-4)	
Listed on IARC (International Agency for Research on Cancer) Listed on INSQ (Mexican National Inventory of Chemical Substances)	
15.3. US State regulations	

# **WARNING:** This product can expose you to Carbon black (airborne, unbound particles of respirable size), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

## **SECTION 16: Other information**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases				
H251	I251 Self-heating; may catch fire			
H315	H315 Causes skin irritation			
H317 May cause an allergic skin reaction				

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H319	Causes serious eye irritation
H351	Suspected of causing cancer
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.