

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

1 Identification

- · Product identifier
- · Trade name: EP-15 Grout Component C
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Product description Epoxy Grout
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E-Chem, LLC

4102 El Rey Rd. SE

Albuquerque, NM 87105

Phone: 505.217.2121 Fax: 505.217.3721

Email: mail@e-chem.net Web: www.e-chem.net

Emergency telephone number:

Chemtrec at 1-800-424-9300 24 Hours

Outside the U.S., call Chemtrec collect at 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of

exposure: Inhalative.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- Hazard-determining components of labeling:

Quartz (SiO2)

· Hazard statements

Harmful if inhaled.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 1)

Causes eye irritation.

May cause cancer.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

100 percent of the mixture consists of ingredient(s) of unknown toxicity.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 3 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



· Other hazards None known

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

Dangerous Components:				
	Quartz (SiO2) Carc. 1A, H350; STOT RE 1, H372; Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	70-90%		
CAS: 7727-43-7 RTECS: CR 0600000	barium sulphate, natural	15-35%		

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 2)

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness, place patient securely on side position for transportation.

- · After skin contact: Wash areas with soap and water.
- · After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Refer to section 8

- *Environmental precautions:* No special measures required.
- · Methods and material for containment and cleaning up:

Powder and fragments should be cleaned up using a method that will avoid the generation of dust in the workplace atmosphere. The use of a vacuum cleaner fitted with an exhaust air filter fine enough to trap the dust is recommended.

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 3)

· Information about protection against explosions and fires:

Avoid dust formation and control ignition sources.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

Components with occupational exposure limits:					
1480	14808-60-7 Quartz (SiO2)				
PEL	see Quartz listing				
REL	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A				
TLV	Long-term value: 0.025* mg/m³ *as respirable fraction				
7727	7727-43-7 barium sulphate, natural				
PEL	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction				
REL	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction				
TLV	Long-term value: 5* mg/m³ *inhalable fraction; E				

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 4)

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Color:
Odor:
Odor threshold:
Powder
White
Odorless
Not determined.

Ph-value:
Not applicable.

· Change in condition

Melting point/Melting range:
 Boiling point/Boiling range:

 Flash point:
 Flammability (solid, gaseous):

 1610 °C (2930 °F)
Not determined.
 Not applicable.
 Not determined.

· Ignition temperature:

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

Danger of explosion:
 Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.Upper: Not determined.Vapor pressure: Not applicable.

• **Density @ 20 °C (68 °F):** 2.66 g/cm³ (22.198 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

Water: Soluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not applicable. **Kinematic:** Not applicable.

· Solvent content:

Organic solvents: 0.0 %
Solids content: 100.0 %

• Other information No further relevant information available.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: Hydrogen Fluoride
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritating effect.
- on the eye:

Irritating effect.

Causes serious eye irritation.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
14808-60-7 Quartz (SiO2)	1
· NTP (National Toxicology Program)	
14808-60-7 Quartz (SiO2)	K
OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Generally not hazardous for water
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Non-Regulated Material

· Packing group

· DOT, ADR, IMDG, IATA Non-Regulated Material

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulphate, natural

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- · Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 7)

· Carcinogenic categories

· EPA (Envir	onmental Protection Agency)			
7727-43-7 barium sulphate, natural D, CBD(inh		D, CBD(inh), NL(oral)		
· TLV (Thres	hold Limit Value established by ACGIH)			
14808-60-7	Quartz (SiO2)	A2		
· NIOSH-Ca (National Institute for Occupational Safety and Health)				
14808-60-7	Quartz (SiO2)			

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Quartz (SiO2)

· Hazard statements

Harmful if inhaled.

Causes eye irritation.

May cause cancer.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP-15 Grout Component C

(Contd. of page 8)

· State Right to Know		
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO2) Carc. 1A, H350; STOT RE 1, H372; Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	70-90%
CAS: 7727-43-7 RTECS: CR 0600000	barium sulphate, natural	15-35%
All ingredients are liste	ed.	

[·] Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of preparation / last revision 01/21/2015 / 3
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Carc. 1A: Carcinogenicity, Hazard Category 1A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106