

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21

inting date 01/21/2015	Reviewed on 01/21/2015
1 Identification	
· Product identifier	
<ul> <li>Trade name: EP Clearseal Component A</li> <li>CAS Number: 25068-38-6</li> <li>NLP Number: 500-033-5</li> <li>Index number: 603-074-00-8</li> <li>Relevant identified uses of the substance or mixture and uses add No further relevant information available.</li> </ul>	vised against

- Product description Clear epoxy sealer
- · Details of the supplier of the safety data sheet · Manufacturer/Supplier: E-Chem, LLC 4102 El Rey Rd. SE Albuquerque, NM 87105 Phone: 505.217.2121 Fax: 505.217.3721 Email: mail@e-chem.net Web: www.e-chem.net · Emergency telephone number: Chemtrec at 1-800-424-9300 24 Hours
- Outside the U.S., call Chemtrec collect at 703-527-3887

Hazard(s) identification

### · Classification of the substance or mixture

**GHS09** Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.	
Eye Irrit. 2	H319 Causes serious eye irritation.	
Skin Sens. 1	H317 May cause an allergic skin rea	ction.

## · Label elements

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: EP Clearseal Component A

(Contd. of page 1)

· Hazard-determining components of labeling:
Epoxy resin
Hazard statements
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.
Precautionary statements
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves.
Wear eye protection / face protection.
Avoid release to the environment.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If on skin: Wash with plenty of water.
Collect spillage.
Take off contaminated clothing and wash it before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Unknown acute toxicity:
100 percent of the mixture consists of ingredient(s) of unknown toxicity.
· Classification system:
· NFPA ratings (scale 0 - 4)
Health = 1
Fire = 1
1  0 Reactivity = 0
· HMIS-ratings (scale 0 - 4)
HEALTH 1 Health = 1
FIRE 1 Fire = 1
REACTIVITY Reactivity = 0
· Other hazards None known
3 Composition/information on ingredients
· Chemical characterization: Substances

• CAS No. Description 25068-38-6 Epoxy resin

- Identification number(s)
- NLP Number: 500-033-5
- · Index number: 603-074-00-8

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: EP Clearseal Component A

(Contd. of page 2)

## 4 First-aid measures

- Description of first aid measures
- After inhalation:

In case of unconsciousness, place patient securely on side position for transportation.

- Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

• After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

• After swallowing:

Never give anything by mouth to an unconscious person. Rinse out mouth and then drink plenty of water. Seek medical treatment.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## 5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

<u>6 Accidental release measures</u>

- · Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:
- Ensure adequate ventilation.

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Avoid contact with skin, eyes and clothing



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

## Trade name: EP Clearseal Component A

Reviewed on 01/21/2015

(Contd. of page 3)

Page 4/9

Avoid breathing fume/gas/mist/vapors/spray. Do not take internally. Use personal protection equipment as outlined in section 8.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Store in a cool, dry place. Store in a well ventilated place.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- · Components with occupational exposure limits:
- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

• Eye protection: Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:	Liquid
Color:	Clear
· Odor:	Solvent-like
· Odor threshold:	Not determined.
· pH-value:	Not applicable.

(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: EP Clearseal Component A

Change in condition Melting point/Melting range: Boiling point/Boiling range:	Not determined. Not determined.
Flash point:	252 °C (486 °F)
Flammability (solid, gaseous):	Product is not flammable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Vapor pressure @ 77 °C (171 °F):	0.04 hPa
Density @ 20 °C (68 °F): Relative density Vapour density Evaporation rate	1.1 g/cm³ (9.18 lbs/gal) Not determined. Not applicable. Not applicable.
Solubility in / Miscibility with Water:	Soluble.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity: Dynamic: Kinematic: Organic solvents:	Not applicable. Not applicable. 0.0 %
Solids content: Other information	100.0 % No further relevant information available.

· Reactivity No further relevant information available.

· Chemical stability Stable under normal conditions.

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

· Incompatible materials:

Strong oxidizing agents.

Strong acids, strong bases

· Hazardous decomposition products: Carbon dioxide, carbon monoxide and nitrogen oxides.

## 1 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin:

Irritant to skin and mucous membranes.

Page 5/9

(Contd. of page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

## Trade name: EP Clearseal Component A

Reviewed on 01/21/2015

(Contd. of page 5)

May cause an allergic skin reaction.

- on the eye:
- Irritating effect.

Causes serious eye irritation.

- Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:
- · Carcinogenic categories
- IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

## 2 Ecological information

#### · Toxicity

· Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

#### · Waste treatment methods

· Recommendation:

It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · *Recommended cleansing agent:* Water, if necessary with cleansing agents.



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: EP Clearseal Component A

	(Contd. of pa
Transport information	
UN-Number DOT ADR, IMDG, IATA	Non-Regulated Material UN3077
UN proper shipping name DOT	Non-Regulated Material
ADR	UN3077 Environmentally hazardous substances, solid, n (EP Clearseal Component A)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SO N.O.S. (EP Clearseal Component A), MARINE POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SO N.O.S. (EP Clearseal Component A)
Transport hazard class(es)	
DOT Class	Non-Regulated Material
ADR	
Class Label	9 (M6) Miscellaneous dangerous substances and articles 9
IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles 9
Packing group	3
DOT	Non-Regulated Material
ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Danger code (Kemler): EMS Number:	90 F-A,S-F
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	
Transport/Additional information:	
ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g (Contd. on pa



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

## Printing date 01/21/2015

Trade name: EP Clearseal Component A

Reviewed on 01/21/2015

· Remarks:	(Contd. of page 7) VkBI. Nr.191 (A44/27.10.71-50-04)
·IMDG	
<ul> <li>Limited quantities (LQ)</li> </ul>	5 kg
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 g
	Maximum net quantity per outer packaging: 1000 g
• UN "Model Regulation":	UN3077, Environmentally hazardous substances, solid, n.o.s.
	(EP Clearseal Component A), 9, III
15 Regulatory information	
· Safety, health and environmental regulations/legislation specific for the substance or mixture	

Section 355 (e	xtremely hazardous substances):
Substance is n	t listed.
Section 313 (	pecific toxic chemical listings):
Substance is n	ot listed.
TSCA (Toxic :	ubstances Control Act):
Substance is li	ted.
Proposition 6	
	own to cause cancer:
Substance is n	it listed.
Chemicals kn	own to cause reproductive toxicity for females:
Substance is n	t listed.
Chemicals kn	own to cause reproductive toxicity for males:
Substance is n	ot listed.
Chemicals kn	own to cause developmental toxicity:
Substance is n	t listed.
Carcinogenic	categories
EPA (Environ	nental Protection Agency)
Substance is n	t listed.
TLV (Thresho	d Limit Value established by ACGIH)
Substance is n	t listed.
NIOSH-Ca (Na	tional Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Warning



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: EP Clearseal Component A

(Contd. of page 8)

Hazard-determining components of labeling:
Epoxy resin
Hazard statements
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.
· Precautionary statements
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves.
Wear eye protection / face protection.
Avoid release to the environment.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If on skin: Wash with plenty of water.
Collect spillage.
Take off contaminated clothing and wash it before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· National regulations:
Substance is not listed.
· State Right to Know
Substance is not listed.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
16 Other information

6 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

### • Date of preparation / last revision 01/21/2015 / 3

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106