

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

1 Identification

- **Product identifier**
- **Trade name: Pile Anchor Grout - Component B**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Product description** Epoxy Grout
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
E-Chem, LLC
4102 El Rey Rd. SE
Albuquerque, NM 87105
Phone: 505.217.2121
Fax: 505.217.3721
Email: mail@e-chem.net
Web: www.e-chem.net
- **Emergency telephone number:**
Chemtrec at 1-800-424-9300 24 Hours
Outside the U.S., call Chemtrec collect at 703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07



GHS08

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 1)

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Tall Oil Fatty Acids, Reaction Product With Tiethylenetetramine triethylenetetramine
- **Hazard statements**
Harmful if swallowed or in contact with skin.
Causes severe skin burns and eye damage.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
Do not breathe dusts or mists.
Wear respiratory protection.
Wear protective gloves.
Wear protective gloves / protective clothing.
Wear eye protection / face protection.
Avoid release to the environment.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
If swallowed: Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
If experiencing respiratory symptoms: Call a poison center/doctor.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If swallowed: Rinse mouth. Do NOT induce vomiting.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Unknown acute toxicity:**
50 percent of the mixture consists of ingredient(s) of unknown toxicity.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards** None known

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous Components:**

112-24-3	triethylenetetramine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-50%
68919-79-9	Tall Oil Fatty Acids, Reaction Product With Triethylenetetramine ⚠ Resp. Sens. 1B, H334; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Irrit. 2B, H320	25-50%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness, place patient securely on side position for transportation.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Use neutralizing agent.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 3)

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin, eyes and clothing

Avoid breathing fume/gas/mist/vapors/spray.

Do not take internally.

Use personal protection equipment as outlined in section 8.

· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with occupational exposure limits:**

112-24-3 triethylenetetramine

WEEL Long-term value: 6 mg/m³, 1 ppm

Skin

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 4)

- **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:** Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Clear

- **Odor:** Amine-like

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Not determined.

Boiling point/Boiling range: 278 °C (532 °F)

- **Flash point:** 135 °C (275 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 335 °C (635 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapor pressure:** Not determined.

- **Density @ 20 °C (68 °F):** 0.961 g/cm³ (8.02 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

- **Solvent content:**

Organic solvents: 0.0 %

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

- **Chemical stability** Stable under normal conditions.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 5)

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:**
 Strong oxidizing agents.
 Strong acids, strong bases
- **Hazardous decomposition products:** Carbon dioxide, carbon monoxide and nitrogen oxides.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

112-24-3 triethylenetetramine

Oral	LD50	2500 mg/kg (rat)
Dermal	LD50	805 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:**

Strong caustic effect on skin and mucous membranes.
 May cause an allergic skin reaction.

- **on the eye:**

Strong irritant with the danger of severe eye injury.
 Corrosive effect.
 Causes serious eye irritation.

- **Sensitization:**

Sensitization possible through inhalation.
 Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful
 Corrosive
 Irritant

Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

Group 1 - Carcinogenic to humans
Group 2A - Probably carcinogenic to humans
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
Group 4 - Probably not carcinogenic to humans

- **NTP (National Toxicology Program)**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 6)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Do not allow product to reach sewage system.
It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste.
State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT** UN3267
- **ADR, IMDG, IATA** UN2259
- **UN proper shipping name**
- **DOT** Corrosive liquid, basic, organic, n.o.s. (Triethylenetetramine)
- **ADR** UN2259 Triethylenetetramine mixture
- **IMDG, IATA** TRIETHYLENETETRAMINE mixture
- **Transport hazard class(es)**

· **DOT**



- **Class** 8 Corrosive substances

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 7)

· **Label** 8

· **ADR**



· **Class** 8 (C7) Corrosive substances

· **Label** 8

· **IMDG, IATA**



· **Class** 8 Corrosive substances

· **Label** 8

· **Packing group**

· **DOT, ADR, IMDG, IATA** II

· **Environmental hazards:**

· **Marine pollutant:** No

· **Special precautions for user** Warning: Corrosive substances

· **Danger code (Kemler):** 80

· **EMS Number:** F-A,S-B

· **Segregation groups** Alkalis

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 1 L
On cargo aircraft only: 30 L

· **ADR**

· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN2259, Triethylenetetramine mixture, 8, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 8)

· Section 313 (Specific toxic chemical listings):
None of the ingredients are listed.
· TSCA (Toxic Substances Control Act):
All ingredients are listed.
· Proposition 65
· Chemicals known to cause cancer:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.
· Chemicals known to cause developmental toxicity:
None of the ingredients are listed.
· Carcinogenic categories
· EPA (Environmental Protection Agency)
None of the ingredients are listed.
· TLV (Threshold Limit Value established by ACGIH)
None of the ingredients are listed.
· NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients are listed.

- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
Tall Oil Fatty Acids, Reaction Product With Triethylenetetramine triethylenetetramine
- **Hazard statements**
Harmful if swallowed or in contact with skin.
Causes severe skin burns and eye damage.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
Do not breathe dusts or mists.
Wear respiratory protection.
Wear protective gloves.
Wear protective gloves / protective clothing.
Wear eye protection / face protection.
Avoid release to the environment.

(Contd. on page 10)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 9)

Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Contaminated work clothing must not be allowed out of the workplace.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Immediately call a poison center/doctor.
 If swallowed: Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 If experiencing respiratory symptoms: Call a poison center/doctor.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Wash contaminated clothing before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If swallowed: Rinse mouth. Do NOT induce vomiting.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

State Right to Know

112-24-3	triethylenetetramine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-50%
68919-79-9	Tall Oil Fatty Acids, Reaction Product With Triethylenetetramine ⚠ Resp. Sens. 1B, H334; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1B, H317; Eye Irrit. 2B, H320	25-50%

All ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of preparation / last revision 01/21/2015 / 3

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 Acute Tox. 4: Acute toxicity, Hazard Category 4
 Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component B

(Contd. of page 10)

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Resp. Sens. 1B: Sensitisation - Respirat., Hazard Category 1B
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106