

Version: 2 Issue Date: 6-26-2015 Revision Date: 8-4-2022

ASI 335WS Clear

Section 1: Product and Company Identification

American Sealants, Inc. Emergency Phone Number

9190 Yeager Ln Infotrac: +1-800-535-5053 (Within US)
Fort Wayne, Indiana 46809 Infotrac: +1-352-323-3500 (Outside US)

Phone: 260-489-0728 Fax: 260-489-0519

Product Identifier: ASI 335WS Clear

Recommended Use: RTV rubbers (electrical, electronic and general industry (gluing and sealing))

Restrictions on Use: Industrial use only.

Section 2: Hazard(s) Identification

Physical Hazards Not classified

Health Hazards Serious eye damage/eye irritation Category 2

Sensitization, skin Category 1
Reproductive toxicity (fertility) Category 2

Specific target organ toxicity, Category 2 (hematopoietic system)

repeated exposure

Environmental Hazards Not classified

OSHA defined hazards Not classified

* Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible"

Label Elements



Signal Word Warning

Hazard Statement Causes serious eye irritation. May cause an allergic skin reaction.

Suspected of damaging fertility. May cause damage to organs (hematopoietic system) through prolonged or repeated exposure.

Precautionary Statement

Prevention Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Do not breathe

dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash

ResponseIF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Get medical advice/attention if you

feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing

and wash it before reuse.

Storage Store locked up.

DisposalDispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified

(HNOC)

None known

None

Supplemental information

Substance(s) formed under the

condition of use

This product reacts with water, moisture or humid air to evolve following

compounds:

Methylethylketoxime

HMIS®ratings Health: 2*

Flammability: 1 Physical Hazard: 0

Section 3: Composition/Information on Ingredients

<u>CAS</u>	Component	<u>Percent</u>		
Proprietary	Methyloximesilane*	1 - < 3		
Proprietary	Vinyloximesilane*	< 1		
Proprietary	Alkoxysilane*	< 1		
96-29-7	Methylethylketoxime (Impurity)	< 1		
556-67-2	Octamethylcyclotetrasiloxane (Impurity)	< 1		
*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.				

Section 4: First-Aid	Measures

Inhalation: Move to fresh	air. Call a physician if sympto	toms develop or persist
----------------------------------	---------------------------------	-------------------------

Skin Contact Wash off with soap and plenty of water. For minor skin contact, avoid spreading

material on unaffected skin.

If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eye Contact Rinse immediately with plenty of water for at least 15 minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. Get medical attention if irritation develops

and persists.

Ingestion Rinse mouth. Get medical attention immediately.

Most important symptoms/effects, acute and delayed Indication of

Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction.

Prolonged exposure may cause chronic effects.

dication of Treat Symptomatically

Indication of immediate medical attention and special treatment needed

Issue Date: 6-26-2015 Page **2** of **10**

Product Identifier: ASI 335WS Clear Version: 2

General If exposed or concerned: Information Get medical advice/attention.

> Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Wash contaminated clothing before reuse.

Section 5: Fire-Fighting Measures

Suitable Extinguishing Media: Use carbon dioxide, regular dry chemical powder, foam, or water fog.

Unsuitable Extinguishing Media: None known.

Specific Hazards Arising from the

Chemical

Specific protective equipment and

precautions for firefighters

Fire-fighting equipment/instructions

General fire hazards

By heating and fire, harmful vapors/gases may be formed. Nitrogen oxides. (corrosive)

Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots, and self-contained

breathing apparatus.

Move containers from fire area if you can do so without risk.

No unusual fire or explosion hazards noted

Section 6: Accidental Release Measures

Personal Precautions, Protective

Equipment and Emergency Procedures:

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch or walk-through spilled material. Ensure adequate ventilation. Wear appropriate personal protective equipment.

Methods and Materials for **Containment and Cleaning Up:** Eliminate sources of ignition.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and

place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. Prevent further leakage or spillage if safe to do so.

Environment Precautions:

Section 7: Handling and Storage

Precautions for Safe Handling Provide adequate ventilation. Use care in handling/storage. Obtain

> special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or

vapor. Avoid contact with eyes. Avoid contact with skin.

Conditions for Safe Storage, including

any Incompatibilities:

Store locked up. Keep in original container and tightly closed. Keep out of the reach of children. Store in a cool, dry place out of direct sunlight.

Keep in original container.

Issue Date: 6-26-2015 Page 3 of 10

10 ppm

Section 8: Exposure Controls/Personal Protection
--

Occupational Exposure Limits

US. Workplace Environmental Exposure Lebel (WEEL) Guides

Components Type Methylethylketoxime **TWA** 36 mg/m3

(Impurity) (CAS 96-29-7)

Vendor Guide

Components Value Type Methylethylketoxime **STEL** 10 ppm (Impurity) (CAS 96-29-7) 3 ppm **TWA**

Biological limit values No biological exposure limits noted for the ingredient(s)

Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Provide evewash station. Pay attention to ventilation such as local exhaust, mechanical and/or door open for

Total dust

at least 24 hours after application.

Individual protection measures, such as personal protective equipment

Eye/face protection Tightly sealed safety glasses according to EN 166

Skin protection

Hand

Wear protective gloves

protection Other Wear suitable protective clothing

Respiratory If airborne concentrations are above the applicable exposure limits, use NIOSH

protection approved respiratory protection.

Thermal Hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

or explosive limits

Avoid contact with eyes. Avoid contact with skin. When using, do not eat, drink or smoke. Keep away from food and drink. Wash hands before breaks and

immediately after handling the product. Contaminated work clothing should not be

allowed out of the workplace. Handle in accordance with good industrial hygiene

and safety practice.

Section	q.	Physical	and	Chemical	Properties
Jechon	J.	riivsicai	allu	Circillica	i riobeities

Appearance Paste Color: Translucent Odor: Oxime odor **Odor Threshold:** Not available pΗ: Not applicable **Melting Point/freezing** Not applicable point:

Initial boiling point and Not applicable

Flash point:

204.8 °F (96 °C) Closed

boiling range: cup

Evaporation Rate: < 1 (Butyl Acetate=1) Upper/lower flammability No data

Flammability (soild, gas) Not applicable **Vapor Pressure:** Negligible (25 °C)

Vapor Density (air = 1): > 1 (air=1) **Density:**

1.03 (25 °C) Partition Coefficient (n-Not applicable

Water Solubility Not soluble

octanol/water)

Not available Auto Ignition: Decomposition Not available

temperature

Issue Date: 6-26-2015 Page 4 of 10

Product Identifier: ASI 335WS Clear Version: 2

Viscosity: Not applicable **Molecular Formula:** Not applicable

Section 10: Stability and Reactivity

Reactivity: No hazardous reaction known under normal conditions of use, storage

and transport.

Stable at normal temperatures and pressure. Chemical Stability: Hazardous polymerization does not occur. Possibility of Hazardous Reactions:

Conditions to Avoid: None known.

Incompatible Materials: Strong oxidizing materials, water, moisture

Hazardous Decomposition Products: This product reacts with water, moisture or humid air to evolve

> following compounds: Methylethylketoxime. Refer to section 8: exposure controls/personal protection and section 11: toxicological

information.

Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon oxides and traces of incompletely burned carbon compounds.

Silicon dioxide, Nitrogen oxides, and Formaldehyde.

Section 11: Toxicological Information

Information on Likely Routes of Exposure

Ingestion: No significant effects are expected. No significant effects are expected. Inhalation: **Skin Contact:** May cause an allergic skin reaction. **Eye Contact:** Causes serious eye irritation.

Symptoms related to the physical,

chemical, and toxicological

characteristics

Dermatitis. Rash. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin

reaction.

Information on toxicological effects

Acute Toxicity

CAS	Component	Result	Species	Dose	Exposure
		LD50 Oral	Rat	2995 mg/kg 2400 mg/kg	N/A
Proprietary	Alkoxysilane	LC50 Inhalation	Rat	1.49-2.44 mg/L	4 hr
		LD50 Dermal	Rabbit	>2000 mg/kg 16 ml/kg	N/A
96-297	Methylethylketoxime (Impurity)	LD50 Oral	Rat	930 mg/kg	N/A
		LD50 Dermal	Rabbit	200 μl/kg	N/A

Skin corrosion/irritation SKIN-RABBIT: Moderately irritating [Alkoxysilane]

SKIN-RABBIT: 500mg/24 r MILD [Octamethylcyclotetrasiloxane]

Serious eye damage/eye irritation Causes serious eye damage. [Vinyloximesilane] [Methylethylketoxime]

EYE-RABBIT: 15 mg SEVERE [Alkoxysilane]

Issue Date: 6-26-2015 Page **5** of **10**

Product Identifier: ASI 335WS Clear Version: 2

Causes serious eye irritation [Methyloximesilane]

EYE-RABBIT: MILD [Octamethylcyclotetrasiloxane]

Respiratory or skin sensitization

Respiratory sensitization Not available

Skin sensitization May cause an allergic skin reaction.

[Methyloximesilane][Vinyloximesilane][Methylethylketoxime]

Positive (Guinea Pig) [Alkoxysilane]

No evidence of sensitization [Octamethylcyclotetrasiloxane] Negative(Ames test, Chromosome analysis, Micronucleus test)

[Alkoxysilane]

Negative(Bacteria) [Octamethylcyclotetrasiloxane]

Carcinogenicity: Suspected of causing cancer. [Methylethylketoxime]

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Germ Cell mutagenicity

Reproductive toxicity Octamethylcyclotetrasiloxane administered to rats by whole body

inhalation at concentrations of 500 and 700 ppm for 70 days prior to mating, through mating, gestation and lactation resulted in decreases in live litter size. Additionally, increases in the incidence of deliveries of offspring extending over an unusually long time period (dystocia) were observed at these concentrations. Statistically significant alterations in these parameters were not observed in the lower concentrations evaluated (300 and 70 ppm). In a previous range-finding study, rats exposed to vapor concentrations of 700 ppm had decreases in the number of implantation sites and live litter size. The significance of these findings to humans is not known. [Octamethylcyclotetrasiloxane] Developmental toxicity: NOAEL 500mg/kg/day (Rat), Maternal toxicity:

NOAEL 500mg/kg/day (Rat) [Alkoxysilane]

Specific target organ toxicity-single

exposure

Not available

Specific Target Organ Toxicity -

Repeated Exposure:

May cause damage to the following organs through prolonged or

repeated exposure:

Hematopoietic system.[Vinyloximesilane]
Hematopoietic system.[Methyloximesilane]

Repeated inhalation or oral exposure of mice and rats to

octamethylcyclotetrasiloxane produced an increase in liver size. No gross histopathological or significant clinical chemistry effects were observed. An increase in liver metabolizing enzymes, as well as a transient increase in the number of normal cells (hyperplasia) followed by an increase in cell size (hypertrophy) were determined to be the underlying causes of the liver enlargement. The biochemical mechanisms producing these effects are highly sensitive in rodents, while similar mechanisms in humans are insensitive. A two year combined chronic and carcinogenicity assay was conducted on octamethylcyclotetrasiloxane. Rats were exposed by wholebody vapor inhalation 6hrs/day, 5days/week for up to 104weeks to 0, 10, 30, 150 or 700ppm of octamethylcyclotetrasiloxane. The increase in incidence of (uterine) endometrial cell hyperplasia and uterine adenomas (benign tumors) were observed in female rats at 700ppm. Since these effects only occurred at 700ppm, a level that greatly exceeds typical workplace or consumer exposure, it is unlikely that industrial, commercial

Issue Date: 6-26-2015 Page **6** of **10**

Product Identifier: ASI 335WS Clear Version: 2

or consumer uses of products containing octamethylcyclotetrasiloxane

would result in a significant risk to humans.

[Octamethylcyclotetrasiloxane]

Aspiration Hazard Not available
Chronic effects Not available

Further Information: Methyl Ethyl Ketoxime (MEKO). Material will generate MEKO on exposure

to humid air gradually. Male rodents exposed to MEKO vapor at high concentration throughout their lifetime developed liver cancer. But relevance to humans is uncertain now. Please read the detail information

to MEKO below:

Skin Irritation Causes mild irritation. Can be absorbed through the

skin.

Eyes Irritation Causes severe irritation
Acute Oral Tox. LD50(rat)=>900 mg/kg
Acute Dermal Tox. LD50(rabbit)=>1000 mg/kg
Acute Inhalation Tox. LD50(rat)>4.83 mg/l/4 hr

Inhalation Tox. Shows narcotic action at high concentration. May

produce blood effects

Skin Sensitization Positive (guinea pig)

Neurotoxicity High dose can produce transient and reversible change

in neurobehavioral function.

Carcinogenicity Liver carcinomas were observed in a lifetime inhalation study (ca.2 years) in which mice and rats were exposed.

Other Chronic Study Degenerative effects on the olfactory epithelium of nasal passages occurred in a concentration related manner in males and females of mice and rats at MEKO concentration of 15,75, and 375 ppm. The significant change in hematological parameters were observed at 404 ppm concentration.

Workplace Environmental Exposure Level

Vendor Guide 3ppm (TWA), 10ppm (STEL), AIHA WEEL, 10ppm

(TWA)

Section 12: Ecological Information

Ecotoxicity

Toxic to aquatic life. Toxic to aquatic life with long lasting effects. [Alkoxysilane] May cause long lasting harmful effects to aquatic life. [Octamethylcyclotetrasiloxane]

Component Analysis - Aquatic Toxicity

CAS	Component	Aquatic	Result	Species	Dose	Exposure
			LC50	Bluegill (Lepomis macrochirus)	>100 mg/L	96 hr
Proprietary	Alkoxysilane	Fish	LC50	Fathead minnow (Pimephales promelas)	>100 mg/L	96 hr

Issue Date: 6-26-2015 Page **7** of **10**

Product Identifier: ASI 335WS Clear Version: 2

			LC50	Rainbow trout (Oncorhynchus mykiss)	>100 mg/L	96 hr
		Algon	EbC50	Green algae (Selenastrum capricornutum)	5.5 mg/L	72 hr
		Algae	ErC50	Green algae (Selenastrum capricornutum)	8.8 mg/L	72 hr
96-29-7	Methylethylketoxime (Impurity)	Fish	LC50	Fathead minnow (Pimephales promelas)	777-914 mg/L	96 hr

Persistence and Degradability: Causes easily hydrolysis in water or atmosphere. [Alkoxysilane]

Bioaccumulative Potential: Bio concentration Factor(BCF) / (Fathead minnows): 12400

[Octamethylcyclotetrasiloxane]

Mobility in soilNot availableOther adverse effectsNot available

Section 13: Disposal Considerations

Disposal instructions Follow applicable Federal, State and Local regulations

Section 14: Transport Information

DOT

Not regulated as dangerous goods

IATA

Not regulated as dangerous goods

IMDG

Not regulated as dangerous goods

Transport in bulk according to Annex

II of MARPOL 73/78 and IBC Code

This product is not intended to be transported in bulk

Section 15: Regulatory Information

US Federal RegulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Issue Date: 6-26-2015 Page **8** of **10**

Product Identifier: ASI 335WS Clear Version: 2

SARA 313 (TRI reporting)

US State regulations

US. Massachusetts RTK - Substance List

Not regulated

US. New Jersey Worker and Community Right-to-Know Act

Not listed

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed

US. Rhode Island RTK

Not regulated

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not know to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory if Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory if Existing Chemical	Yes
	Substances in China (IECSC)	
Europe	European Inventory of Existing	Yes
	Commercial Chemical Substances	
	(EEINECS)	
Europe	European List of Notified Chemical	No
	Substances (ELINCS)	
Japan	Inventory of Existing and New	Yes
•	Chemical Substance (ENCS)	
Korea	Existing Chemical List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals	Yes
	and Chemical Substances (PICCS)	
United States & Puerto Rico	Toxic Substances Control Act (TSCA)	Yes
	Inventory	
* A "Yes" indicates that all compo	onents of this product comply with the inv	entory requirements administered by
the governing country(s)		

У the governing country(s)

Section 16: Other Information

Issue Date: 6-26-2015 **Revision Date:** 8-4-2022

Revision: 2

NFPA Ratings:

Health: 2 Fire: 1

Issue Date: 6-26-2015 Page **9** of **10**

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Product Identifier: ASI 335WS Clear Version: 2

Reactivity: 0



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS III:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

Key/Legend:

AICS (Australia); DSL (Canada); IECSC (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIoC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA PO – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA PO / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

End of Document

Issue Date: 6-26-2015 Page **10** of **10**