

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

#### 1 Identification

- · Product Identifier
- · Trade Name: EP-MV Component A
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Product Description: Medium-viscosity epoxy adhesive
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  E-Chem, LLC
  4102 EI Rey Rd. SE
  Albuquerque, NM 87105
  Phone: 505.217.2121
  Fax: 505.217.3721
  Email: mail@e-chem.net
  Web: www.e-chem.net
  Emergency telephone number:
  Chemtrec at 1-800-424-9300 24 Hours
- Outside the U.S., call Chemtrec collect at 703-527-3887

#### 2 Hazard(s) identification

#### · Classification of the substance or mixture



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2A	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

#### · Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



- · Signal word Warning
- *Hazard-determining components of labeling:* Epoxy resin
- *Hazard statements* Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Trade name: EP-MV Component A

Reviewed on 01/21/2015

(Contd. of page 1)

50-75%

· Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

#### Collect spillage.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

62.5 percent of the mixture consists of ingredient(s) of unknown toxicity.

- Classification system:
- NFPA ratings (scale 0 4)



#### HMIS-ratings (scale 0 - 4)



- Other hazards None known
- 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous Components:

### 25068-38-6 Epoxy resin

Aquatic Chronic 2, H411; 🚸 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, **Н**317

# <u>4 First-aid measures</u>

#### Description of first aid measures

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely on side position for transportation.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor. (Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

#### Trade name: EP-MV Component A

Reviewed on 01/21/2015

(Contd. of page 2)

- · After swallowing: Seek medical treatment.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

#### 6 Accidental release measures

• **Personal precautions, protective equipment and emergency procedures** Not required.

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose of the collected material according to regulations.

- Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### 7 Handling and storage

#### · Handling:

Precautions for safe handling

Use personal protection equipment as outlined in section 8. Avoid breathing fumes. Ensure good ventilation/exhaustion at the workplace.

Ensure good ventilation/exhaustion at the w

Do not take internally.

· Information about protection against explosions and fires: No special measures required.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

#### Trade name: EP-MV Component A

Reviewed on 01/21/2015

(Contd. of page 3)

#### <u>8 Exposur</u>e controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- Control parameters
- Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Tightly sealed goggles

#### 9 Physical and chemical properties

Information on basic physical and chemical properties

• General Information	
· Appearance:	
Form:	Liquid
Color:	See product specification
· Odor:	Mild
· Odor threshold:	Not determined.
· pH-value:	Not determined.
• Change in condition	
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not determined.
· Flash point:	> 93 °C (> 199 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

#### Trade name: EP-MV Component A

Reviewed on 01/21/2015

		(Contd. of page 4)
• Danger of explosion:	Product does not present an explosion hazard.	
• Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure:	Not determined.	
<ul> <li>Density @ 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapour density</li> <li>Evaporation rate</li> </ul>	1.1 g/cm <sup>3</sup> (9.18 lbs/gal) Not determined. Not determined. Not determined.	
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water	): Not determined.	
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> </ul>	Not determined. Not determined.	
<ul> <li>Solvent content:</li> <li>Organic solvents:</li> <li>Other information</li> </ul>	0.0 % No further relevant information available.	
10 Stability and reactivity		

- · *Reactivity* No further relevant information available.
- · Chemical stability Stable under normal conditions.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Causes skin irritation
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- · Carcinogenic categories
- *IARC (International Agency for Research on Cancer)* None of the ingredients are listed.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Trade name: EP-MV Component A

Reviewed on 01/21/2015

(Contd. of page 5)

Page 6/9

Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 2B - Possibly carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans

#### · NTP (National Toxicology Program)

None of the ingredients are listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

#### 2 Ecological information

#### · Toxicity

- Aquatic toxicity:
- Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · *Bioaccumulative potential* No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

3 Disposal considerations

#### · Waste treatment methods

• Recommendation:

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

#### 14 Transport information

- · UN-Number
- · DOT, ADR, ADN, IATA
- ·IMDG
- · UN proper shipping name
- · DOT, ADR, ADN, IATA

Non-Regulated Material UN3082

Non-Regulated Material



Printing date 01/21/2015

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Page 7/9

Reviewed on 01/21/2015

Trade name: EP-MV Component A (Contd. of page 6) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, ·IMDG N.O.S. (Epoxy resin), MARINE POLLUTANT · Transport hazard class(es) · DOT, ADR, ADN, IATA Non-Regulated Material · Class ·IMDG · Class 9 Miscellaneous dangerous substances and articles · Label 9 · Packing group Ш · DOT, ADR, IATA Non-Regulated Material ·IMDG Ш Product contains environmentally hazardous substances: Epoxy · Environmental hazards: resin Yes · Marine pollutant: Symbol (fish and tree) · Special precautions for user Not applicable. • EMS Number: F-A,S-F Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. • Transport/Additional information: ·IMDG · Limited quantities (LQ) 5L • Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml • UN "Model Regulation": Regulatory information · Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara · Section 355 (extremely hazardous substances): None of the ingredients are listed.

- Section 313 (Specific toxic chemical listings): None of the ingredients are listed.
- TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:
- None of the ingredients are listed.
- · Chemicals known to cause reproductive toxicity for females:
- None of the ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Trade name: EP-MV Component A

Reviewed on 01/21/2015

(Contd. of page 7)

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

• Chemicals known to cause developmental toxicity: None of the ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients are listed.

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

#### Hazard-determining components of labeling:

#### Epoxy resin

#### Hazard statements

Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects.

### · Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### • National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015

Reviewed on 01/21/2015

Trade name: EP-MV Component A

			ontd. of page 8)
	· State Right		
	25068-38-6	Epoxy resin Aquatic Chronic 2, H411; () Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	60-90%
All ingredients are listed.		ts are listed.	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

#### · Date of preparation / last revision 01/21/2015 / 3

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

#### \* \* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106