

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : EPO-TEK® H20E-FC PMF SYRINGE

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.4. Supplier's details

Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
T 978-667-3805 - F 978-663-9782
www.epotek.com

1.5. Emergency phone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410	Very toxic to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.

Precautionary statements (GHS US)

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P273 - Avoid release to the environment.
P280 - Wear protective gloves.
P302+P352 - If on skin: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P391 - Collect spillage.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Silver	CAS-No.: 7440-22-4	65 - 85*	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Epoxy phenol novolac resin*	CAS-No.: Trade Secret	10 - 30*	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 2, H411
Reactive diluent*	CAS-No.: Trade Secret	3 - 7*	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 STOT SE 3, H336
Substituted imidazole	CAS-No.: 23996-55-6	1 - 7*	Acute Tox. 4 (Oral), H302
Bisphenol A diglycidyl ether resin*	CAS-No.: Trade Secret	< 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : Components not listed are either non-hazardous or are below reportable limits.

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight.

Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Silver (7440-22-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Silver
ACGIH® TLV® TWA	0.1 mg/m ³ (Metal, dust and fume) 0.01 mg/m ³ (Soluble compounds, as Ag)
Remark (ACGIH®)	TLV® Basis: Argyria
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Silver, metal and soluble compounds (as Ag)
OSHA PEL TWA	0.01 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Silver metal, as Ag
Cal/OSHA PEL (OEL TWA)	0.01 mg/m ³

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Silver (7440-22-4)	
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Silver, metal and soluble compounds (as Ag)
NIOSH REL 10h TWA	0.01 mg/m ³
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid
Color : Silver
Odor : Mild odour
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Flammability (solid, gas) : Not applicable.
Vapor pressure : No data available
Relative vapor density at 20°C : No data available

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Silver (7440-22-4)	
LD50 oral rat	> 2000 mg/kg Source: ECHA
LD50 oral	5000 mg/kg
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LD50 dermal	2500 mg/kg
LC50 Inhalation - Rat	> 5.16 mg/l air Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)
ATE US (oral)	5000 mg/kg body weight
ATE US (dermal)	2500 mg/kg body weight

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Substituted imidazole (23996-55-6)	
ATE US (oral)	500 mg/kg body weight
Reactive diluent	
LD50 oral rat	1582 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 8 day(s))
LD50 oral	800 mg/kg
LD50 dermal	5600 mg/kg
LC50 Inhalation - Rat	> 5.1 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (mixture of vapour and aerosol), 14 day(s))
LC50 Inhalation - Rat (Dust/Mist)	5.1 mg/l/4h
LC50 Inhalation - Rat (Vapors)	> 2.68 mg/l Source: International Uniform Chemical Information Database
ATE US (oral)	800 mg/kg body weight
ATE US (dermal)	5600 mg/kg body weight
ATE US (dust, mist)	5.1 mg/l/4h
Bisphenol A diglycidyl ether resin	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 oral	11400 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
ATE US (oral)	11400 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Silver (7440-22-4)	
pH	No data available in the literature
Reactive diluent	
pH	No data available in the literature
Bisphenol A diglycidyl ether resin	
pH	No data available in the literature
Serious eye damage/irritation	: Causes serious eye damage.
Silver (7440-22-4)	
pH	No data available in the literature
Reactive diluent	
pH	No data available in the literature
Bisphenol A diglycidyl ether resin	
pH	No data available in the literature

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Reactive diluent	
NOAEL (chronic,oral,animal/male,2 years)	225 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:NTP Protocol, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	450 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:NTP Protocol, Remarks on results: other:Effect type: carcinogenicity (migrated information)
IARC group	3 - Not classifiable
Bisphenol A diglycidyl ether resin	
NOAEL (chronic,oral,animal/male,2 years)	15 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
NOAEL (chronic,oral,animal/female,2 years)	100 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)

Reproductive toxicity : Not classified

Silver (7440-22-4)	
LOAEL (animal/female, F0/P)	40 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:
NOAEL (animal/female, F0/P)	4 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:

STOT-single exposure : Not classified

Reactive diluent	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

Silver (7440-22-4)	
LOAEL (oral,rat,90 days)	125 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

Bisphenol A diglycidyl ether resin	
NOAEL (oral,rat,90 days)	50 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents), Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: other:japanese MITI guidelines for toxicity testing of chemicals

Aspiration hazard : Not classified

Silver (7440-22-4)	
Viscosity, kinematic	Not applicable (solid)

Reactive diluent	
Viscosity, kinematic	No data available in the literature

Bisphenol A diglycidyl ether resin	
Viscosity, kinematic	No data available in the literature

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Symptoms/effects after ingestion : None under normal conditions.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic) : Very toxic to aquatic life with long lasting effects.

Silver (7440-22-4)	
LC50 - Fish [1]	4.7 µg/l Test organisms (species): Pimephales promelas
LC50 - Fish [2]	89.4 µg/l Test organisms (species): Pimephales promelas
ErC50 algae	0.285 µg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Silver ion)

Reactive diluent	
LC50 - Fish [1]	56 mg/l (Equivalent or similar to OECD 203, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	> 500 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 algae	> 1000 mg/l (DIN 38412-9, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Estimated value)

Bisphenol A diglycidyl ether resin	
LC50 - Fish [1]	1.3 mg/l (96 h, Pisces, Literature study)
EC50 - Crustacea [1]	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 72h - Algae [1]	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

EPO-TEK® H20E-FC PMF SYRINGE	
Persistence and degradability	Not rapidly degradable
Silver (7440-22-4)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Substituted imidazole (23996-55-6)	
Persistence and degradability	Not rapidly degradable
Reactive diluent	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.
ThOD	1.67 g O ₂ /g substance
Epoxy phenol novolac resin	
Persistence and degradability	Biodegradability in soil: no data available.
Bisphenol A diglycidyl ether resin	
Persistence and degradability	Not readily biodegradable in water.
12.3. Bioaccumulative potential	
Silver (7440-22-4)	
BCF - Fish [1]	70 (30 day(s), Cyprinus carpio, Fresh water, Experimental value, Fresh weight)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Reactive diluent	
BCF - Other aquatic organisms [1]	3.162 l/kg (BCFBAF v3.00, Calculated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-0.566 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Not bioaccumulative.
Epoxy phenol novolac resin	
Bioaccumulative potential	No bioaccumulation data available.
Bisphenol A diglycidyl ether resin	
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
12.4. Mobility in soil	
Silver (7440-22-4)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.
Reactive diluent	
Surface tension	No data available (test not performed)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.544 – 0.811 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.
Bisphenol A diglycidyl ether resin	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Ecology - soil	No (test)data on mobility of the substance available.

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN3082	UN3082	3082	3082
14.2. Proper Shipping Name			
Environmentally hazardous substances, liquid, n.o.s. (Silver, Epoxy Phenol Novolac)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Silver)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Silver)	Environmentally hazardous substance, liquid, n.o.s. (Silver)
14.3. Transport hazard class(es)			
9	9	9	9
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
UN-No. (DOT) : UN3082

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No Limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No Limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
TDG	
UN-No. (TDG)	: UN3082

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS, 99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. may be offered for transport, handled or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport. (2) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no release of the dangerous goods that could endanger public safety.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Emergency Response Guide (ERG) Number	: 171
IMDG	
Special provision (IMDG)	: 274, 335, 375, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A
IATA	
Special provision (IATA)	: A97, A158, A197, A215
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

ERG code (IATA)

: 9L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Silver	CAS-No. 7440-22-4	65 - 85*%
--------	-------------------	-----------

Silver (7440-22-4)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

Silver (7440-22-4)

Listed on the Canadian DSL (Domestic Substances List)

Substituted imidazole (23996-55-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Reactive diluent

Listed on the Canadian DSL (Domestic Substances List)

Epoxy phenol novolac resin

Listed on the Canadian DSL (Domestic Substances List)

Bisphenol A diglycidyl ether resin

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Silver (7440-22-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Reactive diluent

Listed on INSQ (Mexican National Inventory of Chemical Substances)

EPO-TEK® H20E-FC PMF SYRINGE

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

15.3. State regulations

 **WARNING:** This product can expose you to 2-Methylimidazole, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Silver(7440-22-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Revision date : 3/17/2025
Issue date : 10/11/2024

Full text of hazard classes and H-statements	
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

Indication of changes:		
Section	Changed item	Comments
	Precautionary statements (GHS US)	Modified

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.