

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

1 Identification

- · Product identifier
- · Trade name: Pile Anchor Grout Component A
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Product description Epoxy Grout
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E-Chem, LLC

4102 El Rey Rd. SE

Albuquerque, NM 87105 Phone: 505.217.2121

Fax: 505.217.3721

Email: mail@e-chem.net Web: www.e-chem.net

Emergency telephone number:

Chemtrec at 1-800-424-9300 24 Hours

Outside the U.S., call Chemtrec collect at 703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure:

Inhalative.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Quartz (SiO2)

titanium dioxide



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 1)

· Hazard statements

Causes skin and eye irritation.

May cause cancer.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Unknown acute toxicity:

90 percent of the mixture consists of ingredient(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 1

Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*3 Health = *3

1 Fire = 1

REACTIVITY 0 Reactivity = 0

· Other hazards None known

3 Composition/information on ingredients

1317-61-9 Iron Oxide

2-12%

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 2)

· Dangerous Compon	ents:	
CAS: 25085-99-8	Bisphenol A Based Epoxy Resin Skin Irrit. 2, H315	25-50%
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO2) Carc. 1A, H350; STOT RE 1, H372; Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	25-50%
CAS: 13463-67-7	titanium dioxide ❖ Carc. 2, H351; ❖ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	2-12%

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin, eyes and clothing

Avoid breathing fume/gas/mist/vapors/spray.

Do not take internally.

Use personal protection equipment as outlined in section 8.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with occupational exposure limits:

14808-60-7 Quartz (SiO2)

PEL see Quartz listing

REL Long-term value: 0.05* mg/m³

*respirable dust; See Pocket Guide App. A

TLV | Long-term value: 0.025* mg/m³

*as respirable fraction

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

• Eye protection: Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Viscous
Color: Grey
Odor: Mild

Odor threshold: Not determined.pH-value: Not determined.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:Not determined.• Flash point:252 °C (486 °F)• Flammability (solid, gaseous):Not applicable.

• Ignition temperature: > 300 °C (> 572 °F)

· Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined. Not determined.

Vapor pressure: Not determined.

· Density:

Relative densityNot determined.Vapour densityNot determined.Evaporation rateNot determined.

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 0.0 %
Solids content: 50.0 %

• Other information No further relevant information available.

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strong acids, strong bases

Strong oxidizing agents.

· Hazardous decomposition products:

Nitrogen oxides

Oxides of carbon (COx)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye:

Irritating effect.

Causes serious eye irritation.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
14808-60-7 Quartz (SiO2)	1
13463-67-7 titanium dioxide	2B
· NTP (National Toxicology Program)	
14808-60-7 Quartz (SiO2)	K
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: Not known to be hazardous to water.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Do not allow product to reach sewage system.

It is the generators responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Non-Regulated Material

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Non-Regulated Material

· Packing group

· DOT, ADR, IMDG, IATA Non-Regulated Material

· Environmental hazards:

· *Marine pollutant:* No

· Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": -

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355	(extremely	/ hazardous	substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

· Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 01/21/2015 Printing date 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 7)

· Chemicals known to cause developmental toxicity:		
None of the ingredients are listed.		

· Carcinoger	nic categories	
· EPA (Envir	onmental Protection Agency)	
None of the	ingredients are listed.	
· TLV (Thres	hold Limit Value established by ACGIH)	
14808-60-7	Quartz (SiO2)	A2
13463-67-7	titanium dioxide	A4
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
14808-60-7	Quartz (SiO2)	
13463-67-7	titanium dioxide	

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

Quartz (SiO2)

titanium dioxide

· Hazard statements

Causes skin and eye irritation.

May cause cancer.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eve irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

If on skin: Wash with plenty of water.

Take off contaminated clothing and wash it before reuse.

Store locked up.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: Pile Anchor Grout - Component A

(Contd. of page 8)

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations	:	
The product is subject substances.	ct to be labeled according with the prevailing version of the regulations on h	azardous
· State Right to Know		
CAS: 25085-99-8	Bisphenol A Based Epoxy Resin	25-50%
	♦ Skin Irrit. 2, H315	
CAS: 14808-60-7	Quartz (SiO2)	25-50%
RTECS: VV 7330000	♦ Carc. 1A, H350; STOT RE 1, H372; ♦ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	
CAS: 13463-67-7	titanium dioxide	2-12%
	Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
CAS: 1317-61-9	Iron Oxide	2-12%
All ingredients are liste	ed.	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 01/21/2015 / 4

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Carc. 1A: Carcinogenicity, Hazard Category 1A

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106