

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

### \* 1 Identification

- **Product identifier**
- **Trade name: EP-15 Grout XP Component C**
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Product description** Epoxy Grout
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
E-Chem, LLC  
4102 El Rey Rd. SE  
Albuquerque, NM 87105  
Phone: 505.217.2121  
Fax: 505.217.3721  
Email: mail@e-chem.net  
Web: www.e-chem.net
- **Emergency telephone number:**  
Chemtrec at 1-800-424-9300 24 Hours  
Outside the U.S., call Chemtrec collect at 703-527-3887

### \* 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

STOT RE 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

GHS07

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H335 May cause respiratory irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
Quartz (SiO<sub>2</sub>)
- **Hazard statements**  
Harmful if inhaled.

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

**Trade name: EP-15 Grout XP Component C**

(Contd. of page 1)

Causes eye irritation.  
 May cause cancer.  
 May cause respiratory irritation.  
 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

**Precautionary statements**

Do not breathe dust/fume/gas/mist/vapors/spray.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Wash thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 Call a poison center/doctor if you feel unwell.  
 IF exposed or concerned: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 Get medical advice/attention if you feel unwell.  
 Store locked up.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Unknown acute toxicity:**

100 percent of the mixture consists of ingredient(s) of unknown toxicity.

**Classification system:**
**NFPA ratings (scale 0 - 4)**

**HMIS-ratings (scale 0 - 4)**


**Other hazards** None known

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous Components:**

CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO <sub>2</sub> ) ☠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	70-90%
CAS: 7727-43-7 RTECS: CR 0600000	barium sulphate, natural	15-35%

(Contd. on page 3)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

**Trade name: EP-15 Grout XP Component C**

(Contd. of page 2)

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.  
In case of unconsciousness, place patient securely on side position for transportation.
- **After skin contact:** Wash areas with soap and water.
- **After eye contact:**  
Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If swallowed and symptoms occur, consult a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**  
As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Avoid formation of dust.  
Refer to section 8
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:**  
Powder and fragments should be cleaned up using a method that will avoid the generation of dust in the workplace atmosphere. The use of a vacuum cleaner fitted with an exhaust air filter fine enough to trap the dust is recommended.  
Ensure adequate ventilation.  
Dispose contaminated material as waste according to section 13.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Thorough dedusting.  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

**Trade name: EP-15 Grout XP Component C**

(Contd. of page 3)

- **Information about protection against explosions and fires:**  
Avoid dust formation and control ignition sources.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· <b>Components with occupational exposure limits:</b>	
<b>14808-60-7 Quartz (SiO<sub>2</sub>)</b>	
PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction
<b>7727-43-7 barium sulphate, natural</b>	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 5* mg/m <sup>3</sup> *inhalable fraction; E

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing and wash before reuse.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Select glove material based on penetration times, rates of diffusion and degradation.
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

**Trade name: EP-15 Grout XP Component C**

(Contd. of page 4)

- **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:** Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Powder

**Color:** White

- **Odor:** Odorless

- **Odor threshold:** Not determined.

- **pH-value:** Not applicable.

- **Change in condition**

**Melting point/Melting range:** 1610 °C (2930 °F)

**Boiling point/Boiling range:** Not determined.

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not determined.

- **Ignition temperature:**

**Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

**Lower:** Not determined.

**Upper:** Not determined.

- **Vapor pressure:** Not applicable.

- **Density @ 20 °C (68 °F):** 2.66 g/cm<sup>3</sup> (22.198 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not applicable.

- **Evaporation rate** Not applicable.

- **Solubility in / Miscibility with**

**Water:** Soluble.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

**Dynamic:** Not applicable.

**Kinematic:** Not applicable.

- **Solvent content:**

**Organic solvents:** 0.0 %

**Solids content:** 100.0 %

- **Other information** No further relevant information available.

(Contd. on page 6)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

**Trade name: EP-15 Grout XP Component C**

(Contd. of page 5)

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** Hydrogen Fluoride
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritating effect.
- **on the eye:**  
Irritating effect.  
Causes serious eye irritation.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	1
· <b>NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients are listed.		

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

(Contd. on page 7)





**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

**Trade name: EP-15 Grout XP Component C**

(Contd. of page 7)

· **Carcinogenic categories**

· <b>EPA (Environmental Protection Agency)</b>		
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)

· **TLV (Threshold Limit Value established by ACGIH)**

14808-60-7	Quartz (SiO2)	A2
------------	---------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO2)	
------------	---------------	--

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Quartz (SiO2)

· **Hazard statements**

Harmful if inhaled.

Causes eye irritation.

May cause cancer.

May cause respiratory irritation.

Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalative.

· **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 9)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 02/19/2015

Reviewed on 02/19/2015

**Trade name: EP-15 Grout XP Component C**

(Contd. of page 8)

· <b>State Right to Know</b>		
CAS: 14808-60-7 RTECS: VV 7330000	Quartz (SiO <sub>2</sub> ) ☠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	70-90%
CAS: 7727-43-7 RTECS: CR 0600000	barium sulphate, natural	15-35%
All ingredients are listed.		

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision** 02/19/2015 / 4

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 Acute Tox. 4: Acute toxicity, Hazard Category 4  
 Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B  
 Carc. 1A: Carcinogenicity, Hazard Category 1A  
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3  
 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

· **\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services    www.msdsauthoring.com    (877) 204-9106