



**DESCRIPTION: 2037 FIBERGLASS BACKED SHEET VINYL PRESSURE SENSITIVE ADHESIVE**

Taylor 2037 is a clear set, solvent free, pressure sensitive adhesive made for the interior installation of fiberglass sheet goods over approved substrates. This adhesive is formulated to be fast drying for quick installation. Flooring may be installed up to 24 hours after initial drying if the area remains dust and dirt free. Taylor 2037 is a solvent-free, low-odor adhesive that meets all Federal, State, and local government indoor air quality regulations.

**USE TO INSTALL:** All recommended fiberglass sheet goods.

**USE OVER:** Taylor 2037 can be used over the following, above, on, or below grade concrete in the absence of excessive moisture and alkalinity, association grade plywood underlayment, association grade particleboard underlayment, existing-well bonded resilient flooring, poured in place and primed gypsum subfloors, radiant heated subfloors where surface temperatures do not exceed 85°F (20.40°C), and terrazzo. Extremely porous subfloors should be primed with Taylor 2025 prior to the application of the Taylor 2037. The pH level of concrete must be between 5 and 9 (do not install if over 9) and moisture level of concrete must be below 5 lbs./1000 sq. ft./24 hours using an anhydrous calcium chloride test kit according to ASTM F-1869 test method. Relative Humidity readings according to ASTM F-2170 should not exceed (RH) 85%. If both tests are performed the RH test is the qualifying standard.

**FLOOR PREPARATION:** Floor must be clean, level and dry. Remove all foreign substances such as wax, grease, dirt and any substance or chemical that would interfere with a good bond. Fill all holes and cracks with a cement based patching compound. Sand high spots, install underlayment grade plywood or particleboard underlayment over tongue and groove flooring to eliminate the possibility of telegraphing. The adhesive, floor covering, and area to receive resilient flooring must be maintained at a temperature of 65°-95°F (18°-35°C) and at a relative humidity of 30-60% for 72 hours before, during, and after installation. Follow the flooring manufacturer's guidelines regarding site conditions and installation. Adhesive must be completely dry before laying sheet goods (for releasable installation). Dry time will vary with fluctuations of temperature and humidity or porosity of the substrate.

**RECOMMENDED APPLICATOR / COVERAGE:** A smooth surface paint roller up to a 3/8" nap is recommended. Coverage over porous substrates is up to 350 sq. ft./gal. (8.6 sq. meters/liter). Coverage over non-porous substrates is up to 400 sq. ft./gal. (9.8 sq. meters/liter). NOTE: Coverage is approximate and may vary depending on porosity of substrate and the amount of adhesive applied.

**INSTRUCTIONS:** INSTALLATION NOTE: Adhesives applied over non-porous substrates require extended drying time.

1. Apply adhesive with recommended roller to approved substrate. It is the installer's responsibility to apply the proper amount of adhesive for the job condition.
2. Allow adhesive to dry to the point where it will not transfer to the fingers when pressed.
3. Lay flooring according to manufacturer's recommendations. Adhesive will remain tacky up to 24 hours in a clean, dust free environment.
4. For Permanent installations, install sheet goods into the wet adhesive
5. Complete the job by using the "Broom Method" or installer's choice for removing air pockets.

NOTE: Restrict heavy traffic on floor for 48 hours after installation.

**PHYSICAL PROPERTIES**

- Base: Acrylic latex/resin blend  
Appearance: Off- white, light paste  
Open Time: 30 minutes to 1 hour (depending upon environmental conditions)  
Shelf life: One year in unopened container at 70° F (21°C).  
Flammability: Non-flammable Meets NFPA Class A and UBC Class 1 as determined by ASTM E-84 and also passes the Pill Test.  
Other features: Solvent-free, freeze/thaw stable to 10°F (-12°C). Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.  
Clean up: Use soap and water to clean up while adhesive is still wet. If dried, use an approved adhesive remover or stripper.

**CAUTION:** DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

**WARRANTY INFORMATION:** This product is manufactured according to exacting quality control standards and warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Taylor Technical Services at 800-868-4583 ext. 221. You may also visit us on the web at [www.wftaylor.com](http://www.wftaylor.com) or e-mail us at [info@wftaylor.com](mailto:info@wftaylor.com).