

DP**2595**

CLOSED CELL FOAM SPRAY ADHESIVE

A premium quality, solvent based, high performance, fast drying, non-flammable, industrial pressure sensitive insulation adhesive that is water resistant and temperature resistant to 93.3° C.

Recommended Uses:

- Bonding closed cell foam insulation and fiberglass duct liner to the interior or exterior of galvanized steel, stainless steel, and aluminum HVAC duct.
- Bonding a variety of substrates including kraft backed foil, foams, fabrics, plastics, and foil jacketing to urethane foam.

Features and Benefits:

- High Temperature Resistance
- Non-Flammable After Application
- Water Resistant
- Quick Drying
- Pressure Sensitive
- Easy Application
- Exceptional Coverage
- Strong Permanent Bond
- Resistant to Oxidation and Moisture
- Portable

Directions For Use:

Surface Preparation: Surfaces should be clean, dry and free of dirt, oil and any foreign matter.

Application: Use in well ventilated area. Hold spray gun 20 to 25 cm from surface to be sprayed. Spray at 90° to surface. Apply even coats, overlapping passes slightly to insure proper coverage. Avoid excessive build-up or bubbles. Allow to dry for 2 to 4 minutes and become tacky. A second coat is recommended for porous surfaces or crucial areas. Place substrates together in exact position. Bonds instantly on contact and work cannot be repositioned. Apply even pressure along entire bonding surface.

For Permanent Bond: Apply adhesive to both surfaces and allow to dry for 2 to 4 minutes and to become tacky. Place substrates together and apply firm, even pressure along entire bonding surface.

Always point spray tip away from yourself and others. For best performance, use this product at temperatures above 10°C.

Storage: Store at temperatures below 48.9°C in an area away from direct sunlight.

Clean Up: Use mineral spirits.

Rev: v23031

Technical Data:

Color: Clear

Solvent: Methylene Chloride

Chemical Family: Synthetic polymer

Application Temperature: -1.1°C - 43.3°C

Service Temperature: -28.9°C - 93.3°C

Flammability: Non-flammable after application

Flash Point: None when dry

Bonding Time: 1 to 5 minutes depending on humidity, temperature, and substrate

Coverage: Typical spray application will yield up to 20.48 sq. m. per kilogram

Packaging: Net wt. 17.23 kg disposable spray canisters

Shelf Life: 1 Year

NOT FOR SALE IN CALIFORNIA

**KEEP OUT OF REACH OF CHILDREN
CONSULT MSDS BEFORE USING**

NOTICE TO PURCHASER: No warranties, expressed or implied are made including merchantability and/or fitness for a particular purpose. Under no circumstances shall DESIGN POLYMERICS be liable for any loss or damage arising from the purchase, use, or inability to use this product, or for any special, indirect, incidental, or consequential damages. The user may send a sample of the product to DESIGN POLYMERICS for testing. If such testing proves a product defect, the user's sole and exclusive remedy is either reimbursement of the purchase price of the product or replacement of the product. No fabricator, installer, dealer, agent, or employee of DESIGN POLYMERICS has the authority to modify the obligations or limitations of this warranty. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of a product.



A Meridian Brand

5655 E. North Belt Road, Las Vegas, NV 89115
Toll Free 800.641.0808 | Phone 714.432.0600
Fax 714.432.0660 | www.designpoly.com

Rev: v24014