

DP

Seam Sealant



A non-curing, non-skinning, solvent based pumpable butyl injection seam sealant ideal for sealing seams in Pittsburgh, Button Punch, Snap Lock and roll formed seams.

Recommended Uses:

- Pittsburgh duct seams.
- Snap Lock and Button Punch seams.
- Coil line application.
- Roll formed seams.
- Suitable for use on common construction materials including: steel, aluminum, masonry and wood.

Features and Benefits:

- **LEED V4** Qualified
- Permanently Flexible
- Non-Curing, Non-Skinning
- Non-Oxidizing
- Non-Corrosive
- Pumpable
- Withstands Joint Movement
- Excellent Water Resistance
- Excellent Cold Weather Flexibility

Directions For Use:

Uses: DP Seam Sealant may be used in metal seams where a non-curing, permanently flexible seal is required. DP Seam Sealant is ideal for sealing Pittsburgh, Button Punch and Snap Lock longitudinal seams. It may also be used in pocket seams of roll formed metal connectors.

Application: DP Seam Sealant should be injected into seams, typically by pump. Since DP Seam Sealant does not cure, seams should be closed to prevent migration of sealant.

Technical Data:

Color: Gray

Chemical Family: Butyl Rubber

Odor: Mild Solvent Odor

Solids Content: 90%

Application Temperature: 0°F - 100°F

Storage Temperature: 0°F - 100°F

Service Temperature: -40°F - 200°F

Flash Point: >100°F

Pressure Classes: Meets all SMACNA Pressure Classes

Seal Classes: Meets all SMACNA Seal Classes

Shelf Life: 2 Years

Packaging: 5 gallon pails and 54 gallon drums

VOC: ≤ 90 g/l

ASTM E-84 SURFACE BURNING CHARACTERISTICS
DP Seam Sealant applied to inorganic reinforced cement board
Flame Spread: 0 Smoke Developed: 0
Test as applied in one 0.38" wide strip at a thickness of 1/16" on center.
Sealant coverage: 2.1% of the exposed test sample area.



A Meridian Brand

5655 E. North Belt Road, Las Vegas, NV 89115
Toll Free 800.641.0808 | Phone 714.432.0600
Fax 714.432.0660 | www.designpoly.com

Rev: v24014