

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

### Identification

- · Product identifier
- · Trade name: EP15 Grout Component A
- Relevant identified uses of the substance or mixture and uses advised against
- · Product description Epoxy Grout
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E-Chem, LLC

4102 El Rey Rd. SE

Albuquerque, NM 87105 Phone: 505.217.2121

Fax: 505.217.3721

Email: mail@e-chem.net Web: www.e-chem.net

· Emergency telephone number:

Chemtrec at 1-800-424-9300 24 Hours

Outside the U.S., call Chemtrec collect at 703-527-3887

### Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



**GHS09 Environment** 

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



#### GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS07 GHS08 GHS09

· Signal word Warning

· Hazard-determining components of labeling:

Epoxy resin titanium dioxide



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

#### Trade name: EP15 Grout Component A

(Contd. of page 1)

#### · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Toxic to aquatic life with long lasting effects.

#### Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

85 percent of the mixture consists of ingredient(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 1

Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



Health = 1

1 Fire = 1

Other hazards None known

## Composition/information on ingredients

1317-61-9 Iron Oxide

2-12%

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP15 Grout Component A

(Contd. of page 2)

Dangerous Components:			
25068-38-6	Epoxy resin  Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥85%	
	titanium dioxide  Carc. 2, H351;  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	5-10%	

#### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely on side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek medical treatment.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, dry chemical, water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment:

Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

## 6 Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP15 Grout Component A

(Contd. of page 3)

## 7 Handling and storage

- · Handling:
- Precautions for safe handling

Avoid contact with skin, eyes and clothing

Do not take internally.

Use personal protection equipment as outlined in section 8.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool, dry place in tightly closed receptacles.

Store in a well ventilated place.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

#### 13463-67-7 titanium dioxide

PEL Long-term value: 15\* mg/m³

\*total dust

REL See Pocket Guide App. A

TLV Long-term value: 10 mg/m³ withdrawn from NIC

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Suitable respiratory protective device recommended.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection: Tightly sealed goggles

(Contd. on page 5)





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP15 Grout Component A

(Contd. of page 4)

### 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Grey
Odor: Mild

Odor threshold: Not determined.pH-value: Not applicable.

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:
Not determined.
Not determined.

248 °C (478 °F)
Flammability (solid, gaseous):
Not determined.

· Ignition temperature:

**Decomposition temperature:** Not determined.

· Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.Upper: Not determined.Vapor pressure: Not applicable.

• **Density @ 20 °C (68 °F):** 1.14 g/cm³ (9.513 lbs/gal)

• Relative density
• Vapour density
Not determined.
>1 (Air=1)

• Evaporation rate Slower than n-butyl acetate

· Solubility in / Miscibility with

Water: Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not applicable. **Kinematic:** Not applicable.

Other information
 No further relevant information available.

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials:

Strong oxidizing agents.

Strong acids, strong bases

(Contd. on page 6)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP15 Grout Component A

(Contd. of page 5)

**Amines** 

· Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin:

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

- · on the eye: Causes serious eye irritation.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
13463-67-7 titanium dioxide	2B
· NTP (National Toxicology Program)	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients are listed.	

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (Self-assessment): hazardous for water

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 7)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP15 Grout Component A

(Contd. of page 6)

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Do not allow product to reach sewage system.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state and federal environmental regulations.

- Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport information

· UN-Number

· **DOT** Non-Regulated Material

· **ADR, IMDG, IATA** UN3077

· UN proper shipping name

· **DOT** Non-Regulated Material

ADR
 IMDG
 UN3077 Environmentally hazardous substances, solid, n.o.s.
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S. (Epoxy resin), MARINE POLLUTANT

· IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

· Transport hazard class(es)

· DOT

· Class Non-Regulated Material

· ADR, IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles

· Label

· Packing group

· **DOT** Non-Regulated Material

· ADR, IMDG, IATA

· Environmental hazards: Product contains environmentally hazardous substances: Epoxy

resin

· Marine pollutant: Yes

Symbol (fish and tree)
Special marking (ADR):
Special marking (IATA):
Symbol (fish and tree)
Symbol (fish and tree)

Special precautions for user Warning: Miscellaneous dangerous substances and articles

· **EMS Number:** F-A,S-F

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP15 Grout Component A

(Contd. of page 7)

· Transport/Additional information:

ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 5 kg
 Code: E1

Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· UN "Model Regulation": UN3077, Environmentally hazardous substances, solid, n.o.s., 9,

Ш

#### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

13463-67-7 titanium dioxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- Carcinogenic categories
- EPA (Environmental Protection Agency)

None of the ingredients are listed.

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7 titanium dioxide

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

### Trade name: EP15 Grout Component A

(Contd. of page 8)

#### Hazard pictograms







GHS07 GHS08 GHS09

#### · Signal word Warning

#### Hazard-determining components of labeling:

Epoxy resin

titanium dioxide

#### · Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Wear eye protection / face protection.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right	· State Right to Know			
25068-38-6	Epoxy resin	≥85%		
	Aquatic Chronic 2, H411;  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317			
	titanium dioxide	5-10%		
	♦ Carc. 2, H351; ♦ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335			
1317-61-9	Iron Oxide	2-12%		
All ingredien	All ingredients are listed.			

(Contd. on page 10)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 01/21/2015 Reviewed on 01/21/2015

Trade name: EP15 Grout Component A

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of preparation / last revision 01/21/2015 / 4
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

\* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106