

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : 20-3030CLVTR

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Potting compound
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.4. Supplier's details

Epoxies, Etc.
21 Starline Way
Cranston, RI 02921
USA
T 401-946-5564
www.epoxies.com

1.5. Emergency phone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) :

- H314 - Causes severe skin burns and eye damage
- H317 - May cause an allergic skin reaction
- H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) :

- P260 - Do not breathe dusts or mists.
- P264 - Wash hands, forearms and face thoroughly after handling.
- P272 - Contaminated work clothing must not be allowed out of the workplace.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Take off immediately all contaminated clothing and wash it before reuse.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Polyaminoamide	CAS-No.: 68410-23-1	≥ 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Triethylenetetramine	CAS-No.: 112-24-3	1 – 30	Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Comments : Components not listed are either non-hazardous or are below reportable limits.

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.
Personal protection for first-aid responders.	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.
------------------	---

For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	: Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up	: Take up liquid spill into absorbent material.

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store locked up.

Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: According to product specification
Odor	: Amine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Triethylenetetramine (112-24-3)	
LD50 oral rat	1716 mg/kg body weight (BASF test, Rat, Experimental value, Oral)
LD50 oral	2500 mg/kg
LD50 dermal rabbit	1465 mg/kg body weight (BASF test, Rabbit, Experimental value, Dermal)
LD50 dermal	550 mg/kg

Polyaminoamide (68410-23-1)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method), Guideline: EU Method B.1 tris (Acute Oral Toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Skin corrosion/irritation : Causes severe skin burns.

Triethylenetetramine (112-24-3)	
pH	10 (1 %, 20 °C)
Polyaminoamide (68410-23-1)	
pH	11.08 Temp.: 25 °C Concentration: 1 vol%

Serious eye damage/irritation : Causes serious eye damage.

Triethylenetetramine (112-24-3)	
pH	10 (1 %, 20 °C)
Polyaminoamide (68410-23-1)	
pH	11.08 Temp.: 25 °C Concentration: 1 vol%

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Polyaminoamide (68410-23-1)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Aspiration hazard : Not classified

Triethylenetetramine (112-24-3)	
Viscosity, kinematic	No data available in the literature
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Triethylenetetramine (112-24-3)	
LC50 - Fish [1]	495 mg/l (96 h, Pimephales promelas, Fresh water, Literature study)
EC50 - Crustacea [1]	31.1 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Literature study)
ErC50 algae	27 mg/l
NOEC chronic algae	0.468 mg/l
Polyaminoamide (68410-23-1)	
LC50 - Fish [1]	7.07 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	5.18 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	4.11 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

20-3030CLVTR	
Persistence and degradability	Not rapidly degradable
Triethylenetetramine (112-24-3)	
Persistence and degradability	Not readily biodegradable in water.
Polyaminoamide (68410-23-1)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Triethylenetetramine (112-24-3)	
Partition coefficient n-octanol/water (Log Pow)	-2.65 (Estimated value, KOWWIN)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Triethylenetetramine (112-24-3)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.885 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN2735	UN2735	2735	2735
14.2. Proper Shipping Name			
Polyamines, liquid, corrosive, n.o.s. (Triethylenetetramine ; Polyaminoamide)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Triethylenetetramine ; Polyaminoamide)	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Triethylenetetramine ; Polyaminoamide)	Polyamines, liquid, corrosive, n.o.s. (Triethylenetetramine ; Polyaminoamide)
14.3. Transport hazard class(es)			
8	8	8	8
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN2735

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 52 - Stow "separated from" acids
TDG	
UN-No. (TDG)	: UN2735
TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L
Emergency Response Guide (ERG) Number	: 153
IMDG	
Special provision (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Segregation (IMDG)	: SGG18, SG35
Properties and observations (IMDG)	: Colorless to yellowish liquids or solutions with a pungent odor. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

IATA

Special provision (IATA)	: A3, A803
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
ERG code (IATA)	: 8L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Triethylenetetramine (112-24-3)

Listed on the Canadian DSL (Domestic Substances List)

Polyaminoamide (68410-23-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Triethylenetetramine (112-24-3)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Polyaminoamide (68410-23-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

20-3030CLVTR

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Component	State or local regulations
Triethylenetetramine(112-24-3)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Issue date : 8/13/2025

Full text of hazard classes and H-statements	
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.