

TABLE 1: Crack injection estimating guide for CRACKBOND LR-321 LV, SLV and TXO^{1,2,3}

Approximate Coverage Rates Linear Feet (Linear Meters)					
Crack Width in. (cm)	Crack Depth in. (cm)	Packaging Size			
		6 fl. oz. (177 ml)	16 fl. oz. (473 ml)	102 fl. oz. (3.2 L)	3 Gal (56.8L)
1/400 in. or 0.0025 (0.006)	4 (10.2)	75.2 (22.9)	225.6 (68.8)	1,534 (467.6)	5,775 (1760.3)
	6 (15.2)	50.1 (15.3)	150.4 (45.8)	1,023 (311.7)	3,850 (1173.5)
	8 (20.3)	37.6 (11.5)	112.8 (34.4)	767 (233.8)	2,888 (880.1)
	10 (25.4)	30.1 (9.2)	90.2 (27.5)	614 (187.0)	2,310 (704.1)
1/200 in. or 0.0050 (0.013)	4 (10.2)	37.6 (11.5)	112.8 (34.4)	767 (233.8)	2,888 (880.1)
	6 (15.2)	25.1 (7.6)	75.2 (22.9)	511 (155.9)	1,925 (586.8)
	8 (20.3)	18.8 (5.7)	56.4 (17.2)	384 (116.9)	1,444 (440.1)
	10 (25.4)	15.0 (4.6)	45.1 (13.8)	307 (93.5)	1,155 (352.1)
1/64 in. or 0.0156 (0.040)	4 (10.2)	12.1 (3.7)	36.2 (11.0)	246 (74.9)	926 (282.1)
	6 (15.2)	8.0 (2.4)	24.1 (7.3)	164 (50.0)	617 (188.1)
	8 (20.3)	6.0 (1.8)	18.1 (5.5)	123 (37.5)	463 (141.0)
	10 (25.4)	4.8 (1.5)	14.5 (4.4)	98 (30.0)	370 (112.8)
1/32 in. or 0.0313 (0.079)	4 (10.2)	6.0 (1.8)	18.0 (5.5)	123 (37.4)	462 (140.8)
	6 (15.2)	4.0 (1.2)	12.0 (3.7)	82 (24.9)	308 (93.9)
	8 (20.3)	3.0 (0.9)	9.0 (2.8)	61 (18.7)	231 (70.4)
	10 (25.4)	2.4 (0.7)	7.2 (2.2)	49 (15.0)	185 (56.3)
1/16 in. or 0.0625 (0.159)	4 (10.2)	3.0 (0.9)	9.0 (2.8)	61 (18.7)	231 (70.4)
	6 (15.2)	2.0 (0.6)	6.0 (1.8)	41 (12.5)	154 (46.9)
	8 (20.3)	1.5 (0.5)	4.5 (1.4)	31 (9.4)	116 (35.2)
	10 (25.4)	1.2 (0.4)	3.6 (1.1)	25 (7.5)	92 (28.2)
1/8 in. or 0.1250 (0.318)	4 (10.2)	1.5 (0.5)	4.5 (1.4)	31 (9.4)	116 (35.2)
	6 (15.2)	1.0 (0.3)	3.0 (0.9)	20 (6.2)	77 (23.5)
	8 (20.3)	0.8 (0.2)	2.3 (0.7)	15 (4.7)	58 (17.6)
	10 (25.4)	0.6 (0.2)	1.8 (0.6)	12 (3.7)	46 (14.1)

1. Values are approximate and may vary depending on waste, concrete and user technique.

2. Capping cracks using MIRACLE BOND REPAIR EPOXY in a 9 oz. cartridge will cap approximately 7 linear feet (2.1 linear meters) of a crack with a 3/16 in. (4.7 mm) thick by 1 in. (25.4 mm) wide bead.

3. Capping cracks using CRACKBOND EPOXY REPAIR PASTE in a 21.2 oz. cartridge will cap approximately 16 linear feet (4.8 linear meters) of a crack with a 3/16 in. (4.7 mm) thick by 1 in. (25.4 mm) wide bead.